

PSEA: Population-Specific Expression Analysis

*Alexandre Kuhn*¹

¹alexandre.m.kuhn@gmail.com

April 27, 2020

Contents

1	Introduction	1
2	Reference signals	2
3	Principle of PSEA.	3
4	Deconvolution of expression profiles	6
5	Session Information	8

1 Introduction

The characterization of molecular changes in diseased tissues can provide crucial information about pathophysiological mechanisms and is important for the development of targeted drugs and therapies. However, many disease processes are accompanied by changes of cell populations due to cell migration, proliferation or death. Identification of key molecular events can thus be overshadowed by confounding changes in tissue composition.

To address the issue of confounding between cell population composition and cellular expression changes, we developed Population-Specific Expression Analysis (PSEA) [1, 2]. This method works by exploiting linear regression modeling of queried expression levels to the abundance of each cell population. Since a direct measure of population size is often unobtainable (e.g. from human clinical or autopsy samples), PSEA instead tracks relative cell population size via levels of mRNAs expressed in a single population only. Thus, a reference measure is constructed for each cell population by averaging expression data for cell-type-specific mRNAs derived from the same expression profile.

Here we will demonstrate some of the functionalities in the PSEA package. We will first generate reference signals and deconvolve individual transcripts to illustrate the method. We will then show how to apply PSEA to entire expression profiles. Let us start by loading the package

```
> library(PSEA)
```

We have included expression data obtained from brain samples of 41 individuals as well as their phenotypes, i.e. control and Huntington's disease (HD) (the full data is deposited at <http://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE3790>)




Figure 1: Component-plus-residual plots showing deconvolved neuronal, astrocytic, oligodendrocytic and microglial expression of Calceineurin A in control samples

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	103.60	918.19	0.113	0.911
neuron_reference	4604.72	505.05	9.117	2.89e-09 ***
astro_reference	-21.35	385.48	-0.055	0.956
oligo_reference	-267.37	276.29	-0.968	0.343
micro_reference	-288.05	491.12	-0.587	0.563

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 483.2 on 24 degrees of freedom

Multiple R-squared: 0.818, Adjusted R-squared: 0.7877

F-statistic: 26.97 on 4 and 24 DF, p-value: 1.428e-08

There is indeed a strong correlation between the expression of Calceineurin A and the neuronal reference signal (neuron_reference), as indicated by the highly significant ($p = 2.89 \times 10^{-9}$) coefficient of this reference signal. This reflects the fact that Calceineurin A is expressed in neurons. The coefficient of the neuronal reference signal (4605) represents the normalized neuron-specific expression of this gene. It is the slope of the regression line in the first panel of Figure 1.

Next, we test for a difference in neuron-specific expression in HD versus control samples and model the expression of Calceineurin A as a combination of the neuronal reference signal and the neuron-specific group difference (neuronal interaction regressor)

```
> model2 <- lm(expression["202429_s_at",] ~ neuron_reference + neuron_difference)
```

The fitted model is visualized as follows

```
> crplot(model2, "neuron_reference", g="neuron_difference")
```




Figure 2: Component-plus-residual plot showing deconvolved neuron-specific expression in controls (black) and HD subjects (red)

It shows that neuronal expression of Calcineurin A is decreased in HD (red) compared to control (black) samples, as indicated by the smaller slope of the regression line for HD samples (Figure 2). The fit summary

```
> summary(model2)
```

Call:

```
lm(formula = expression["202429_s_at", ] ~ neuron_reference + neuron_difference)
```

Residuals:

Min	1Q	Median	3Q	Max
-757.06	-317.30	-49.51	324.19	1109.58

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	-387.8	379.6	-1.021	0.313490
neuron_reference	4548.5	345.5	13.165	9.82e-16 ***
neuron_difference	-831.5	215.5	-3.859	0.000428 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 435.6 on 38 degrees of freedom

Multiple R-squared: 0.8953, Adjusted R-squared: 0.8898

F-statistic: 162.5 on 2 and 38 DF, p-value: < 2.2e-16

reveals that the coefficient of the group-specific difference is negative (-831) and highly significant (0.0004). This reflects the fact that Calcineurin A expression is downregulated in neurons of HD patients. Normalized neuron-specific expression in the control group is given

by the coefficient of the neuronal reference signal (4548) and normalized neuron-specific expression in HD is given by the sum of both coefficients (4548 - 831 = 3117). These two coefficients are the slopes of the regression lines in Figure 2. The fold change in neuronal expression can thus be easily calculated using the fitted coefficients

```
> foldchange <- (model2$coefficients[2] + model2$coefficients[3]) / model2$coefficients[2]
```

Finally, note that the model fit is excellent (adjusted $R^2 = 0.89$) which means that most of the variations in Calcineurin A expression across samples is explained by the variation in neuronal abundance (as measured by the neuronal reference signal) and the group-specific difference between HD and control samples.

4 Deconvolution of expression profiles

An important aspect of PSEA (and statistical model building in general) is how to choose the parameters to include in the model. Indeed, adding more parameters will always result in a better overall fit (and increase the coefficient of determination R^2) but will not necessarily result in a more informative or predictive expression model. The goal thus is to reach a balance between the number of parameters in the model and how much of the data it can account for.

The stepwise method is a classical approach to model selection. It can be applied to model building for PSEA (as in [2]) and `swlm` provides a simple wrapper function that performs stepwise model selection on every transcript in turn (see `?swlm` for details). However, it might not be computationally efficient when considering a large number of transcripts and might lack flexibility in model specification. Here we will illustrate the "all-subset" approach used in [1] in more details.

We will restrict the statistical models under consideration to those that provide appropriate gene expression models. In the present case, the small number of samples also makes it unlikely to robustly fit highly complex expression models and we might want to exclude models containing several parameters coding for expression changes in different cell populations. The function `lmfitst` efficiently fits a set of models to every transcript in an expression profile and selects the best model for each transcript.

We first need to define a model matrix containing all possible parameters as columns (including an intercept as the first column)

```
> model_matrix <- fmm(cbind(neuron_reference, astro_reference,
+                           oligo_reference, micro_reference), groups)
```

We then specify the subset of models that we want to fit as a list. Each list item represents a model by specifying the included parameters (as their column indices in the model matrix). The function `em_quantvg` enumerates models automatically

```
> model_subset <- em_quantvg(c(2,3,4,5), tnv=4, ng=2)
```

For instance, the 17th model in the list,

```
> model_subset[[17]]
[1] 1 2 6
```

PSEA

represents an expression model containing an intercept (column 1 in `model_matrix`), the neuronal reference signal (column 2) and the neuron-specific expression change (column 6).

We can then fit each probeset in the expression profile with all models in the subset and for each probeset select the best expression model (using AIC as a criterion)

```
> models <- lmfittst(t(expression), model_matrix, model_subset)
```

The function `lmfittst` returns two lists. The first contains the identity of the best and next best models for each transcript. The second contains details of the (fitted) best model for each transcript. For PPP3CA, for instance, the selected expression model contains the parameters corresponding to neuronal expression and neuron-specific expression change (as we previously manually worked out)

```
> summary(models[[2]][["202429_s_at"]])
```

Call:

```
lm(formula = y[, x] ~ ., data = data.frame(fmdl[, st[[wcrto1[x]]][-1]]))
```

Residuals:

Min	1Q	Median	3Q	Max
-757.06	-317.30	-49.51	324.19	1109.58

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
1	-387.8	379.6	-1.021	0.313490
2	4548.5	345.5	13.165	9.82e-16 ***
6	-831.5	215.5	-3.859	0.000428 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 435.6 on 38 degrees of freedom

Multiple R-squared: 0.8953, Adjusted R-squared: 0.8898

F-statistic: 162.5 on 2 and 38 DF, p-value: < 2.2e-16

We can then check that the selected models provide appropriate expression models and focus on transcripts with features of interest like e.g. expression in a particular cell population or significant population-specific expression change. To this end, we extract the coefficients, p-values and adjusted R^2 for the selected models using a few ad hoc functions

```
> regressor_names <- as.character(1:9)
> coefficients <- coefmat(models[[2]], regressor_names)
> pvalues <- pvalmat(models[[2]], regressor_names)
> models_summary <- lapply(models[[2]], summary)
> adjusted_R2 <- slt(models_summary, 'adj.r.squared')
```

We use specific criteria to filter satisfactory expression models (e.g. sufficient R^2 and small intercept, see [1] for more details)

```
> average_expression <- apply(expression, 1, mean)
> filter <- adjusted_R2 > 0.6 & coefficients[,1] / average_expression < 0.5
```

We can now list transcripts that we would like to focus on (excluding transcripts used to construct reference signals). Here we for instance identify transcripts with significant expression in oligodendrocytes (corresponding to column 4 in `model_matrix`). There is one such transcript in our small example dataset

```
> filter[match(unlist(c(neuron_probesets, astro_probesets, oligo_probesets, micro_probesets)),
+             rownames(expression))] <- FALSE
> select <- which(filter & pvalues[, 4] < 0.05)
> coefficients[select,]

  coef.1  coef.2  coef.3  coef.4  coef.5  coef.6  coef.7  coef.8
19.38714    NA    NA 69.27515    NA    NA    NA 33.26382
  coef.9
    NA
```

5 Session Information

The version number of R and packages loaded for generating the vignette were:

```
R version 4.0.0 (2020-04-24)
Platform: x86_64-pc-linux-gnu (64-bit)
Running under: Ubuntu 18.04.4 LTS

Matrix products: default
BLAS: /home/biocbuild/bbs-3.11-bioc/R/lib/libRblas.so
LAPACK: /home/biocbuild/bbs-3.11-bioc/R/lib/libRlapack.so

locale:
 [1] LC_CTYPE=en_US.UTF-8      LC_NUMERIC=C
 [3] LC_TIME=en_US.UTF-8      LC_COLLATE=C
 [5] LC_MONETARY=en_US.UTF-8  LC_MESSAGES=en_US.UTF-8
 [7] LC_PAPER=en_US.UTF-8     LC_NAME=C
 [9] LC_ADDRESS=C             LC_TELEPHONE=C
[11] LC_MEASUREMENT=en_US.UTF-8 LC_IDENTIFICATION=C

attached base packages:
[1] stats    graphics  grDevices  utils      datasets  methods   base

other attached packages:
[1] PSEA_1.22.0

loaded via a namespace (and not attached):
 [1] Rcpp_1.0.4.6      digest_0.6.25    MASS_7.3-51.6
 [4] evaluate_0.14    rlang_0.4.5      rmarkdown_2.1
 [7] BiocStyle_2.16.0 tools_4.0.0      Biobase_2.48.0
[10] xfun_0.13        yaml_2.2.1       parallel_4.0.0
```



```
[13] compiler_4.0.0      BiocGenerics_0.34.0 BiocManager_1.30.10
[16] htmltools_0.4.0     knitr_1.28
```

References

- [1] Alexandre Kuhn, Doris Thu, Henry J Waldvogel, Richard LM Faull, and Ruth Luthi-Carter. Population-specific expression analysis (psea) reveals molecular changes in diseased brain. *Nat. Methods*, 9(8):945–947, 2011. URL: <http://www.nature.com/nmeth/journal/v8/n11/full/nmeth.1710.html>, doi:10.1038/nmeth.1710.
- [2] Alexandre Kuhn, Azad Kumar, Alexandre Beilina, Allissa Dillman, Mark R Cookson, and Andrew B Singleton. Cell population-specific expression analysis of human cerebellum. *BMC Genomics*, 13(610), 2012. URL: <http://www.biomedcentral.com/1471-2164/13/610>, doi:doi:10.1186/1471-2164-13-610.