

# Package ‘SNPRelate’

April 23, 2016

**Type** Package

**Title** Parallel Computing Toolset for Relatedness and Principal Component Analysis of SNP Data

**Version** 1.4.2

**Date** 2016-01-17

**Depends** R (>= 2.14), gdsfmt (>= 1.5.9)

**LinkingTo** gdsfmt

**Suggests** parallel, RUnit, knitr, MASS, BiocGenerics

**Enhances** SeqArray

**Description** Genome-wide association studies (GWAS) are widely used to investigate the genetic basis of diseases and traits, but they pose many computational challenges. We developed an R package SNPRelate to provide a binary format for single-nucleotide polymorphism (SNP) data in GWAS utilizing CoreArray Genomic Data Structure (GDS) data files. The GDS format offers the efficient operations specifically designed for integers with two bits, since a SNP could occupy only two bits. SNPRelate is also designed to accelerate two key computations on SNP data using parallel computing for multi-core symmetric multiprocessing computer architectures: Principal Component Analysis (PCA) and relatedness analysis using Identity-By-Descent measures. The SNP GDS format in this package is also used by the GWASTools package with the support of S4 classes and generic functions. The extended GDS format is implemented in the SeqArray package to support the storage of single nucleotide variation (SNV), insertion/deletion polymorphism (indel) and structural variation calls.

**License** GPL-3

**VignetteBuilder** knitr

**URL** <http://github.com/zhengxwen/SNPRelate>,  
<http://corearray.sourceforge.net/tutorials/SNPRelate/>

**BugReports** <http://github.com/zhengxwen/SNPRelate/issues>

**biocViews** Infrastructure, Genetics, StatisticalMethod,  
PrincipalComponent

**NeedsCompilation** yes

**Author** Xiuwen Zheng [aut, cre, cph],  
Stephanie Gogarten [ctb],  
Cathy Laurie [ctb],  
Bruce Weir [ctb, ths]

**Maintainer** Xiuwen Zheng <zhengx@u.washington.edu>

## R topics documented:

SNPRelate-package . . . . .	3
hapmap_geno . . . . .	5
snpGDSAdmixProp . . . . .	6
snpGDSAlleleSwitch . . . . .	8
snpGDSApartSelection . . . . .	9
snpGDSBED2GDS . . . . .	10
snpGDSClose . . . . .	12
snpGDSCombineGeno . . . . .	13
snpGDSCreateGeno . . . . .	14
snpGDSCreateGenoSet . . . . .	16
snpGDSCutTree . . . . .	18
snpGDSDiss . . . . .	20
snpGDSDrawTree . . . . .	22
snpGDSEIGMIX . . . . .	24
snpGDSErrMsg . . . . .	26
snpGDSExampleFileName . . . . .	27
SNPGDSFileClass . . . . .	27
snpGDSFst . . . . .	28
snpGDSGDS2BED . . . . .	29
snpGDSGDS2Eigen . . . . .	31
snpGDSGDS2PED . . . . .	32
snpGDSGEN2GDS . . . . .	33
snpGDSGetGeno . . . . .	35
snpGDSGRM . . . . .	36
snpGDSHCluster . . . . .	38
snpGDSHWE . . . . .	39
snpGDSIBDKING . . . . .	40
snpGDSIBDMLE . . . . .	43
snpGDSIBDMLELogLik . . . . .	46
snpGDSIBDMoM . . . . .	48
snpGDSIBDSelection . . . . .	51
snpGDSIBS . . . . .	52
snpGDSIBSNum . . . . .	54
snpGDSIndInb . . . . .	55
snpGDSIndInbCoef . . . . .	56
snpGDSLDMat . . . . .	58

snpgdsLDpair . . . . .	59
snpgdsLDpruning . . . . .	61
snpgdsOpen . . . . .	63
snpgdsOption . . . . .	64
snpgdsPairIBD . . . . .	65
snpgdsPairIBDMLELogLik . . . . .	67
snpgdsPairScore . . . . .	70
snpgdsPCA . . . . .	72
snpgdsPCACorr . . . . .	75
snpgdsPCASampLoading . . . . .	77
snpgdsPCASNPLoading . . . . .	78
snpgdsPED2GDS . . . . .	80
snpgdsSampMissRate . . . . .	81
snpgdsSelectSNP . . . . .	82
snpgdsSlidingWindow . . . . .	83
snpgdsSNPList . . . . .	85
snpgdsSNPListClass . . . . .	86
snpgdsSNPListIntersect . . . . .	86
snpgdsSNPListStrand . . . . .	87
snpgdsSNPRateFreq . . . . .	88
snpgdsSummary . . . . .	89
snpgdsTranspose . . . . .	90
snpgdsVCF2GDS . . . . .	91
snpgdsVCF2GDS_R . . . . .	94

**Index****97**

SNPRelate-package

*Parallel Computing Toolset for Genome-Wide Association Studies***Description**

Genome-wide association studies are widely used to investigate the genetic basis of diseases and traits, but they pose many computational challenges. We developed SNPRelate (R package for multi-core symmetric multiprocessing computer architectures) to accelerate two key computations on SNP data: principal component analysis (PCA) and relatedness analysis using identity-by-descent measures. The kernels of our algorithms are written in C/C++ and highly optimized.

**Details**

Package: SNPRelate  
 Type: Package  
 License: GPL version 3  
 Depends: gdsfmt (>= 1.0.4)

The genotypes stored in GDS format can be analyzed by the R functions in SNPRelate, which utilize the multi-core feature of machine for a single computer.

Webpage: <http://github.com/zhengxwen/SNPRelate>, <http://corearray.sourceforge.net/>

Tutorial: <http://corearray.sourceforge.net/tutorials/SNPRelate/>

### Author(s)

Xiuwen Zheng <zhengxwen@gmail.com>

### References

Zheng X, Levine D, Shen J, Gogarten SM, Laurie C, Weir BS. A High-performance Computing Toolset for Relatedness and Principal Component Analysis of SNP Data. *Bioinformatics* (2012); doi: 10.1093/bioinformatics/bts610

### Examples

```
#####
# Convert the PLINK BED file to the GDS file
#

# PLINK BED files
bed.fn <- system.file("extdata", "plinkhapmap.bed.gz", package="SNPRelate")
fam.fn <- system.file("extdata", "plinkhapmap.fam.gz", package="SNPRelate")
bim.fn <- system.file("extdata", "plinkhapmap.bim.gz", package="SNPRelate")

# convert
snpGDSBED2GDS(bed.fn, fam.fn, bim.fn, "HapMap.gds")

#####
# Principal Component Analysis
#

# open
genofile <- snpGDSOpen("HapMap.gds")

RV <- snpGDSPCA(genofile)
plot(RV$eigenvect[,2], RV$eigenvect[,1], xlab="PC 2", ylab="PC 1",
      col=rgb(0,0,150, 50, maxColorValue=255), pch=19)

# close the file
snpGDSClose(genofile)

#####
# Identity-By-Descent (IBD) Analysis
#

# open
genofile <- snpGDSOpen(snpGDSExampleFileName())
```

```

RV <- snpgdsIBDMoM(genofile)
flag <- lower.tri(RV$k0)
plot(RV$k0[flag], RV$k1[flag], xlab="k0", ylab="k1",
      col=rgb(0,0,150, 50, maxColorValue=255), pch=19)
abline(1, -1, col="red", lty=4)

# close the file
snpgdsClose(genofile)

#####
# Identity-By-State (IBS) Analysis
#

# open
genofile <- snpgdsOpen(snpgdsExampleFileName())

RV <- snpgdsIBS(genofile)
m <- 1 - RV$ibs
colnames(m) <- rownames(m) <- RV$sample.id
GeneticDistance <- as.dist(m[1:45, 1:45])
HC <- hclust(GeneticDistance, "ave")
plot(HC)

# close the file
snpgdsClose(genofile)

#####
# Linkage Disequilibrium (LD) Analysis
#

# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

snpset <- read.gdsn(index.gdsn(genofile, "snp.id"))[1:200]
L1 <- snpgdsLDmat(genofile, snp.id=snpset, method="composite", slide=-1)

# plot
image(abs(L1$LD), col=terrain.colors(64))

# close the file
snpgdsClose(genofile)

```

---

hapmap\_gen0

*SNP genotypes of HapMap samples*


---

### Description

A list object including the following components:

`sample.id` – a vector of sample ids;  
`snp.id` – a vector of SNP ids;  
`snp.position` – a vector of SNP positions;  
`snp.chromosome` – a vector of chromosome indices;  
`snp.allele` – a character vector of “reference / non-reference”;  
`genotype` – a “# of SNPs” X “# of samples” genotype matrix.

### Usage

```
hapmap_geno
```

### Value

A list

---

snpGdsAdmixProp	<i>Estimate ancestral proportions from the eigen-analysis</i>
-----------------	---

---

### Description

Estimate ancestral (admixture) proportions based on the eigen-analysis.

### Usage

```
snpGdsAdmixProp(eigobj, groups, bound=FALSE)
```

### Arguments

<code>eigobj</code>	an object of <code>snpGdsEigMixClass</code> from <a href="#">snpGdsEIGMIX</a> , or an object of <code>snpGdsPCAClass</code> from <a href="#">snpGdsPCA</a>
<code>groups</code>	a list of sample IDs, such like <code>groups = list(CEU = c("NA0101", "NA1022", ...), YRI = c(...))</code>
<code>bound</code>	if TRUE, the estimates are bounded so that no component < 0 or > 1, and the sum of proportions is one

### Details

The minor allele frequency and missing rate for each SNP passed in `snp.id` are calculated over all the samples in `sample.id`.

### Value

Return a `snpGdsEigMixClass` object, and it is a list:

<code>sample.id</code>	the sample ids used in the analysis
<code>snp.id</code>	the SNP ids used in the analysis
<code>eigenval</code>	eigenvalues
<code>eigenvect</code>	eigenvectors, "# of samples" x "eigen.cnt"
<code>ibdmat</code>	the IBD matrix

**Author(s)**

Xiuwen Zheng

**References**

Zheng X, Weir BS. Eigenanalysis on SNP Data with an Interpretation of Identity by Descent. 2015. Theoretical Population Biology.

**See Also**

[snpGDS\\_EIGMIX](#), [snpGDS\\_PCA](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGDSOpen(snpGDSExampleFileName())

# get population information
# or pop_code <- scan("pop.txt", what=character())
# if it is stored in a text file "pop.txt"
pop_code <- read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))

# get sample id
samp.id <- read.gdsn(index.gdsn(genofile, "sample.id"))

# run eigen-analysis
RV <- snpGDS_EIGMIX(genofile)

# eigenvalues
RV$eigenval

# make a data.frame
tab <- data.frame(sample.id = samp.id, pop = factor(pop_code),
  EV1 = RV$eigenvect[,1], # the first eigenvector
  EV2 = RV$eigenvect[,2], # the second eigenvector
  stringsAsFactors = FALSE)
head(tab)

# draw
plot(tab$EV2, tab$EV1, col=as.integer(tab$pop),
  xlab="eigenvector 2", ylab="eigenvector 1")
legend("topleft", legend=levels(tab$pop), pch="o", col=1:4)

# define groups
groups <- list(CEU = samp.id[pop_code == "CEU"],
  YRI = samp.id[pop_code == "YRI"],
  CHB = samp.id[is.element(pop_code, c("HCB", "JPT"))])

prop <- snpGDSAdmixProp(RV, groups=groups)

# draw
```

```

plot(prop[, "YRI"], prop[, "CEU"], col=as.integer(tab$pop),
     xlab = "Admixture Proportion from YRI",
     ylab = "Admixture Proportion from CEU")
abline(v=0, col="gray25", lty=2)
abline(h=0, col="gray25", lty=2)
abline(a=1, b=-1, col="gray25", lty=2)
legend("topright", legend=levels(tab$pop), pch="o", col=1:4)

# run eigen-analysis
RV <- snpgdsEIGMIX(genofile, sample.id=samp.id[pop_code=="JPT"])
z <- RV$ibdmat

mean(c(z))
mean(diag(z))

# close the genotype file
snpgdsClose(genofile)

```

---

snpgdsAlleleSwitch      *Allele-switching*

---

## Description

Switch alleles according to the reference if needed.

## Usage

```
snpgdsAlleleSwitch(gdsobj, A.allele, verbose=TRUE)
```

## Arguments

gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
A.allele	characters, referring to A allele
verbose	if TRUE, show information

## Value

A logical vector with TRUE indicating allele-switching and NA when it is unable to determine. NA occurs when A.allele = NA or A.allele is not in the list of alleles.

## Author(s)

Xiuwen Zheng



**Examples**

```

# the file name of SNP GDS
(fn <- snpGDSExampleFileName())

# copy the file
file.copy(fn, "test.gds", overwrite=TRUE)

# open the SNP GDS file
genofile <- snpGDSOpen("test.gds", readonly=FALSE)

# allelic information
allele <- read.gdsn(index.gdsn(genofile, "snp.allele"))
allele.list <- strsplit(allele, "/")

A.allele <- sapply(allele.list, function(x) { x[1] })
B.allele <- sapply(allele.list, function(x) { x[2] })

set.seed(1000)
flag <- rep(FALSE, length(A.allele))
flag[sample.int(length(A.allele), 50, replace=TRUE)] <- TRUE

A.allele[flag] <- B.allele[flag]
A.allele[sample.int(length(A.allele), 10, replace=TRUE)] <- NA
table(A.allele, exclude=NULL)

# allele switching
z <- snpGDSAlleleSwitch(genofile, A.allele)

table(z, exclude=NULL)

# close the file
snpGDSClose(genofile)

# delete the temporary file
unlink("test.gds", force=TRUE)

```

---

snpGDSApartSelection    *Select SNPs with a basepair distance*

---

**Description**

Randomly selects SNPs for which each pair is at least as far apart as the specified basepair distance.

**Usage**

```

snpGDSApartSelection(chromosome, position, min.dist=100000,
  max.n.snp.perchr=-1, verbose=TRUE)

```

**Arguments**

chromosome	chromosome codes
position	SNP positions in base pair
min.dist	A numeric value to specify minimum distance required (in basepairs)
max.n.snp.perchr	A numeric value specifying the maximum number of SNPs to return per chromosome, "-1" means no number limit
verbose	if TRUE, show information

**Value**

A logical vector indicating which SNPs were selected.

**Author(s)**

Xiuwen Zheng

**See Also**

[snpgdsLDpruning](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())
genofile

chr <- read.gdsn(index.gdsn(genofile, "snp.chromosome"))
pos <- read.gdsn(index.gdsn(genofile, "snp.position"))

set.seed(1000)
flag <- snpgdsApartSelection(chr, pos, min.dist=250000, verbose=TRUE)
table(flag)

# close the genotype file
snpgdsClose(genofile)
```

**Description**

Convert a PLINK binary ped file to a GDS file.

**Usage**

```
snpGDSBED2GDS(bed.fn, fam.fn, bim.fn, out.gdsfn, family=FALSE,
  snpfirstdim=NA, compress.annotation="ZIP_RA.max", compress.geno="",
  option=NULL, cvt.chr=c("int", "char"), cvt.snpid=c("auto", "int"),
  verbose=TRUE)
```

**Arguments**

<i>bed.fn</i>	the file name of binary file, genotype information
<i>fam.fn</i>	the file name of first six columns of ".ped"
<i>bim.fn</i>	the file name of extended MAP file: two extra columns = allele names
<i>out.gdsfn</i>	the output GDS file
<i>family</i>	if TRUE, to include family information in the sample annotation
<i>snpfirstdim</i>	if TRUE, genotypes are stored in the individual-major mode, (i.e, list all SNPs for the first individual, and then list all SNPs for the second individual, etc); NA, the dimension is determined by the BED file
<i>compress.annotation</i>	the compression method for the GDS variables, except "genotype"; optional values are defined in the function <code>add.gdsn</code>
<i>compress.geno</i>	the compression method for "genotype"; optional values are defined in the function <code>add.gdsn</code>
<i>option</i>	NULL or an object from <code>snpGDSOption</code> , see details
<i>cvt.chr</i>	"int" – chromosome code in the GDS file is integer; "char" – chromosome code in the GDS file is character
<i>cvt.snpid</i>	"int" – to create an integer <code>snp.id</code> starting from 1; "auto" – if SNP IDs in the PLINK file are not unique, to create an integer <code>snp.id</code> , otherwise to use SNP IDs for <code>snp.id</code>
<i>verbose</i>	if TRUE, show information

**Details**

GDS – Genomic Data Structures, the extended file name used for storing genetic data, and the file format is used in the `gdsfmt` package.

BED – the PLINK binary ped format.

The user could use `option` to specify the range of code for autosomes. For humans there are 22 autosomes (from 1 to 22), but dogs have 38 autosomes. Note that the default settings are used for humans. The user could call `option = snpGDSOption(autosome.end=38)` for importing the BED file of dog. It also allow define new chromosome coding, e.g., `option = snpGDSOption(Z=27)`.

**Value**

Return the file name of GDS format with an absolute path.

**Author(s)**

Xiuwen Zheng

## References

Purcell S, Neale B, Todd-Brown K, Thomas L, Ferreira MAR, Bender D, Maller J, Sklar P, de Bakker PIW, Daly MJ & Sham PC. 2007. PLINK: a toolset for whole-genome association and population-based linkage analysis. *American Journal of Human Genetics*, 81.

<http://corearray.sourceforge.net/>

## See Also

[snpgdsOption](#), [snpgdsPED2GDS](#), [snpgdsGDS2PED](#)

## Examples

```
# PLINK BED files
bed.fn <- system.file("extdata", "plinkhapmap.bed.gz", package="SNPRelate")
fam.fn <- system.file("extdata", "plinkhapmap.fam.gz", package="SNPRelate")
bim.fn <- system.file("extdata", "plinkhapmap.bim.gz", package="SNPRelate")

# convert
snpgdsBED2GDS(bed.fn, fam.fn, bim.fn, "HapMap.gds")

# open
genofile <- snpgdsOpen("HapMap.gds")
genofile

# close
snpgdsClose(genofile)

# delete the temporary file
unlink("HapMap.gds", force=TRUE)
```

---

snpgdsClose

*Close the SNP GDS File*

---

## Description

Close the SNP GDS file

## Usage

```
snpgdsClose(gdsobj)
```

## Arguments

gdsobj            an object of class [SNPGDSFileClass](#), a SNP GDS file

## Details

It is suggested to call `snpgdsClose` instead of `closefn.gds`.

**Value**

None.

**Author(s)**

Xiuwen Zheng

**See Also**

[snpgdsOpen](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpGdsExampleFileName())

genofile

# close the file
snpGdsClose(genofile)
```

---

snpGdsCombineGeno	<i>Merge SNP datasets</i>
-------------------	---------------------------

---

**Description**

To merge GDS files of SNP genotypes into a single GDS file

**Usage**

```
snpGdsCombineGeno(gds.fn, out.fn, sample.id=NULL, snpobj=NULL,
  name.prefix=NULL, snpfirstdim=TRUE, compress.annotation="ZIP_RA.MAX",
  compress.geno="", other.vars=NULL, verbose=TRUE)
```

**Arguments**

<code>gds.fn</code>	a list of SNP GDS files to be merged
<code>out.fn</code>	the name of output GDS file
<code>sample.id</code>	NULL, or a list. If it is a list, specify sample ids for each SNP GDS file
<code>snpobj</code>	specify a <a href="#">snpGdsSNPListClass</a> object, used for strand switch; if NULL, the strand information of the first SNP GDS file is used
<code>name.prefix</code>	NULL, a character vector (added to sample ids for each GDS file)
<code>snpfirstdim</code>	if TRUE, genotypes are stored in the individual-major mode, (i.e, list all SNPs for the first individual, and then list all SNPs for the second individual, etc)
<code>compress.annotation</code>	the compression method for the variables except genotype

compress.geno the compression method for the variable genotype  
other.vars a list object storing other variables  
verbose if TRUE, show information

### Details

The typical variables specified in other.vars are “sample.annot” and “snp.annot”, which are data.frame objects.

### Value

None.

### Author(s)

Xiuwen Zheng

### See Also

[snpgdsCreateGeno](#), [snpgdsCreateGenoSet](#)

### Examples

```
# get the file name of a gds file
fn <- snpgdsExampleFileName()

# combine
snpgdsCombineGeno(c(fn, fn), "test.gds")

snpgdsSummary("test.gds")
```

---

snpgdsCreateGeno *Create a SNP genotype dataset from a matrix*

---

### Description

To create a GDS file of genotypes from a matrix.

### Usage

```
snpgdsCreateGeno(gds.fn, genmat, sample.id=NULL, snp.id=NULL, snp.rs.id=NULL,
  snp.chromosome=NULL, snp.position=NULL, snp.allele=NULL, snpfirstdim=TRUE,
  compress.annotation="ZIP_RA.max", compress.geno="", other.vars=NULL)
```

## Arguments

<code>gds.fn</code>	the file name of gds
<code>genmat</code>	a matrix of genotypes
<code>sample.id</code>	the sample ids, which should be unique
<code>snp.id</code>	the SNP ids, which should be unique
<code>snp.rs.id</code>	the rs ids for SNPs, which can be not unique
<code>snp.chromosome</code>	the chromosome indices
<code>snp.position</code>	the SNP positions in basepair
<code>snp.allele</code>	the reference/non-reference alleles
<code>snpfirstdim</code>	if TRUE, genotypes are stored in the individual-major mode, (i.e, list all SNPs for the first individual, and then list all SNPs for the second individual, etc)
<code>compress.annotation</code>	the compression method for the variables except genotype
<code>compress.geno</code>	the compression method for the variable genotype
<code>other.vars</code>	a list object storing other variables

## Details

There are possible values stored in the variable `genmat`: 0, 1, 2 and other values. “0” indicates two B alleles, “1” indicates one A allele and one B allele, “2” indicates two A alleles, and other values indicate a missing genotype.

If `snpfirstdim` is TRUE, then `genmat` should be “# of SNPs X # of samples”; if `snpfirstdim` is FALSE, then `genmat` should be “# of samples X # of SNPs”.

The typical variables specified in `other.vars` are “`sample.annot`” and “`snp.annot`”, which are `data.frame` objects.

## Value

None.

## Author(s)

Xiuwen Zheng

## See Also

[snpGDS::createGenoSet](#), [snpGDS::combineGeno](#)

## Examples

```
# load data
data(hapmap_genotype)

# create a gds file
with(hapmap_genotype, snpGDS::createGeno("test.gds", genmat=genotype,
  sample.id=sample.id, snp.id=snp.id, snp.chromosome=snp.chromosome,
```

```

    snp.position=snp.position, snp.allele=snp.allele, snpfirstdim=TRUE))

# open the gds file
genofile <- snpgdsOpen("test.gds")

RV <- snpgdsPCA(genofile)
plot(RV$eigenvect[,2], RV$eigenvect[,1], xlab="PC 2", ylab="PC 1")

# close the file
snpgdsClose(genofile)

```

---

snpgdsCreateGenoSet     *Create a SNP genotype dataset from a GDS file*

---

### Description

To create a GDS file of genotypes from a specified GDS file.

### Usage

```

snpgdsCreateGenoSet(src.fn, dest.fn, sample.id=NULL, snp.id=NULL,
  snpfirstdim=NULL, compress.annotation="ZIP_RA.max", compress.geno="",
  verbose=TRUE)

```

### Arguments

src.fn	the file name of a specified GDS file
dest.fn	the file name of output GDS file
sample.id	a vector of sample id specifying selected samples; if NULL, all samples are used
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
snpfirstdim	if TRUE, genotypes are stored in the individual-major mode, (i.e, list all SNPs for the first individual, and then list all SNPs for the second individual, etc)
compress.annotation	the compression method for the variables except genotype
compress.geno	the compression method for the variable genotype
verbose	if TRUE, show information

### Value

None.

### Author(s)

Xiuwen Zheng



**See Also**

[snpgdsCreateGeno](#), [snpgdsCombineGeno](#)

**Examples**

```
# open an example dataset (HapMap)
(genofile <- snpgdsOpen(snpgdsExampleFileName()))
# + [ ] *
# |--+ sample.id { FStr8 279 ZIP(23.10%) }
# |--+ snp.id { Int32 9088 ZIP(34.76%) }
# |--+ snp.rs.id { FStr8 9088 ZIP(42.66%) }
# |--+ snp.position { Int32 9088 ZIP(94.73%) }
# |--+ snp.chromosome { UInt8 9088 ZIP(0.94%) } *
# |--+ snp.allele { FStr8 9088 ZIP(14.45%) }
# |--+ genotype { Bit2 9088x279 } *
# |--+ sample.annot [ data.frame ] *
# | |--+ sample.id { FStr8 279 ZIP(23.10%) }
# | |--+ family.id { FStr8 279 ZIP(28.37%) }
# | |--+ geneva.id { Int32 279 ZIP(80.29%) }
# | |--+ father.id { FStr8 279 ZIP(12.98%) }
# | |--+ mother.id { FStr8 279 ZIP(12.86%) }
# | |--+ plate.id { FStr8 279 ZIP(1.29%) }
# | |--+ sex { FStr8 279 ZIP(28.32%) }
# | |--+ pop.group { FStr8 279 ZIP(7.89%) }

set.seed(1000)
snpset <- unlist(snpgdsLDpruning(genofile))
length(snpset)
# 6547

# close the file
snpgdsClose(genofile)

snpgdsCreateGenoSet(snpgdsExampleFileName(), "test.gds", snp.id=snpset)

#####
# check

(gfile <- snpgdsOpen("test.gds"))
# + [ ] *
# |--+ sample.id { VStr8 279 ZIP(29.89%) }
# |--+ snp.id { Int32 6547 ZIP(34.89%) }
# |--+ snp.rs.id { VStr8 6547 ZIP(40.52%) }
# |--+ snp.position { Int32 6547 ZIP(94.85%) }
# |--+ snp.chromosome { Int32 6547 ZIP(0.41%) }
# |--+ snp.allele { VStr8 6547 ZIP(11.51%) }
# |--+ genotype { Bit2 6547x279 } *

# close the file
snpgdsClose(gfile)
```

```
unlink("test.gds", force=TRUE)
```

---

snpgdsCutTree      *Determine clusters of individuals*

---

### Description

To determine sub groups of individuals using a specified dendrogram from hierarchical cluster analysis

### Usage

```
snpgdsCutTree(hc, z.threshold=15, outlier.n=5, n.perm = 5000, samp.group=NULL,
  col.outlier="red", col.list=NULL, pch.outlier=4, pch.list=NULL,
  label.H=FALSE, label.Z=TRUE, verbose=TRUE)
```

### Arguments

hc	an object of <a href="#">snpgdsHCluster</a>
z.threshold	the threshold of Z score to determine whether split the node or not
outlier.n	the cluster with size less than or equal to outlier.n is considered as outliers
n.perm	the times for permutation
samp.group	if NULL, determine groups by Z score; if a vector of factor, assign each individual in dendrogram with respect to samp.group
col.outlier	the color of outlier
col.list	the list of colors for different clusters
pch.outlier	plotting 'character' for outliers
pch.list	plotting 'character' for different clusters
label.H	if TRUE, plotting heights in a dendrogram
label.Z	if TRUE, plotting Z scores in a dendrogram
verbose	if TRUE, show information

### Details

The details will be described in future.

### Value

Return a list:

sample.id	the sample ids used in the analysis
z.threshold	the threshold of Z score to determine whether split the node or not
outlier.n	the cluster with size less than or equal to outlier.n is considered as outliers
samp.order	the order of samples in the dendrogram

samp.group	a vector of factor, indicating the group of each individual
dmat	a matrix of pairwise group dissimilarity
dendrogram	the dendrogram of individuals
merge	a data.frame of (z, n1, n2) describing each combination: z, the Z score; n1, the size of the first cluster; n2, the size of the second cluster
clust.count	the counts for clusters

**Author(s)**

Xiuwen Zheng

**See Also**

[snpgdsHCluster](#), [snpgdsDrawTree](#), [snpgdsIBS](#), [snpgdsDiss](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

pop.group <- as.factor(read.gdsn(index.gdsn(
  genofile, "sample.annot/pop.group")))
pop.level <- levels(pop.group)

diss <- snpgdsDiss(genofile)
hc <- snpgdsHCluster(diss)

# close the genotype file
snpgdsClose(genofile)

#####
# cluster individuals
#

set.seed(100)
rv <- snpgdsCutTree(hc, label.H=TRUE, label.Z=TRUE)

# the distribution of Z scores
snpgdsDrawTree(rv, type="z-score", main="HapMap Phase II")

# draw dendrogram
snpgdsDrawTree(rv, main="HapMap Phase II",
  edgePar=list(col=rgb(0.5,0.5,0.5, 0.75), t.col="black"))

#####
# or cluster individuals by ethnic information
#
```

```

rv2 <- snpgdsCutTree(hc, samp.group=pop.group)

# cluster individuals by Z score, specifying 'clust.count'
snpgdsDrawTree(rv2, rv$clust.count, main="HapMap Phase II",
  edgePar = list(col=rgb(0.5,0.5,0.5, 0.75), t.col="black"),
  labels = c("YRI", "CHB/JPT", "CEU"), y.label=0.1)
legend("bottomleft", legend=levels(pop.group), col=1:nlevels(pop.group),
  pch=19, ncol=4, bg="white")

#####
# zoom in ...
#

snpgdsDrawTree(rv2, rv$clust.count, dend.idx = c(1),
  main="HapMap Phase II -- YRI",
  edgePar=list(col=rgb(0.5,0.5,0.5, 0.75), t.col="black"),
  y.label.kinship=TRUE)

snpgdsDrawTree(rv2, rv$clust.count, dend.idx = c(2,2),
  main="HapMap Phase II -- CEU",
  edgePar=list(col=rgb(0.5,0.5,0.5, 0.75), t.col="black"),
  y.label.kinship=TRUE)

snpgdsDrawTree(rv2, rv$clust.count, dend.idx = c(2,1),
  main="HapMap Phase II -- CHB/JPT",
  edgePar=list(col=rgb(0.5,0.5,0.5, 0.75), t.col="black"),
  y.label.kinship=TRUE)

```

---

snpgdsDiss

*Individual dissimilarity analysis*


---

## Description

Calculate the individual dissimilarities for each pair of individuals.

## Usage

```

snpgdsDiss(gdsobj, sample.id=NULL, snp.id=NULL, autosome.only=TRUE,
  remove.monosnp=TRUE, maf=NaN, missing.rate=NaN, num.thread=1, verbose=TRUE)

```

## Arguments

gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
sample.id	a vector of sample id specifying selected samples; if NULL, all samples are used
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
autosome.only	if TRUE, use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome

<code>remove.monosnp</code>	if TRUE, remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " <code>&gt;= maf</code> " only; if NaN, no MAF threshold
<code>missing.rate</code>	to use the SNPs with " <code>&lt;= missing.rate</code> " only; if NaN, no missing threshold
<code>num.thread</code>	the number of (CPU) cores used; if NA, detect the number of cores automatically
<code>verbose</code>	if TRUE, show information

### Details

The minor allele frequency and missing rate for each SNP passed in `snp.id` are calculated over all the samples in `sample.id`.

The details will be described in future.

### Value

Return a class "snpGDSClass":

<code>sample.id</code>	the sample ids used in the analysis
<code>snp.id</code>	the SNP ids used in the analysis
<code>diss</code>	a matrix of individual dissimilarity

### Author(s)

Xiuwen Zheng

### References

Zheng, Xiuwen. 2013. Statistical Prediction of HLA Alleles and Relatedness Analysis in Genome-Wide Association Studies. PhD dissertation, the department of Biostatistics, University of Washington.

Weir BS, Zheng X. SNPs and SNVs in Forensic Science. 2015. Forensic Science International: Genetics Supplement Series.

### See Also

[snpGDSHCluster](#)

### Examples

```
# open an example dataset (HapMap)
genofile <- snpGDSOpen(snpGDSExampleFileName())

pop.group <- as.factor(read.gdsn(index.gdsn(
  genofile, "sample.annot/pop.group")))
pop.level <- levels(pop.group)

diss <- snpGDS(snpGDSExampleFileName())
hc <- snpGDSHCluster(diss)

# close the genotype file
```

```

snpGDSClose(genofile)

# split
set.seed(100)
rv <- snpGDSCutTree(hc, label.H=TRUE, label.Z=TRUE)

# draw dendrogram
snpGDSDrawTree(rv, main="HapMap Phase II",
  edgePar=list(col=rgb(0.5,0.5,0.5, 0.75), t.col="black"))

```

---

snpGDSDrawTree      *Draw a dendrogram*

---

## Description

To draw a dendrogram or the distribution of Z scores

## Usage

```

snpGDSDrawTree(obj, clust.count=NULL, dend.idx=NULL,
  type=c("dendrogram", "z-score"), yaxis.height=TRUE, yaxis.kinship=TRUE,
  y.kinship.baseline=NaN, y.label.kinship=FALSE, outlier.n=NULL,
  shadow.col=c(rgb(0.5, 0.5, 0.5, 0.25), rgb(0.5, 0.5, 0.5, 0.05)),
  outlier.col=rgb(1, 0.50, 0.50, 0.5), leaflab="none",
  labels=NULL, y.label=0.2, ...)

```

## Arguments

obj	an object returned by <a href="#">snpGDSCutTree</a>
clust.count	the counts for clusters, drawing shadows
dend.idx	the index of sub tree, plot obj\$dendrogram[[dend.idx]], or NULL for the whole tree
type	"dendrogram", draw a dendrogram; or "z-score", draw the distribution of Z score
yaxis.height	if TRUE, draw the left Y axis: height of tree
yaxis.kinship	if TRUE, draw the right Y axis: kinship coefficient
y.kinship.baseline	the baseline value of kinship; if NaN, it is the height of the first split from top in a dendrogram; only works when yaxis.kinship = TRUE
y.label.kinship	if TRUE, show 'PO/FS' etc on the right axis
outlier.n	the cluster with size less than or equal to outlier.n is considered as outliers; if NULL, let outlier.n = obj\$outlier.n
shadow.col	two colors for shadow
outlier.col	the colors for outliers

leaflab	a string specifying how leaves are labeled. The default "perpendicular" write text vertically (by default). "textlike" writes text horizontally (in a rectangle), and "none" suppresses leaf labels.
labels	the legend for different regions
y.label	y positions of labels
...	Arguments to be passed to the method "plot(, ...)", such as graphical parameters.

### Details

The details will be described in future.

### Value

None.

### Author(s)

Xiuwen Zheng

### See Also

[snpgdsCutTree](#)

### Examples

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

pop.group <- as.factor(read.gdsn(index.gdsn(
  genofile, "sample.annot/pop.group")))
pop.level <- levels(pop.group)

diss <- snpgdsDiss(genofile)
hc <- snpgdsHCluster(diss)

# close the genotype file
snpgdsClose(genofile)

# split
set.seed(100)
rv <- snpgdsCutTree(hc, label.H=TRUE, label.Z=TRUE)

# draw dendrogram
snpgdsDrawTree(rv, main="HapMap Phase II",
  edgePar=list(col=rgb(0.5,0.5,0.5, 0.75), t.col="black"))
```

snpgdsEIGMIX

*Eigen-analysis on SNP genotype data***Description**

Eigen-analysis on IBD matrix based SNP genotypes.

**Usage**

```
snpgdsEIGMIX(gdsobj, sample.id=NULL, snp.id=NULL, autosome.only=TRUE,
  remove.monosnp=TRUE, maf=NaN, missing.rate=NaN, num.thread=1L,
  eigen.cnt=32L, need.ibdmat=FALSE, ibdmat.only=FALSE, verbose=TRUE)
```

**Arguments**

<code>gdsobj</code>	an object of class <code>SNPGDSFileClass</code> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if <code>NULL</code> , all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if <code>NULL</code> , all SNPs are used
<code>autosome.only</code>	if <code>TRUE</code> , use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if <code>TRUE</code> , remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " <code>&gt;= maf</code> " only; if <code>NaN</code> , no MAF threshold
<code>missing.rate</code>	to use the SNPs with " <code>&lt;= missing.rate</code> " only; if <code>NaN</code> , no missing threshold
<code>num.thread</code>	the number of (CPU) cores used; if <code>NA</code> , detect the number of cores automatically
<code>eigen.cnt</code>	output the number of eigenvectors; if <code>eigen.cnt &lt;= 0</code> , then return all eigenvectors
<code>need.ibdmat</code>	if <code>TRUE</code> , return the IBD matrix
<code>ibdmat.only</code>	return the IBD matrix only, do not compute the eigenvalues and eigenvectors
<code>verbose</code>	if <code>TRUE</code> , show information

**Value**

Return a `snpgdsEigMixClass` object, and it is a list:

<code>sample.id</code>	the sample ids used in the analysis
<code>snp.id</code>	the SNP ids used in the analysis
<code>eigenval</code>	eigenvalues
<code>eigenvect</code>	eigenvectors, "# of samples" x "eigen.cnt"
<code>ibdmat</code>	the IBD matrix

**Author(s)**

Xiuwen Zheng



## References

Zheng X, Weir BS. Eigenanalysis on SNP Data with an Interpretation of Identity by Descent. 2015. Theoretical Population Biology.

## See Also

[snpgdsEIGMIX](#), [snpgdsPCA](#)

## Examples

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

# get population information
# or pop_code <- scan("pop.txt", what=character())
# if it is stored in a text file "pop.txt"
pop_code <- read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))

# get sample id
samp.id <- read.gdsn(index.gdsn(genofile, "sample.id"))

# run eigen-analysis
RV <- snpgdsEIGMIX(genofile)

# eigenvalues
RV$eigenval

# make a data.frame
tab <- data.frame(sample.id = samp.id, pop = factor(pop_code),
  EV1 = RV$eigenvect[,1], # the first eigenvector
  EV2 = RV$eigenvect[,2], # the second eigenvector
  stringsAsFactors = FALSE)
head(tab)

# draw
plot(tab$EV2, tab$EV1, col=as.integer(tab$pop),
  xlab="eigenvector 2", ylab="eigenvector 1")
legend("topleft", legend=levels(tab$pop), pch="o", col=1:4)

# define groups
groups <- list(CEU = samp.id[pop_code == "CEU"],
  YRI = samp.id[pop_code == "YRI"],
  CHB = samp.id[is.element(pop_code, c("HCB", "JPT"))])

prop <- snpgdsAdmixProp(RV, groups=groups)

# draw
plot(prop[, "YRI"], prop[, "CEU"], col=as.integer(tab$pop),
  xlab = "Admixture Proportion from YRI",
  ylab = "Admixture Proportion from CEU")
abline(v=0, col="gray25", lty=2)
```

```
abline(h=0, col="gray25", lty=2)
abline(a=1, b=-1, col="gray25", lty=2)
legend("topright", legend=levels(tab$pop), pch="o", col=1:4)

# run eigen-analysis
RV <- snpgdsEIGMIX(genofile, sample.id=samp.id[pop_code=="JPT"],
  need.ibdmat=TRUE)
z <- RV$ibdmat

mean(c(z))
mean(diag(z))

# close the genotype file
snpgdsClose(genofile)
```

---

snpgdsErrMsg

*Get the last error information*

---

## **Description**

Return the last error message.

## **Usage**

```
snpgdsErrMsg()
```

## **Value**

Characters

## **Author(s)**

Xiuwen Zheng

## **Examples**

```
snpgdsErrMsg()
```

---

snpGDSExampleFileName *Example GDS file*

---

**Description**

Return the file name of example data

**Usage**

```
snpGDSExampleFileName()
```

**Details**

A GDS genotype file was created from a subset of HapMap Phase II dataset consisting of 270 individuals and duplicates.

**Value**

Characters

**Author(s)**

Xiuwen Zheng

**Examples**

```
snpGDSExampleFileName()
```

---

SNPGDSFileClass      *SNPGDSFileClass*

---

**Description**

A SNPGDSFileClass object provides access to a GDS file containing genome-wide SNP data. It extends the class [gds.class](#) in the gdsfmt package.

**Author(s)**

Xiuwen Zheng

**See Also**

[snpGDSOpen](#), [snpGDSClose](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGDSOpen(snpGDSExampleFileName())
genofile

class(genofile)
# "SNPGDSFileClass" "gds.class"

# close the file
snpGDSClose(genofile)
```

---

snpGDSfst	<i>F-statistics (fixation indices)</i>
-----------	--

---

**Description**

Calculate relatedness measures F-statistics (also known as fixation indices) for given populations

**Usage**

```
snpGDSfst(gdsobj, population, method=c("W&H02", "W&C84"), sample.id=NULL,
          snp.id=NULL, autosome.only=TRUE, remove.monosnp=TRUE, maf=NaN,
          missing.rate=NaN, with.id=FALSE, verbose=TRUE)
```

**Arguments**

<code>gdsobj</code>	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
<code>population</code>	a factor, indicating population information for each individual
<code>method</code>	"W&H02" – relative beta estimator in Weir&Hill 2002, "W&C84" – Fst estimator in Weir&Cockerham 1984
<code>sample.id</code>	a vector of sample id specifying selected samples; if NULL, all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
<code>autosome.only</code>	if TRUE, use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if TRUE, remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " $\geq$ maf" only; if NaN, no MAF threshold
<code>missing.rate</code>	to use the SNPs with " $\leq$ missing.rate" only; if NaN, no missing threshold
<code>with.id</code>	if TRUE, the returned value with <code>sample.id</code> and <code>sample.id</code>
<code>verbose</code>	if TRUE, show information

**Details**

The minor allele frequency and missing rate for each SNP passed in `snp.id` are calculated over all the samples in `sample.id`.

**Value**

Return a list:

sample.id	the sample ids used in the analysis
snp.id	the SNP ids used in the analysis
Fst	Fst estimator
Beta	Beta matrix

**Author(s)**

Xiuwen Zheng

**References**

Weir, B. S. & Cockerham, C. C. Estimating F-statistics for the analysis of population structure. (1984).

Weir, B. S. & Hill, W. G. Estimating F-statistics. Annual review of genetics 36, 721-50 (2002).

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGDSOpen(snpGDSExampleFileName())

group <- as.factor(read.gdsn(index.gdsn(
  genofile, "sample.annot/pop.group")))

# Fst estimation
snpGDSFst(genofile, population=group, method="W&H02")

# or
snpGDSFst(genofile, population=group, method="W&C84")

# close the genotype file
snpGSDSClose(genofile)
```

---

snpGDS2BED

*Conversion from GDS to PLINK BED*


---

**Description**

Convert a GDS file to a PLINK binary ped file.

**Usage**

```
snpGDS2BED(gdsobj, bed.fn, sample.id=NULL, snp.id=NULL, snpfirstdim=NULL,
  verbose=TRUE)
```

**Arguments**

gdsobj	an object of class <code>SNPGDSFileClass</code> , a SNP GDS file; or characters, the file name of GDS
bed.fn	the file name of output
sample.id	a vector of sample id specifying selected samples; if NULL, all samples are used
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
snpfirstdim	if TRUE, genotypes are stored in the individual-major mode, (i.e, list all SNPs for the first individual, and then list all SNPs for the second individual, etc); if NULL, determine automatically
verbose	if TRUE, show information

**Details**

GDS – Genomic Data Structures, the extended file name used for storing genetic data, and the file format used in the `gdsfmt` package.

BED – the PLINK binary ped format.

**Value**

None.

**Author(s)**

Xiuwen Zheng

**References**

Purcell S, Neale B, Todd-Brown K, Thomas L, Ferreira MAR, Bender D, Maller J, Sklar P, de Bakker PIW, Daly MJ & Sham PC. 2007. PLINK: a toolset for whole-genome association and population-based linkage analysis. *American Journal of Human Genetics*, 81.

<http://corearray.sourceforge.net/>

**See Also**

[snpgdsBED2GDS](#), [snpgdsGDS2PED](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

snpset <- snpgdsSelectSNP(genofile, missing.rate=0.95)
snpgdsGDS2BED(genofile, bed.fn="test", snp.id=snpset)

# close the genotype file
snpgdsClose(genofile)
```

---

snpGDS2Eigen      *Conversion from GDS to Eigen (EIGENSTRAT)*

---

### Description

Convert a GDS file to an EIGENSTRAT file.

### Usage

```
snpGDS2Eigen(gdsobj, eigen.fn, sample.id=NULL, snp.id=NULL, verbose=TRUE)
```

### Arguments

gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
eigen.fn	the file name of EIGENSTRAT
sample.id	a vector of sample id specifying selected samples; if NULL, all samples are used
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
verbose	if TRUE, show information

### Details

GDS – Genomic Data Structures, the extended file name used for storing genetic data, and the file format used in the [gdsfmt](#) package.

Eigen – the text format used in EIGENSTRAT.

### Value

None.

### Author(s)

Xiuwen Zheng

### References

Patterson N, Price AL, Reich D (2006) Population structure and eigenanalysis. *PLoS Genetics* 2:e190.

Price AL, Patterson NJ, Plenge RM, Weinblatt ME, Shadick NA, Reich D (2006) Principal components analysis corrects for stratification in genome-wide association studies. *Nat Genet.* 38, 904-909.

<http://corearray.sourceforge.net/>

### See Also

[snpGDS2PED](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

snpset <- snpgdsSelectSNP(genofile, missing.rate=0.95)
snpgdsGDS2Eigen(genofile, eigen.fn="tmpeigen", snp.id=snpset)

# close the genotype file
snpgdsClose(genofile)
```

---

snpgdsGDS2PED

*Conversion from GDS to PED*


---

**Description**

Convert a GDS file to a PLINK ped file.

**Usage**

```
snpgdsGDS2PED(gdsobj, ped.fn, sample.id=NULL, snp.id=NULL, use.snp.rs.id=TRUE,
  format=c("A/G/C/T", "A/B", "1/2"), verbose=TRUE)
```

**Arguments**

gdsobj	a GDS file object ( <a href="#">gds.class</a> )
ped.fn	the file name of output
sample.id	a vector of sample id specifying selected samples; if NULL, all samples are used
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
use.snp.rs.id	if TRUE, use "snp.rs.id" instead of "snp.id" if available
format	specify the coding: "A/G/C/T" – allelic codes stored in "snp.allele" of the GDS file; "A/B" – A and B codes; "1/2" – 1 and 2 codes
verbose	if TRUE, show information

**Details**

GDS – Genomic Data Structures, the extended file name used for storing genetic data, and the file format used in the [gdsfmt](#) package.

PED – the PLINK text ped format.

**Value**

None.

**Author(s)**

Xiuwen Zheng



**References**

Purcell S, Neale B, Todd-Brown K, Thomas L, Ferreira MAR, Bender D, Maller J, Sklar P, de Bakker PIW, Daly MJ & Sham PC. 2007. PLINK: a toolset for whole-genome association and population-based linkage analysis. *American Journal of Human Genetics*, 81.

<http://corearray.sourceforge.net/>

**See Also**

[snpGDS2BED](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGDSOpen(snpGDSExampleFileName())

# GDS ==> PED
snpGDS2PED(genofile, ped.fn="tmp")

# close the GDS file
snpGDSClose(genofile)
```

---

snpGDSGEN2GDS

*Conversion from Oxford GEN format to GDS*


---

**Description**

Convert an Oxford GEN file (text format) to a GDS file.

**Usage**

```
snpGDSGEN2GDS(gen.fn, sample.fn, out.fn, chr.code=NULL,
  call.threshold=0.9, version=c(">=2.0", "<=1.1.5"),
  snpfirstdim=FALSE, compress.annotation="ZIP_RA.max", compress.geno="",
  verbose=TRUE)
```

**Arguments**

gen.fn	the file name of Oxford GEN text file(s), it could be a vector indicate merging all files
sample.fn	the file name of sample annotation
out.fn	the output GDS file
chr.code	a vector of chromosome code according to gen.fn, indicating chromosomes. It could be either numeric or character-type
call.threshold	the threshold to determine missing genotypes
version	either ">=2.0" or "<=1.1.5", see details

snpfirstdim	if TRUE, genotypes are stored in the individual-major mode, (i.e, list all SNPs for the first individual, and then list all SNPs for the second individual, etc)
compress.annotation	the compression method for the GDS variables, except "genotype"; optional values are defined in the function add.gdsn
compress.geno	the compression method for "genotype"; optional values are defined in the function add.gdsn
verbose	if TRUE, show information

### Details

GDS – Genomic Data Structures, the extended file name used for storing genetic data, and the file format is used in the [gdsfmt](#) package.

NOTE : the sample file format (`sample.fn`) has changed with the release of SNPTEST v2. Specifically, the way in which covariates and phenotypes are coded on the second line of the header file has changed. `version` has to be specified, and the function uses "`>=2.0`" by default.

### Value

Return the file name of GDS format with an absolute path.

### Author(s)

Xiuwen Zheng

### References

[http://www.stats.ox.ac.uk/~marchini/software/gwas/file\\_format.html](http://www.stats.ox.ac.uk/~marchini/software/gwas/file_format.html)

### See Also

[snpgdsBED2GDS](#), [snpgdsVCF2GDS](#)

### Examples

```
cat("running snpgdsGEN2GDS ...\n")
## Not run:
snpgdsGEN2GDS("test.gen", "test.sample", "output.gds", chr.code=1)

## End(Not run)
```

---

snpgdsGetGeno                      *To get a genotype matrix*

---

### Description

To get a genotype matrix from a specified GDS file

### Usage

```
snpgdsGetGeno(gdsobj, sample.id=NULL, snp.id=NULL, snpfirstdim=NULL,
              with.id=FALSE, verbose=TRUE)
```

### Arguments

gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file; or characters to specify the file name of SNP GDS
sample.id	a vector of sample id specifying selected samples; if NULL, all samples are used
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
snpfirstdim	if TRUE, genotypes are stored in the individual-major mode, (i.e, list all SNPs for the first individual, and then list all SNPs for the second individual, etc); if NULL, determine automatically
with.id	if TRUE, return sample.id and snp.id
verbose	if TRUE, show information

### Value

The function returns an integer matrix with values 0, 1, 2 or NA representing the number of reference allele when `with.id=FALSE`; or `list(genotype, sample.id, snp.id)` when `with.id=TRUE`. The orders of sample and SNP IDs in the genotype matrix are actually consistent with `sample.id` and `snp.id` in the GDS file, which may not be as the same as the arguments `sample.id` and `snp.id` specified by users.

### Author(s)

Xiuwen Zheng

### Examples

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

set.seed(1000)
snpset <- sample(read.gdsn(index.gdsn(genofile, "snp.id")), 1000)

mat1 <- snpgdsGetGeno(genofile, snp.id=snpset, snpfirstdim=TRUE)
dim(mat1)
# 1000 279
```

```

table(c(mat1), exclude=NULL)

mat2 <- snpgdsGetGeno(genofile, snp.id=snpset, snpfirstdim=FALSE)
dim(mat2)
# 279 1000
table(c(mat2), exclude=NULL)

identical(t(mat1), mat2)
# TRUE

# close the file
snpgdsClose(genofile)

```

---

snpGDSGRM

*Genetic Relationship Matrix (GRM) for SNP genotype data*


---

## Description

Calculate Genetic Relationship Matrix (GRM) using SNP genotype data.

## Usage

```

snpgdsGRM(gdsobj, sample.id=NULL, snp.id=NULL, autosome.only=TRUE,
  remove.monosnp=TRUE, maf=NaN, missing.rate=NaN,
  method=c("Visscher", "Eigenstrat", "EIGMIX", "W&Z15"), num.thread=1L,
  with.id=TRUE, verbose=TRUE)

```

## Arguments

<code>gdsobj</code>	an object of class <code>SNPGDSFileClass</code> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if <code>NULL</code> , all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if <code>NULL</code> , all SNPs are used
<code>autosome.only</code>	if <code>TRUE</code> , use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if <code>TRUE</code> , remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " $\geq$ maf" only; if <code>NaN</code> , no MAF threshold
<code>missing.rate</code>	to use the SNPs with " $\leq$ missing.rate" only; if <code>NaN</code> , no missing threshold
<code>method</code>	"Visscher" – genetic relationship matrix defined in CGTA; "Eigenstrat" – genetic covariance matrix in EIGENSTRAT; "EIGMIX" – coancestry matrix defined in Zheng & Weir (2015), "W&Z15" – individual beta estimator
<code>num.thread</code>	the number of (CPU) cores used; if <code>NA</code> , detect the number of cores automatically
<code>with.id</code>	if <code>TRUE</code> , the returned value with <code>sample.id</code> and <code>sample.id</code>
<code>verbose</code>	if <code>TRUE</code> , show information

**Value**

Return a list if with.id = TRUE:

sample.id	the sample ids used in the analysis
snp.id	the SNP ids used in the analysis
grm	the genetic relationship matrix

If with.id = FALSE, this function returns the genetic relationship matrix (GRM) without sample and SNP IDs.

**Author(s)**

Xiuwen Zheng

**References**

Yang, J., Lee, S. H., Goddard, M. E. & Visscher, P. M. GCTA: a tool for genome-wide complex trait analysis. *American journal of human genetics* 88, 76-82 (2011).

Patterson, N., Price, A. L. & Reich, D. Population structure and eigenanalysis. *PLoS Genet.* 2, e190 (2006).

Zheng X, Weir BS. Eigenanalysis on SNP Data with an Interpretation of Identity by Descent. 2015. *Theoretical Population Biology*.

Weir BS, Zheng X. SNPs and SNVs in Forensic Science. 2015. *Forensic Science International: Genetics Supplement Series*.

**See Also**

[snpGDSIndInb](#), [snpGDSFst](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGDSOpen(snpGDSExampleFileName())

rv <- snpGDSGRM(genofile, method="Visscher")
eig <- eigen(rv$grm) # Eigendecomposition

pop <- factor(read.gdsn(index.gdsn(genofile, "sample.annot/pop.group")))
plot(eig$vectors[,1], eig$vectors[,2], col=pop)
legend("topleft", legend=levels(pop), pch=19, col=1:4)

# close the file
snpGSDSClose(genofile)
```

---

snpGdsHCluster      *Hierarchical cluster analysis*

---

### Description

Perform hierarchical cluster analysis on the dissimilarity matrix.

### Usage

```
snpGdsHCluster(dist, sample.id=NULL, need.mat=TRUE, hang=0.25)
```

### Arguments

dist	an object of "snpGdsDissClass" from <a href="#">snpGdsDiss</a> , an object of "snpGdsIBSClass" from <a href="#">snpGdsIBS</a> , or a square matrix for dissimilarity
sample.id	to specify sample id, only work if dist is a matrix
need.mat	if TRUE, store the dissimilarity matrix in the result
hang	The fraction of the plot height by which labels should hang below the rest of the plot. A negative value will cause the labels to hang down from 0.

### Details

Call the function [hclust](#) to perform hierarchical cluster analysis, using method="average".

### Value

Return a list (class "snpGdsHCClass"):

sample.id	the sample ids used in the analysis
hclust	an object returned from <a href="#">hclust</a>
dendrogram	
dist	the dissimilarity matrix, if need.mat = TRUE

### Author(s)

Xiuwen Zheng

### See Also

[snpGdsIBS](#), [snpGdsDiss](#), [snpGdsCutTree](#)

**Examples**

```

# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

pop.group <- read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))
pop.group <- as.factor(pop.group)
pop.level <- levels(pop.group)

diss <- snpgdsDiss(genofile)
hc <- snpgdsHCluster(diss)
rv <- snpgdsCutTree(hc)
rv

# call 'plot' to draw a dendrogram
plot(rv$dendrogram, leaflab="none", main="HapMap Phase II")

# the distribution of Z scores
snpgdsDrawTree(rv, type="z-score", main="HapMap Phase II")

# draw dendrogram
snpgdsDrawTree(rv, main="HapMap Phase II",
  edgePar=list(col=rgb(0.5,0.5,0.5, 0.75), t.col="black"))

# close the file
snpgdsClose(genofile)

```

---

snpgdsHWE

*Statistical test of Hardy-Weinberg Equilibrium*


---

**Description**

Calculate the p-values for the exact SNP test of Hardy-Weinberg Equilibrium.

**Usage**

```
snpgdsHWE(gdsobj, sample.id=NULL, snp.id=NULL, with.id=FALSE)
```

**Arguments**

<code>gdsobj</code>	an object of class <code>SNPGDSFileClass</code> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if <code>NULL</code> , all samples will be used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if <code>NULL</code> , all SNPs will be used
<code>with.id</code>	if <code>TRUE</code> , the returned value with sample and SNP IDs

**Value**

If `with.id=FALSE`, return a vector of numeric values (p-value); otherwise, return a list with three components "pvalue", "sample.id" and "snp.id".

**Author(s)**

Xiuwen Zheng, Janis E. Wigginton

**References**

Wigginton, J. E., Cutler, D. J. & Abecasis, G. R. A note on exact tests of Hardy-Weinberg equilibrium. *Am. J. Hum. Genet.* 76, 887-93 (2005).

**See Also**

[snpGdsSNPRateFreq](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

# Japanese samples
sample.id <- read.gdsn(index.gdsn(genofile, "sample.id"))
pop <- read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))
(samp.sel <- sample.id[pop=="JPT"])
samp.sel <- samp.sel[nchar(samp.sel) == 7]

# chromosome 1
snp.id <- snpGdsSelectSNP(genofile, sample.id=samp.sel, autosome.only=1L)

# HWE test
p <- snpGdsHWE(genofile, sample.id=samp.sel, snp.id=snp.id)
summary(p)

# QQ plot
plot(-log10((1:length(p))/length(p)), -log10(p[order(p)]),
     xlab="-log10(expected P)", ylab="-log10(observed P)", main="QQ plot")
abline(a=0, b=1, col="blue")

# close the genotype file
snpGdsClose(genofile)
```

---

snpGdsIBDKING

*KING method of moment for the identity-by-descent (IBD) analysis*

---

**Description**

Calculate IBD coefficients by KING method of moment.



**Usage**

```
snpGDSIBDKING(gdsobj, sample.id=NULL, snp.id=NULL, autosome.only=TRUE,
  remove.monosnp=TRUE, maf=NaN, missing.rate=NaN,
  type=c("KING-robust", "KING-homo"), family.id=NULL,
  num.thread=1, verbose=TRUE)
```

**Arguments**

<code>gdsobj</code>	an object of class <code>SNPGDSFileClass</code> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if <code>NULL</code> , all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if <code>NULL</code> , all SNPs are used
<code>autosome.only</code>	if <code>TRUE</code> , use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if <code>TRUE</code> , remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " <code>&gt;= maf</code> " only; if <code>NaN</code> , no MAF threshold
<code>missing.rate</code>	to use the SNPs with " <code>&lt;= missing.rate</code> " only; if <code>NaN</code> , no missing threshold
<code>type</code>	"KING-robust" – relationship inference in the presence of population stratification; "KING-homo" – relationship inference in a homogeneous population
<code>family.id</code>	if <code>NULL</code> , all individuals are treated as singletons; if <code>family.id</code> is given, within- and between-family relationship are estimated differently. If <code>sample.id=NULL</code> , <code>family.id</code> should have the same length as "sample.id" in the GDS file, otherwise <code>family.id</code> should have the same length and order as the argument <code>sample.id</code>
<code>num.thread</code>	the number of (CPU) cores used; if <code>NA</code> , detect the number of cores automatically
<code>verbose</code>	if <code>TRUE</code> , show information

**Details**

KING IBD estimator is a moment estimator, and it is computationally efficient relative to MLE method. The approaches include "KING-robust" – robust relationship inference within or across families in the presence of population substructure, and "KING-homo" – relationship inference in a homogeneous population.

With "KING-robust", the function would return the proportion of SNPs with zero IBS ( $IBS_0$ ) and kinship coefficient (kinship). With "KING-homo" it would return the probability of sharing one IBD ( $k_1$ ) and the probability of sharing zero IBD ( $k_0$ ).

The minor allele frequency and missing rate for each SNP passed in `snp.id` are calculated over all the samples in `sample.id`.

**Value**

Return a list:

<code>sample.id</code>	the sample ids used in the analysis
<code>snp.id</code>	the SNP ids used in the analysis
<code>k0</code>	IBD coefficient, the probability of sharing zero IBD

k1 IBD coefficient, the probability of sharing one IBD  
 IBS0 proportion of SNPs with zero IBS  
 kinship the estimated kinship coefficients, if the parameter kinship=TRUE

### Author(s)

Xiuwen Zheng

### References

Manichaikul A, Mychaleckyj JC, Rich SS, Daly K, Sale M, Chen WM. Robust relationship inference in genome-wide association studies. *Bioinformatics*. 2010 Nov 15;26(22):2867-73.

### See Also

[snpGdsIBDMLE](#), [snpGdsIBDMoM](#)

### Examples

```
# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

# CEU population
samp.id <- read.gdsn(index.gdsn(genofile, "sample.id"))
CEU.id <- samp.id[
  read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))=="CEU"]

#### KING-robust:
#### relationship inference in the presence of population stratification
#### robust relationship inference across family

ibd.robust <- snpGdsIBDKING(genofile, sample.id=CEU.id, family.id=NULL)
names(ibd.robust)
# [1] "sample.id" "snp.id" "afreq" "IBS0" "kinship"

# select a set of pairs of individuals
dat <- snpGdsIBDSelection(ibd.robust, 1/32)
head(dat)

plot(dat$IBS0, dat$kinship, xlab="Proportion of Zero IBS",
      ylab="Estimated Kinship Coefficient (KING-robust)")

#### KING-robust:
#### relationship inference in the presence of population stratification
#### within- and between-family relationship inference

# incorporate with pedigree information
```

```

family.id <- read.gdsn(index.gdsn(genofile, "sample.annot/family.id"))
family.id <- family.id[match(CEU.id, samp.id)]

ibd.robust2 <- snpGdsIBDKING(genofile, sample.id=CEU.id, family.id=family.id)
names(ibd.robust2)

# select a set of pairs of individuals
dat <- snpGdsIBDSelection(ibd.robust2, 1/32)
head(dat)

plot(dat$IBS0, dat$kinship, xlab="Proportion of Zero IBS",
      ylab="Estimated Kinship Coefficient (KING-robust)")

#### KING-homo: relationship inference in a homogeneous population

ibd.homo <- snpGdsIBDKING(genofile, sample.id=CEU.id, type="KING-homo")
names(ibd.homo)
# "sample.id" "snp.id" "afreq" "k0" "k1"

# select a subset of pairs of individuals
dat <- snpGdsIBDSelection(ibd.homo, 1/32)
head(dat)

plot(dat$k0, dat$kinship, xlab="Pr(IBD=0)",
      ylab="Estimated Kinship Coefficient (KING-homo)")

# close the genotype file
snpGdsClose(genofile)

```

---

snpGdsIBDMLE	<i>Maximum likelihood estimation (MLE) for the Identity-By-Descent (IBD) Analysis</i>
--------------	---

---

## Description

Calculate the three IBD coefficients ( $k_0$ ,  $k_1$ ,  $k_2$ ) for non-inbred individual pairs by Maximum Likelihood Estimation.

## Usage

```

snpGdsIBDMLE(gdsobj, sample.id=NULL, snp.id=NULL, autosome.only=TRUE,
             remove.monosnp=TRUE, maf=NaN, missing.rate=NaN, kinship=FALSE,
             kinship.constraint=FALSE, allele.freq=NULL,
             method=c("EM", "downhill.simplex", "Jacquard"), max.niter=1000L,
             reltol=sqrt(.Machine$double.eps), coeff.correct=TRUE,
             out.num.iter=TRUE, num.thread=1, verbose=TRUE)

```

**Arguments**

<code>gdsobj</code>	an object of class <code>SNPGDSFileClass</code> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if NULL, all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
<code>autosome.only</code>	if TRUE, use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if TRUE, remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " $\geq maf$ " only; if NaN, no any MAF threshold
<code>missing.rate</code>	to use the SNPs with " $\leq missing.rate$ " only; if NaN, no any missing threshold
<code>kinship</code>	if TRUE, output the estimated kinship coefficients
<code>kinship.constraint</code>	if TRUE, constrict IBD coefficients ( $k_{0,k_1,k_2}$ ) in the genealogical region ( $2 k_0 k_1 \geq k_2^2$ )
<code>allele.freq</code>	to specify the allele frequencies; if NULL, determine the allele frequencies from <code>gdsobj</code> using the specified samples; if <code>snp.id</code> is specified, <code>allele.freq</code> should have the same order as <code>snp.id</code>
<code>method</code>	"EM", "downhill.simplex", "Jacquard", see details
<code>max.niter</code>	the maximum number of iterations
<code>reltol</code>	relative convergence tolerance; the algorithm stops if it is unable to reduce the value of log likelihood by a factor of $reltol * (abs(\log \text{likelihood with the initial parameters}) + reltol)$ at a step.
<code>coeff.correct</code>	TRUE by default, see details
<code>out.num.iter</code>	if TRUE, output the numbers of iterations
<code>num.thread</code>	the number of (CPU) cores used; if NA, detect the number of cores automatically
<code>verbose</code>	if TRUE, show information

**Details**

The minor allele frequency and missing rate for each SNP passed in `snp.id` are calculated over all the samples in `sample.id`.

The PLINK moment estimates are used as the initial values in the algorithm of searching maximum value of log likelihood function. Two numeric approaches can be used: one is Expectation-Maximization (EM) algorithm, and the other is Nelder-Mead method or downhill simplex method. Generally, EM algorithm is more robust than downhill simplex method. "Jacquard" refers to the estimation of nine Jacquard's coefficients.

If `coeff.correct` is TRUE, the final point that is found by searching algorithm (EM or downhill simplex) is used to compare the six points (fullsib, offspring, halfsib, cousin, unrelated), since any numeric approach might not reach the maximum position after a finite number of steps. If any of these six points has a higher value of log likelihood, the final point will be replaced by the best one.

Although MLE estimates are more reliable than MoM, MLE is much more computationally intensive than MoM, and might not be feasible to estimate pairwise relatedness for a large dataset.

**Value**

Return a snpGDSIBDClass object, which is a list:

sample.id	the sample ids used in the analysis
snp.id	the SNP ids used in the analysis
afreq	the allele frequencies used in the analysis
k0	IBD coefficient, the probability of sharing ZERO IBD, if method="EM" or "downhill.simplex"
k1	IBD coefficient, the probability of sharing ONE IBD, if method="EM" or "downhill.simplex"
D1, ..., D8	Jacquard's coefficients, if method="Jacquard"
kinship	the estimated kinship coefficients, if the parameter kinship=TRUE

**Author(s)**

Xiuwen Zheng

**References**

- Milligan BG. 2003. Maximum-likelihood estimation of relatedness. *Genetics* 163:1153-1167.
- Weir BS, Anderson AD, Hepler AB. 2006. Genetic relatedness analysis: modern data and new challenges. *Nat Rev Genet.* 7(10):771-80.
- Choi Y, Wijsman EM, Weir BS. 2009. Case-control association testing in the presence of unknown relationships. *Genet Epidemiol* 33(8):668-78.
- Jacquard, A. *Structures Genetiques des Populations* (Masson & Cie, Paris, 1970); English translation available in Charlesworth, D. & Charlesworth, B. *Genetics of Human Populations* (Springer, New York, 1974).

**See Also**

[snpGDSIBDMLELogLik](#), [snpGDSIBDMoM](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGDSOpen(snpGDSExampleFileName())

YRI.id <- read.gdsn(index.gdsn(genofile, "sample.id"))[
  read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))=="YRI"]
YRI.id <- YRI.id[1:30]

# SNP pruning
set.seed(10)
snpset <- snpGDSLdPruning(genofile, sample.id=YRI.id, maf=0.05,
  missing.rate=0.05)
snpset <- sample(unlist(snpset), 250)
mibd <- snpGDSIBDMLE(genofile, sample.id=YRI.id, snp.id=snpset)
names(mibd)

# select a set of pairs of individuals
```

```

d <- snpgdsIBDSelection(mibd, kinship.cutoff=1/8)
head(d)

# log likelihood

loglik <- snpgdsIBDMLELogLik(genofile, mibd)
loglik0 <- snpgdsIBDMLELogLik(genofile, mibd, relatedness="unrelated")

# likelihood ratio test
p.value <- pchisq(loglik - loglik0, 1, lower.tail=FALSE)

flag <- lower.tri(mibd$k0)
plot(NaN, xlim=c(0,1), ylim=c(0,1), xlab="k0", ylab="k1")
lines(c(0,1), c(1,0), col="red", lty=3)
points(mibd$k0[flag], mibd$k1[flag])

# specify the allele frequencies
afreq <- snpgdsSNPRateFreq(genofile, sample.id=YRI.id,
  snp.id=snpset)$AlleleFreq
subibd <- snpgdsIBDMLE(genofile, sample.id=YRI.id[1:25], snp.id=snpset,
  allele.freq=afreq)
summary(c(subibd$k0 - mibd$k0[1:25, 1:25]))
# ZERO
summary(c(subibd$k1 - mibd$k1[1:25, 1:25]))
# ZERO

# close the genotype file
snpgdsClose(genofile)

```

---

snpgdsIBDMLELogLik	<i>Log likelihood for MLE method in the Identity-By-Descent (IBD) Analysis</i>
--------------------	--

---

## Description

Calculate the log likelihood values from maximum likelihood estimation.

## Usage

```

snpgdsIBDMLELogLik(gdsobj, ibdobj, k0 = NaN, k1 = NaN,
  relatedness=c("", "self", "fullsib", "offspring",
  "halfsib", "cousin", "unrelated"))

```

## Arguments

**gdsobj** an object of class [SNPGDSFileClass](#), a SNP GDS file

ibdobj	the snpGdsIBDClass object returned from <a href="#">snpGdsIBDMLE</a>
k0	specified IBD coefficient
k1	specified IBD coefficient
relatedness	specify a relatedness, otherwise use the values of k0 and k1

### Details

If (relatedness == "") and (k0 == NaN or k1 == NaN), then return the log likelihood values for each (k0, k1) stored in ibdobj. \ If (relatedness == "") and (k0 != NaN) and (k1 != NaN), then return the log likelihood values for a specific IBD coefficient (k0, k1). \ If relatedness is: "self", then k0 = 0, k1 = 0; "fullsib", then k0 = 0.25, k1 = 0.5; "offspring", then k0 = 0, k1 = 1; "halfsib", then k0 = 0.5, k1 = 0.5; "cousin", then k0 = 0.75, k1 = 0.25; "unrelated", then k0 = 1, k1 = 0.

### Value

Return a n-by-n matrix of log likelihood values, where n is the number of samples.

### Author(s)

Xiuwen Zheng

### References

- Milligan BG. 2003. Maximum-likelihood estimation of relatedness. *Genetics* 163:1153-1167.
- Weir BS, Anderson AD, Hepler AB. 2006. Genetic relatedness analysis: modern data and new challenges. *Nat Rev Genet.* 7(10):771-80.
- Choi Y, Wijsman EM, Weir BS. 2009. Case-control association testing in the presence of unknown relationships. *Genet Epidemiol* 33(8):668-78.

### See Also

[snpGdsIBDMLE](#), [snpGdsIBDMoM](#)

### Examples

```
# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

YRI.id <- read.gdsn(index.gdsn(genofile, "sample.id"))[
  read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))=="YRI"]
YRI.id <- YRI.id[1:30]

# SNP pruning
set.seed(10)
snpset <- snpGdsLDpruning(genofile, sample.id=YRI.id, maf=0.05,
  missing.rate=0.05)
snpset <- sample(unlist(snpset), 250)
mibd <- snpGdsIBDMLE(genofile, sample.id=YRI.id, snp.id=snpset)
names(mibd)
```

```

# select a set of pairs of individuals
d <- snpgdsIBDSelection(mibd, kinship.cutoff=1/8)
head(d)

# log likelihood

loglik <- snpgdsIBDMLELogLik(genofile, mibd)
loglik0 <- snpgdsIBDMLELogLik(genofile, mibd, relatedness="unrelated")

# likelihood ratio test
p.value <- pchisq(loglik - loglik0, 1, lower.tail=FALSE)

flag <- lower.tri(mibd$k0)
plot(NaN, xlim=c(0,1), ylim=c(0,1), xlab="k0", ylab="k1")
lines(c(0,1), c(1,0), col="red", lty=3)
points(mibd$k0[flag], mibd$k1[flag])

# specify the allele frequencies
afreq <- snpgdsSNPRateFreq(genofile, sample.id=YRI.id,
  snp.id=snpset)$AlleleFreq
subibd <- snpgdsIBDMLE(genofile, sample.id=YRI.id[1:25], snp.id=snpset,
  allele.freq=afreq)
summary(c(subibd$k0 - mibd$k0[1:25, 1:25]))
# ZERO
summary(c(subibd$k1 - mibd$k1[1:25, 1:25]))
# ZERO

# close the genotype file
snpGDSClose(genofile)

```

---

snpGDSIBDMoM

*PLINK method of moment (MoM) for the Identity-By-Descent (IBD) Analysis*


---

## Description

Calculate three IBD coefficients for non-inbred individual pairs by PLINK method of moment (MoM).

## Usage

```

snpGDSIBDMoM(gdsobj, sample.id=NULL, snp.id=NULL, autosome.only=TRUE,
  remove.monosnp=TRUE, maf=NaN, missing.rate=NaN, allele.freq=NULL,
  kinship=FALSE, kinship.constraint=FALSE, num.thread=1, verbose=TRUE)

```



**Arguments**

<code>gdsobj</code>	an object of class <code>SNPGDSFileClass</code> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if NULL, all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
<code>autosome.only</code>	if TRUE, use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if TRUE, remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " $\geq maf$ " only; if NaN, no MAF threshold
<code>missing.rate</code>	to use the SNPs with " $\leq missing.rate$ " only; if NaN, no missing threshold
<code>allele.freq</code>	to specify the allele frequencies; if NULL, determine the allele frequencies from <code>gdsobj</code> using the specified samples; if <code>snp.id</code> is specified, <code>allele.freq</code> should have the same order as <code>snp.id</code>
<code>kinship</code>	if TRUE, output the estimated kinship coefficients
<code>kinship.constraint</code>	if TRUE, constrict IBD coefficients ( $k_0, k_1, k_2$ ) in the geneological region ( $k_0 k_1 \geq k_2^2$ )
<code>num.thread</code>	the number of (CPU) cores used; if NA, detect the number of cores automatically
<code>verbose</code>	if TRUE, show information

**Details**

PLINK IBD estimator is a moment estimator, and it is computationally efficient relative to MLE method. In the PLINK method of moment, a correction factor based on allele counts is used to adjust for sampling. However, if allele frequencies are specified, no correction factor is conducted since the specified allele frequencies are assumed to be known without sampling.

The minor allele frequency and missing rate for each SNP passed in `snp.id` are calculated over all the samples in `sample.id`.

**Value**

Return a list:

<code>sample.id</code>	the sample ids used in the analysis
<code>snp.id</code>	the SNP ids used in the analysis
<code>k0</code>	IBD coefficient, the probability of sharing ZERO IBD
<code>k1</code>	IBD coefficient, the probability of sharing ONE IBD
<code>kinship</code>	the estimated kinship coefficients, if the parameter <code>kinship=TRUE</code>

**Author(s)**

Xiuwen Zheng

## References

Purcell S, Neale B, Todd-Brown K, Thomas L, Ferreira MAR, Bender D, Maller J, Sklar P, de Bakker PIW, Daly MJ & Sham PC. 2007. PLINK: a toolset for whole-genome association and population-based linkage analysis. *American Journal of Human Genetics*, 81.

## See Also

[snpGDSIBDMLE](#), [snpGDSIBDMLELogLik](#)

## Examples

```
# open an example dataset (HapMap)
genofile <- snpGDSOpen(snpGDSExampleFileName())

#####
# CEU population

CEU.id <- read.gdsn(index.gdsn(genofile, "sample.id"))[
  read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))=="CEU"]
pibd <- snpGDSIBDMoM(genofile, sample.id=CEU.id)
names(pibd)

flag <- lower.tri(pibd$k0)
plot(NaN, xlim=c(0,1), ylim=c(0,1), xlab="k0", ylab="k1")
lines(c(0,1), c(1,0), col="red", lty=3)
points(pibd$k0[flag], pibd$k1[flag])

# select a set of pairs of individuals
d <- snpGDSIBDSelection(pibd, kinship.cutoff=1/8)
head(d)

#####
# YRI population

YRI.id <- read.gdsn(index.gdsn(genofile, "sample.id"))[
  read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))=="YRI"]
pibd <- snpGDSIBDMoM(genofile, sample.id=YRI.id)
flag <- lower.tri(pibd$k0)
plot(NaN, xlim=c(0,1), ylim=c(0,1), xlab="k0", ylab="k1")
lines(c(0,1), c(1,0), col="red", lty=3)
points(pibd$k0[flag], pibd$k1[flag])

# specify the allele frequencies
afreq <- snpGDSSNPRateFreq(genofile, sample.id=YRI.id)$AlleleFreq
aibd <- snpGDSIBDMoM(genofile, sample.id=YRI.id, allele.freq=afreq)
flag <- lower.tri(aibd$k0)
plot(NaN, xlim=c(0,1), ylim=c(0,1), xlab="k0", ylab="k1")
lines(c(0,1), c(1,0), col="red", lty=3)
points(aibd$k0[flag], aibd$k1[flag])
```

```
# analysis on a subset
subibd <- snpGdsIBDMoM(genofile, sample.id=YRI.id[1:25], allele.freq=afreq)
summary(c(subibd$k0 - aibd$k0[1:25, 1:25]))
# ZERO
summary(c(subibd$k1 - aibd$k1[1:25, 1:25]))
# ZERO

# close the genotype file
snpGdsClose(genofile)
```

---

snpGdsIBDSelection      *Get a table of IBD coefficients*

---

### Description

Return a data frame with IBD coefficients.

### Usage

```
snpGdsIBDSelection(ibdobj, kinship.cutoff=NaN, samp.sel=NULL)
```

### Arguments

**ibdobj**            an object of snpGdsIBDClass returned by [snpGdsIBDML](#) or [snpGdsIBDMoM](#)

**kinship.cutoff**   select the individual pairs with kinship coefficients  $\geq$  kinship.cutoff; no filter if kinship.cutoff = NaN

**samp.sel**          a logical vector or integer vector to specify selection of samples

### Value

Return a data.frame:

**ID1**              the id of the first individual

**ID2**              the id of the second individual

**k0**                the probability of sharing ZERO alleles

**k1**                the probability of sharing ONE alleles

**kinship**          kinship coefficient

### Author(s)

Xiuwen Zheng

### See Also

[snpGdsIBDML](#), [snpGdsIBDMoM](#), [snpGdsIBDKING](#)

**Examples**

```

# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

# YRI population
YRI.id <- read.gdsn(index.gdsn(genofile, "sample.id"))[
  read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))=="YRI"]
pibd <- snpGdsIBDMoM(genofile, sample.id=YRI.id)
flag <- lower.tri(pibd$k0)
plot(NaN, xlim=c(0,1), ylim=c(0,1), xlab="k0", ylab="k1")
lines(c(0,1), c(1,0), col="red", lty=3)
points(pibd$k0[flag], pibd$k1[flag])

# close the genotype file
snpGdsClose(genofile)

# IBD coefficients
dat <- snpGdsIBDSelection(pibd, 1/32)
head(dat)
#      ID1      ID2      k0      k1      kinship
# 1 NA19152 NA19154 0.010749154 0.9892508 0.24731271
# 2 NA19152 NA19093 0.848207777 0.1517922 0.03794806
# 3 NA19139 NA19138 0.010788047 0.9770181 0.25035144
# 4 NA19139 NA19137 0.012900661 0.9870993 0.24677483
# 5 NA18912 NA18914 0.008633077 0.9913669 0.24784173
# 6 NA19160 NA19161 0.008635754 0.9847777 0.24948770

```

---

snpGdsIBS

*Identity-By-State (IBS) proportion*


---

**Description**

Calculate the fraction of identity by state for each pair of samples

**Usage**

```

snpGdsIBS(gdsobj, sample.id = NULL, snp.id = NULL, autosome.only = TRUE,
  remove.monosnp = TRUE, maf = NaN, missing.rate = NaN,
  num.thread = 1, verbose = TRUE)

```

**Arguments**

<code>gdsobj</code>	an object of class <code>SNPGDSFileClass</code> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if <code>NULL</code> , all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if <code>NULL</code> , all SNPs are used
<code>autosome.only</code>	if <code>TRUE</code> , use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if <code>TRUE</code> , remove monomorphic SNPs

maf	to use the SNPs with " $\geq$ maf" only; if NaN, no MAF threshold
missing.rate	to use the SNPs with " $\leq$ missing.rate" only; if NaN, no missing threshold
num.thread	the number of (CPU) cores used; if NA, detect the number of cores automatically
verbose	if TRUE, show information

### Details

The minor allele frequency and missing rate for each SNP passed in `snp.id` are calculated over all the samples in `sample.id`.

The values of the IBS matrix range from ZERO to ONE.

### Value

Return a list (class "snpgdsIBSClass"):

sample.id	the sample ids used in the analysis
snp.id	the SNP ids used in the analysis
ibs	a matrix of IBS proportion, "# of samples" x "# of samples"

### Author(s)

Xiuwen Zheng

### See Also

[snpgdsIBSNum](#)

### Examples

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

# perform identity-by-state calculations
ibs <- snpgdsIBS(genofile)

# perform multidimensional scaling analysis on
# the genome-wide IBS pairwise distances:
loc <- cmdscale(1 - ibs$ibs, k = 2)
x <- loc[, 1]; y <- loc[, 2]
race <- as.factor(read.gdsn(index.gdsn(genofile, "sample.annot/pop.group")))
plot(x, y, col=race, xlab = "", ylab = "", main = "cmdscale(IBS Distance)")
legend("topleft", legend=levels(race), text.col=1:nlevels(race))

# close the file
snpgdsClose(genofile)
```

---

snpgdsIBSNum	<i>Identity-By-State (IBS)</i>
--------------	--------------------------------

---

### Description

Calculate the number of SNPs for identity by state for each pair of samples.

### Usage

```
snpgdsIBSNum(gdsobj, sample.id = NULL, snp.id = NULL, autosome.only = TRUE,
  remove.monosnp = TRUE, maf = NaN, missing.rate = NaN, num.thread = 1,
  verbose = TRUE)
```

### Arguments

<code>gdsobj</code>	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if NULL, all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
<code>autosome.only</code>	if TRUE, use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if TRUE, remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " $\geq$ maf" only; if NaN, no MAF threshold
<code>missing.rate</code>	to use the SNPs with " $\leq$ missing.rate" only; if NaN, no missing threshold
<code>num.thread</code>	the number of (CPU) cores used; if NA, detect the number of cores automatically
<code>verbose</code>	if TRUE, show information

### Details

The minor allele frequency and missing rate for each SNP passed in `snp.id` are calculated over all the samples in `sample.id`.

### Value

Return a list (n is the number of samples):

<code>sample.id</code>	the sample ids used in the analysis
<code>snp.id</code>	the SNP ids used in the analysis
<code>ibs0</code>	a n-by-n matrix, the number of SNPs sharing 0 IBS
<code>ibs1</code>	a n-by-n matrix, the number of SNPs sharing 1 IBS
<code>ibs2</code>	a n-by-n matrix, the number of SNPs sharing 2 IBS

### Author(s)

Xiuwen Zheng

**See Also**[snpGdsIBS](#)**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

RV <- snpGdsIBSNum(genofile)
pop <- read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))
L <- order(pop)
image(RV$ibs0[L, L]/length(RV$snp.id))

# close the genotype file
snpGdsClose(genofile)
```

snpGdsIndInb

*Individual Inbreeding Coefficients***Description**

To calculate individual inbreeding coefficients using SNP genotype data

**Usage**

```
snpGdsIndInb(gdsobj, sample.id=NULL, snp.id=NULL,
  autosome.only=TRUE, remove.monosnp=TRUE, maf=NaN, missing.rate=NaN,
  method=c("mom.weir", "mom.visscher", "mle"), allele.freq=NULL,
  out.num.iter=TRUE, reltol=.Machine$double.eps^0.75, verbose=TRUE)
```

**Arguments**

<code>gdsobj</code>	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if NULL, all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
<code>autosome.only</code>	if TRUE, use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if TRUE, remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " $\geq$ maf" only; if NaN, no MAF threshold
<code>missing.rate</code>	to use the SNPs with " $\leq$ missing.rate" only; if NaN, no missing threshold
<code>method</code>	see details
<code>allele.freq</code>	to specify the allele frequencies; if NULL, the allele frequencies are estimated from the given samples
<code>out.num.iter</code>	output the numbers of iterations

reltol            relative convergence tolerance used in MLE; the algorithm stops if it is unable to reduce the value of log likelihood by a factor of  $\$reltol * (abs(log likelihood with the initial parameters) + reltol)$  at a step.

verbose           if TRUE, show information

### Details

The method can be: "mom.weir": a modified Visscher's estimator, proposed by Bruce Weir; "mom.visscher": Visscher's estimator described in Yang et al. (2010); "mle": the maximum likelihood estimation.

### Value

Return estimated inbreeding coefficient.

### Author(s)

Xiuwen Zheng

### References

Yang J, Benyamin B, McEvoy BP, Gordon S, Henders AK, Nyholt DR, Madden PA, Heath AC, Martin NG, Montgomery GW, Goddard ME, Visscher PM. 2010. Common SNPs explain a large proportion of the heritability for human height. Nat Genet. 42(7):565-9. Epub 2010 Jun 20.

### Examples

```
# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

rv <- snpGdsIndInb(genofile, method="mom.visscher")
head(rv$inbreeding)
summary(rv$inbreeding)

# close the genotype file
snpGdsClose(genofile)
```

---

snpGdsIndInbCoef            *Individual Inbreeding Coefficient*

---

### Description

To calculate an individual inbreeding coefficient using SNP genotype data

### Usage

```
snpGdsIndInbCoef(x, p, method = c("mom.weir", "mom.visscher", "mle"),
  reltol=.Machine$double.eps^0.75)
```



**Arguments**

x	SNP genotypes
p	allele frequencies
method	see details
reltol	relative convergence tolerance used in MLE; the algorithm stops if it is unable to reduce the value of log likelihood by a factor of $\$reltol * (abs(log likelihood with the initial parameters) + reltol)$ at a step.

**Details**

The method can be: "mom.weir": a modified Visscher's estimator, proposed by Bruce Weir; "mom.visscher": Visscher's estimator described in Yang et al. (2010); "mle": the maximum likelihood estimation.

**Value**

Return estimated inbreeding coefficient.

**Author(s)**

Xiuwen Zheng

**References**

Yang J, Benyamin B, McEvoy BP, Gordon S, Henders AK, Nyholt DR, Madden PA, Heath AC, Martin NG, Montgomery GW, Goddard ME, Visscher PM. 2010. Common SNPs explain a large proportion of the heritability for human height. Nat Genet. 42(7):565-9. Epub 2010 Jun 20.

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

chr1 <- read.gdsn(index.gdsn(genofile, "snp.id"))[
  read.gdsn(index.gdsn(genofile, "snp.chromosome"))==1]
chr1idx <- match(chr1, read.gdsn(index.gdsn(genofile, "snp.id")))

AF <- snpgdsSNPRateFreq(genofile)
g <- read.gdsn(index.gdsn(genofile, "genotype"), start=c(1,1), count=c(-1,1))

snpgdsIndInbCoef(g[chr1idx], AF$AlleleFreq[chr1idx], method="mom.weir")
snpgdsIndInbCoef(g[chr1idx], AF$AlleleFreq[chr1idx], method="mom.visscher")
snpgdsIndInbCoef(g[chr1idx], AF$AlleleFreq[chr1idx], method="mle")

# close the genotype file
snpgdsClose(genofile)
```

snpgdsLDMat

*Linkage Disequilibrium (LD) analysis***Description**

Return a LD matrix for SNP pairs.

**Usage**

```
snpgdsLDMat(gdsobj, sample.id=NULL, snp.id=NULL, slide=250L,
            method=c("composite", "r", "dprime", "corr", "cov"), mat.trim=FALSE,
            num.thread=1L, with.id=TRUE, verbose=TRUE)
```

**Arguments**

<code>gdsobj</code>	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if NULL, all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
<code>slide</code>	# of SNPs, the size of sliding window, see details
<code>method</code>	"composite", "r", "dprime", "corr", "cov", see details
<code>mat.trim</code>	if TRUE, trim the matrix when <code>slide &gt; 0</code> : the function returns a "num_slide x (n_snp - slide)" matrix
<code>num.thread</code>	the number of (CPU) cores used; if NA, detect the number of cores automatically
<code>with.id</code>	if TRUE, the returned value with <code>sample.id</code> and <code>sample.id</code>
<code>verbose</code>	if TRUE, show information

**Details**

Four methods can be used to calculate linkage disequilibrium values: "composite" for LD composite measure, "r" for R coefficient (by EM algorithm assuming HWE, it could be negative), "dprime" for D', and "corr" for correlation coefficient. The method "corr" is equivalent to "composite", when SNP genotypes are coded as: 0 – BB, 1 – AB, 2 – AA.

If `slide <= 0`, the function returns a n-by-n LD matrix where the value of i row and j column is LD of i and j SNPs. If `slide > 0`, it returns a m-by-n LD matrix where n is the number of SNPs, m is the size of sliding window, and the value of i row and j column is LD of j and j+i SNPs.

**Value**

Return a list:

<code>sample.id</code>	the sample ids used in the analysis
<code>snp.id</code>	the SNP ids used in the analysis
<code>LD</code>	a matrix of LD values
<code>slide</code>	the size of sliding window

**Author(s)**

Xiuwen Zheng

**References**

Weir B: Inferences about linkage disequilibrium. *Biometrics* 1979; 35: 235-254.

Weir B: *Genetic Data Analysis II*. Sunderland, MA: Sinauer Associates, 1996.

Weir BS, Cockerham CC: Complete characterization of disequilibrium at two loci; in Feldman MW (ed): *Mathematical Evolutionary Theory*. Princeton, NJ: Princeton University Press, 1989.

**See Also**

[snpGdsLDpair](#), [snpGdsLDpruning](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

# chromosome 15
snpset <- read.gdsn(index.gdsn(genofile, "snp.id"))[
  read.gdsn(index.gdsn(genofile, "snp.chromosome")) == 15]
length(snpset)

# LD matrix without sliding window
ld.noslide <- snpGdsLDMat(genofile, snp.id=snpset, slide=-1, method="composite")
# plot
image(t(ld.noslide$LD^2), col=terrain.colors(16))

# LD matrix with a sliding window
ld.slide <- snpGdsLDMat(genofile, snp.id=snpset, method="composite")
# plot
image(t(ld.slide$LD^2), col=terrain.colors(16))

# close the genotype file
snpGdsClose(genofile)
```

---

snpGdsLDpair

*Linkage Disequilibrium (LD)*

---

**Description**

Return a LD value between snp1 and snp2.

**Usage**

```
snpGdsLDpair(snp1, snp2, method = c("composite", "r", "dprime", "corr"))
```

**Arguments**

snp1	a vector of SNP genotypes (0 – BB, 1 – AB, 2 – AA)
snp2	a vector of SNP genotypes (0 – BB, 1 – AB, 2 – AA)
method	"composite", "r", "dprime", "corr", see details

**Details**

Four methods can be used to calculate linkage disequilibrium values: "composite" for LD composite measure, "r" for R coefficient (by EM algorithm assuming HWE, it could be negative), "dprime" for D', and "corr" for correlation coefficient. The method "corr" is equivalent to "composite", when SNP genotypes are coded as: 0 – BB, 1 – AB, 2 – AA.

**Value**

Return a numeric vector:

ld	a measure of linkage disequilibrium
if method = "r" or "dprime",	
pA_A	haplotype frequency of AA, the first locus is A and the second locus is A
pA_B	haplotype frequency of AB, the first locus is A and the second locus is B
pB_A	haplotype frequency of BA, the first locus is B and the second locus is A
pB_B	haplotype frequency of BB, the first locus is B and the second locus is B

**Author(s)**

Xiuwen Zheng

**References**

- Weir B: Inferences about linkage disequilibrium. *Biometrics* 1979; 35: 235-254.
- Weir B: *Genetic Data Analysis II*. Sunderland, MA: Sinauer Associates, 1996.
- Weir BS, Cockerham CC: Complete characterization of disequilibrium at two loci; in Feldman MW (ed): *Mathematical Evolutionary Theory*. Princeton, NJ: Princeton University Press, 1989.

**See Also**

[snpGdsLDMat](#), [snpGdsLDpruning](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

snp1 <- read.gdsn(index.gdsn(genofile, "genotype"), start=c(1,1), count=c(1,-1))
snp2 <- read.gdsn(index.gdsn(genofile, "genotype"), start=c(2,1), count=c(1,-1))

snpGdsLDpair(snp1, snp2, method = "composite")
```

```
snpGDSLDpair(snp1, snp2, method = "r")
snpGDSLDpair(snp1, snp2, method = "dprime")
snpGDSLDpair(snp1, snp2, method = "corr")

# close the genotype file
snpGDSClose(genofile)
```

---

snpGDSLDpruning

*Linkage Disequilibrium (LD) based SNP pruning*


---

## Description

Recursively removes SNPs within a sliding window

## Usage

```
snpGDSLDpruning(gdsobj, sample.id = NULL, snp.id = NULL, autosome.only = TRUE,
  remove.monosnp = TRUE, maf = NaN, missing.rate = NaN,
  method = c("composite", "r", "dprime", "corr"), slide.max.bp = 500000,
  slide.max.n = NA, ld.threshold = 0.2, num.thread = 1, verbose = TRUE)
```

## Arguments

<code>gdsobj</code>	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if NULL, all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
<code>autosome.only</code>	if TRUE, use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if TRUE, remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " $\geq$ maf" only; if NaN, no MAF threshold
<code>missing.rate</code>	to use the SNPs with " $\leq$ missing.rate" only; if NaN, no missing threshold
<code>method</code>	"composite", "r", "dprime", "corr", see details
<code>slide.max.bp</code>	the maximum basepairs in the sliding window
<code>slide.max.n</code>	the maximum number of SNPs in the sliding window
<code>ld.threshold</code>	the LD threshold
<code>num.thread</code>	the number of (CPU) cores used; if NA, detect the number of cores automatically
<code>verbose</code>	if TRUE, show information

## Details

The minor allele frequency and missing rate for each SNP passed in `snp.id` are calculated over all the samples in `sample.id`.

Four methods can be used to calculate linkage disequilibrium values: "composite" for LD composite measure, "r" for R coefficient (by EM algorithm assuming HWE, it could be negative), "dprime" for  $D'$ , and "corr" for correlation coefficient. The method "corr" is equivalent to "composite", when SNP genotypes are coded as: 0 – BB, 1 – AB, 2 – AA. The argument `ld.threshold` is the absolute value of measurement.

It is useful to generate a pruned subset of SNPs that are in approximate linkage equilibrium with each other. The function `snpgdsLDpruning` recursively removes SNPs within a sliding window based on the pairwise genotypic correlation. SNP pruning is conducted chromosome by chromosome, since SNPs in a chromosome can be considered to be independent with the other chromosomes.

The pruning algorithm on a chromosome is described as follows ( $n$  is the total number of SNPs on that chromosome):

- 1) Randomly select a starting position  $i$ , and let the current SNP set  $S = \{ i \}$ ;
- 2) For each right position  $j$  from  $i+1$  to  $n$ : if any LD between  $j$  and  $k$  is greater than `ld.threshold`, where  $k$  belongs to  $S$ , and both of  $j$  and  $k$  are in the sliding window, then skip  $j$ ; otherwise, let  $S$  be  $S + \{ j \}$ ;
- 3) For each left position  $j$  from  $i-1$  to 1: if any LD between  $j$  and  $k$  is greater than `ld.threshold`, where  $k$  belongs to  $S$ , and both of  $j$  and  $k$  are in the sliding window, then skip  $j$ ; otherwise, let  $S$  be  $S + \{ j \}$ ;
- 4) Output  $S$ , the final selection of SNPs.

## Value

Return a list of SNP IDs stratified by chromosomes.

## Author(s)

Xiuwen Zheng

## References

- Weir B: Inferences about linkage disequilibrium. *Biometrics* 1979; 35: 235-254.
- Weir B: *Genetic Data Analysis II*. Sunderland, MA: Sinauer Associates, 1996.
- Weir BS, Cockerham CC: Complete characterization of disequilibrium at two loci; in Feldman MW (ed): *Mathematical Evolutionary Theory*. Princeton, NJ: Princeton University Press, 1989.

## See Also

[snpgdsLDMat](#), [snpgdsLDpair](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

set.seed(1000)
snpset <- snpgdsLDpruning(genofile)
names(snpset)
# [1] "chr1" "chr2" "chr3" "chr4" "chr5" "chr6" "chr7" "chr8" "chr9"
# [10] "chr10" "chr11" "chr12" "chr13" "chr14" "chr15" "chr16" "chr17" "chr18"
# .....
head(snpset$chr1)
# [1] 1 2 3 4 5 6

# get SNP ids
snp.id <- unlist(snpset)

# close the genotype file
snpgdsClose(genofile)
```

snpgdsOpen

*Open a SNP GDS File***Description**

Open a SNP GDS file

**Usage**

```
snpgdsOpen(filename, readonly=TRUE, allow.duplicate=FALSE, allow.fork=FALSE)
```

**Arguments**

filename	the file name
readonly	whether read-only or not
allow.duplicate	if TRUE, it is allowed to open a GDS file with read-only mode when it has been opened in the same R session, see <a href="#">openfn.gds</a>
allow.fork	TRUE for parallel environment using forking, see <a href="#">openfn.gds</a>

**Details**

It is strongly suggested to call `snpgdsOpen` instead of `openfn.gds`, since `snpgdsOpen` will perform internal checking for data integrity.

**Value**

Return an object of class `SNPGDSFileClass`.

**Author(s)**

Xiuwen Zheng

**See Also**[snpgdsClose](#)**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

genofile

# close the file
snpgdsClose(genofile)
```

---

`snpgdsOption`*Option settings: chromosome coding, etc*

---

**Description**

Return an option list used by the SNPRelate package or a GDS file

**Usage**

```
snpgdsOption(gdsobj=NULL, autosome.start=1L, autosome.end=22L, ...)
```

**Arguments**

<code>gdsobj</code>	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
<code>autosome.start</code>	the starting index of autosome
<code>autosome.end</code>	the ending index of autosome
<code>...</code>	optional arguments for new chromosome coding

**Value**

A list

**Author(s)**

Xiuwen Zheng



**Examples**

```
# define the new chromosomes 'Z' and 'W'
snpGdsOption(Z=27L, W=28L)

# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

snpGdsOption(genofile)

# close the genotype file
snpGdsClose(genofile)
```

---

snpGdsPairIBD                      *Calculate Identity-By-Descent (IBD) Coefficients*

---

**Description**

Calculate the three IBD coefficients (k0, k1, k2) for non-inbred individual pairs by Maximum Likelihood Estimation (MLE) or PLINK Method of Moment (MoM).

**Usage**

```
snpGdsPairIBD(geno1, geno2, allele.freq,
  method=c("EM", "downhill.simplex", "MoM"), kinship.constraint=FALSE,
  max.niter=1000, reltol=sqrt(.Machine$double.eps), coeff.correct=TRUE,
  out.num.iter=TRUE, verbose=TRUE)
```

**Arguments**

geno1	the SNP genotypes for the first individual, 0 – BB, 1 – AB, 2 – AA, other values – missing
geno2	the SNP genotypes for the second individual, 0 – BB, 1 – AB, 2 – AA, other values – missing
allele.freq	the allele frequencies
method	"EM", "downhill.simplex", or "MoM", see details
kinship.constraint	if TRUE, constrict IBD coefficients ( $k_0, k_1, k_2$ ) in the genealogical region ( $k_0 k_1 \geq k_2^2$ )
max.niter	the maximum number of iterations
reltol	relative convergence tolerance; the algorithm stops if it is unable to reduce the value of log likelihood by a factor of $\text{reltol} * (\text{abs}(\log \text{likelihood with the initial parameters}) + \text{reltol})$ at a step.
coeff.correct	TRUE by default, see details
out.num.iter	if TRUE, output the numbers of iterations
verbose	if TRUE, show information

**Details**

If `method = "MoM"`, then PLINK Method of Moment without a allele-count-based correction factor is conducted. Otherwise, two numeric approaches for maximum likelihood estimation can be used: one is Expectation-Maximization (EM) algorithm, and the other is Nelder-Mead method or downhill simplex method. Generally, EM algorithm is more robust than downhill simplex method.

If `coeff.correct` is TRUE, the final point that is found by searching algorithm (EM or downhill simplex) is used to compare the six points (fullsib, offspring, halfsib, cousin, unrelated), since any numeric approach might not reach the maximum position after a finite number of steps. If any of these six points has a higher value of log likelihood, the final point will be replaced by the best one.

**Value**

Return a data.frame:

<code>k0</code>	IBD coefficient, the probability of sharing ZERO IBD
<code>k1</code>	IBD coefficient, the probability of sharing ONE IBD
<code>loglik</code>	the value of log likelihood
<code>niter</code>	the number of iterations

**Author(s)**

Xiuwen Zheng

**References**

- Milligan BG. 2003. Maximum-likelihood estimation of relatedness. *Genetics* 163:1153-1167.
- Weir BS, Anderson AD, Hepler AB. 2006. Genetic relatedness analysis: modern data and new challenges. *Nat Rev Genet.* 7(10):771-80.
- Choi Y, Wijsman EM, Weir BS. 2009. Case-control association testing in the presence of unknown relationships. *Genet Epidemiol* 33(8):668-78.
- Purcell S, Neale B, Todd-Brown K, Thomas L, Ferreira MAR, Bender D, Maller J, Sklar P, de Bakker PIW, Daly MJ & Sham PC. 2007. PLINK: a toolset for whole-genome association and population-based linkage analysis. *American Journal of Human Genetics*, 81.

**See Also**

[snpGdsPairIBDMLELogLik](#), [snpGdsIBDMLE](#), [snpGdsIBDMLELogLik](#), [snpGdsIBDMoM](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

YRI.id <- read.gdsn(index.gdsn(genofile, "sample.id"))[
  read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))=="YRI"]

# SNP pruning
set.seed(10)
```

```

snpset <- snpgdsLDpruning(genofile, sample.id=YRI.id, maf=0.05,
  missing.rate=0.05)
snpset <- unname(sample(unlist(snpset), 250))

# the number of samples
n <- 25

# specify allele frequencies
RF <- snpgdsSNPRateFreq(genofile, sample.id=YRI.id, snp.id=snpset,
  with.id=TRUE)
summary(RF$AlleleFreq)

subMLE <- snpgdsIBDMLE(genofile, sample.id=YRI.id[1:n], snp.id=RF$snp.id,
  allele.freq=RF$AlleleFreq)
subMoM <- snpgdsIBDMoM(genofile, sample.id=YRI.id[1:n], snp.id=RF$snp.id,
  allele.freq=RF$AlleleFreq)

# genotype matrix
mat <- snpgdsGetGeno(genofile, sample.id=YRI.id[1:n], snp.id=snpset,
  snpfirstdim=TRUE)

#####

rv <- NULL
for (i in 2:n)
{
  rv <- rbind(rv, snpgdsPairIBD(mat[,1], mat[,i], RF$AlleleFreq, "EM"))
  print(snpgdsPairIBDMLELogLik(mat[,1], mat[,i], RF$AlleleFreq,
    relatedness="unrelated", verbose=TRUE))
}
rv
summary(rv$k0 - subMLE$k0[1, 2:n])
summary(rv$k1 - subMLE$k1[1, 2:n])
# ZERO

rv <- NULL
for (i in 2:n)
  rv <- rbind(rv, snpgdsPairIBD(mat[,1], mat[,i], RF$AlleleFreq, "MoM"))
rv
summary(rv$k0 - subMoM$k0[1, 2:n])
summary(rv$k1 - subMoM$k1[1, 2:n])
# ZERO

# close the genotype file
snpgdsClose(genofile)

```

---

snpGdsPairIBDMLELogLik

*Log likelihood for MLE method in the Identity-By-Descent (IBD) Analysis*

---

### Description

Calculate the log likelihood values from maximum likelihood estimation.

### Usage

```
snpGdsPairIBDMLELogLik(geno1, geno2, allele.freq, k0=NaN, k1=NaN,
  relatedness=c("", "self", "fullsib", "offspring", "halfsib",
    "cousin", "unrelated"), verbose=TRUE)
```

### Arguments

geno1	the SNP genotypes for the first individual, 0 – BB, 1 – AB, 2 – AA, other values – missing
geno2	the SNP genotypes for the second individual, 0 – BB, 1 – AB, 2 – AA, other values – missing
allele.freq	the allele frequencies
k0	specified IBD coefficient
k1	specified IBD coefficient
relatedness	specify a relatedness, otherwise use the values of k0 and k1
verbose	if TRUE, show information

### Details

If (relatedness == "") and (k0 == NaN or k1 == NaN), then return the log likelihood values for each (k0, k1) stored in ibdobj.

If (relatedness == "") and (k0 != NaN) and (k1 != NaN), then return the log likelihood values for a specific IBD coefficient (k0, k1).

If relatedness is: "self", then k0 = 0, k1 = 0; "fullsib", then k0 = 0.25, k1 = 0.5; "offspring", then k0 = 0, k1 = 1; "halfsib", then k0 = 0.5, k1 = 0.5; "cousin", then k0 = 0.75, k1 = 0.25; "unrelated", then k0 = 1, k1 = 0.

### Value

The value of log likelihood.

### Author(s)

Xiuwen Zheng

## References

Milligan BG. 2003. Maximum-likelihood estimation of relatedness. *Genetics* 163:1153-1167.

Weir BS, Anderson AD, Hepler AB. 2006. Genetic relatedness analysis: modern data and new challenges. *Nat Rev Genet.* 7(10):771-80.

Choi Y, Wijsman EM, Weir BS. 2009. Case-control association testing in the presence of unknown relationships. *Genet Epidemiol* 33(8):668-78.

## See Also

[snpgdsPairIBD](#), [snpgdsIBDMLE](#), [snpgdsIBDMLELogLik](#), [snpgdsIBDMoM](#)

## Examples

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

YRI.id <- read.gdsn(index.gdsn(genofile, "sample.id"))[
  read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))=="YRI"]

# SNP pruning
set.seed(10)
snpset <- snpgdsLDpruning(genofile, sample.id=YRI.id, maf=0.05,
  missing.rate=0.05)
snpset <- unname(sample(unlist(snpset), 250))

# the number of samples
n <- 25

# specify allele frequencies
RF <- snpgdsSNPRateFreq(genofile, sample.id=YRI.id, snp.id=snpset,
  with.id=TRUE)
summary(RF$AlleleFreq)

subMLE <- snpgdsIBDMLE(genofile, sample.id=YRI.id[1:n], snp.id=RF$snp.id,
  allele.freq=RF$AlleleFreq)
subMoM <- snpgdsIBDMoM(genofile, sample.id=YRI.id[1:n], snp.id=RF$snp.id,
  allele.freq=RF$AlleleFreq)

# genotype matrix
mat <- snpgdsGetGeno(genofile, sample.id=YRI.id[1:n], snp.id=snpset,
  snpfirstdim=TRUE)

#####

rv <- NULL
for (i in 2:n)
{
  rv <- rbind(rv, snpgdsPairIBD(mat[,1], mat[,i], RF$AlleleFreq, "EM"))
  print(snpgdsPairIBDMLELogLik(mat[,1], mat[,i], RF$AlleleFreq,
```

```

        relatedness="unrelated", verbose=TRUE))
    }
    rv
    summary(rv$k0 - subMLE$k0[1, 2:n])
    summary(rv$k1 - subMLE$k1[1, 2:n])
    # ZERO

    rv <- NULL
    for (i in 2:n)
        rv <- rbind(rv, snpgdsPairIBD(mat[,1], mat[,i], RF$AlleleFreq, "MoM"))
    rv
    summary(rv$k0 - subMoM$k0[1, 2:n])
    summary(rv$k1 - subMoM$k1[1, 2:n])
    # ZERO

    # close the genotype file
    snpgdsClose(genofile)

```

---

snpgdsPairScore

*Genotype Score for Pairs of Individuals*


---

## Description

Calculate the genotype score for pairs of individuals based on identity-by-state (IBS) measure

## Usage

```

snpgdsPairScore(gdsobj, sample1.id, sample2.id, snp.id=NULL,
  method=c("IBS", "GVH", "HVG"),
  type=c("per.pair", "per.snp", "matrix", "gds.file"),
  with.id=TRUE, output=NULL, verbose=TRUE)

```

## Arguments

<code>gdsobj</code>	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
<code>sample1.id</code>	a vector of sample id specifying selected samples; if NULL, all samples are used
<code>sample2.id</code>	a vector of sample id specifying selected samples; if NULL, all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
<code>method</code>	"IBS" – identity-by-state score, "GVH" or "HVG", see Details
<code>type</code>	"per.pair", "per.snp" or "matrix", see Value
<code>with.id</code>	if TRUE, returns "sample.id" and "snp.id"; see Value
<code>output</code>	if type="gds.file", the file name
<code>verbose</code>	if TRUE, show information

## Details

Patient (sample1.id)	Coded Genotype	Donor (sample2.id)	Coded Genotype	IBS	GVH	HVG
AA	0	AA	0	2	0	0
AA	0	AB	1	1	0	1
AA	0	BB	2	0	2	2
AB	1	AA	0	1	1	0
AB	1	AB	1	2	0	0
AB	1	BB	2	1	1	0
BB	2	AA	0	0	2	2
BB	2	AB	1	1	0	1
BB	2	BB	2	2	0	0

**Value**

Return a list:

sample.id	the sample ids used in the analysis, if with .id=TRUE
snp.id	the SNP ids used in the analysis, if with .id=TRUE
score	a matrix of genotype score: if type="per.pair", a # of pairs-by-3 matrix with the first column for average scores, the second column for standard deviation and the third column for the valid number of SNPs; if type="per.snp", a 3-by-# of SNPs matrix with the first row for average scores, the second row for standard deviation and the third row for the valid number of individual pairs; if type="matrix", a # of pairs-by-# of SNPs matrix with rows for pairs of individuals

**Author(s)**

Xiuwen Zheng

**References**

Warren, E. H., Zhang, X. C., Li, S., Fan, W., Storer, B. E., Chien, J. W., Boeckh, M. J., et al. (2012). Effect of MHC and non-MHC donor/recipient genetic disparity on the outcome of allogeneic HCT. *Blood*, 120(14), 2796-806. doi:10.1182/blood-2012-04-347286

**See Also**

[snpGdsIBS](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGdsOpen(snpGdsExampleFileName())

# autosomal SNPs
selsnp <- snpGdsSelectSNP(genofile, autosome.only=TRUE, remove.monosnp=FALSE)
```

```

# sample ID
sample.id <- read.gdsn(index.gdsn(genofile, "sample.id"))
father.id <- read.gdsn(index.gdsn(genofile, "sample.annot/father.id"))

offspring.id <- sample.id[father.id != ""]
father.id <- father.id[father.id != ""]

# calculate average genotype scores
z1 <- snpGDSPairScore(genofile, offspring.id, father.id, snp.id=selsnp,
  method="IBS", type="per.pair")
names(z1)
z1$score

# calculate average genotype scores
z2 <- snpGDSPairScore(genofile, offspring.id, father.id, snp.id=selsnp,
  method="IBS", type="per.snp")
names(z2)
mean(z2$score["Avg",])
mean(z2$score["SD",])

plot(z2$score["Avg",], pch=20, cex=0.75, xlab="SNP Index", ylab="IBS score")

# calculate a matrix of genotype scores over samples and SNPs
z3 <- snpGDSPairScore(genofile, offspring.id, father.id, snp.id=selsnp,
  method="IBS", type="matrix")
dim(z3$score)

# output the score matrix to a GDS file
snpGDSPairScore(genofile, offspring.id, father.id, snp.id=selsnp,
  method="IBS", type="gds.file", output="tmp.gds")
(f <- snpGDSOpen("tmp.gds"))
snpGDSClose(f)

# close the file
snpGDSClose(genofile)

unlink("tmp.gds", force=TRUE)

```

---

snpGDSPCA

*Principal Component Analysis (PCA) on SNP genotype data*


---

### Description

To calculate the eigenvectors and eigenvalues for principal component analysis in GWAS.



**Usage**

```
snpGdsPCA(gdsobj, sample.id=NULL, snp.id=NULL, autosome.only=TRUE,
  remove.monosnp=TRUE, maf=NaN, missing.rate=NaN, eigen.cnt=32,
  num.thread=1L, bayesian=FALSE, need.genmat=FALSE, genmat.only=FALSE,
  eigen.method=c("DSPEVX", "DSPEV"), verbose=TRUE)
```

**Arguments**

<code>gdsobj</code>	an object of class <code>SNPGDSFileClass</code> , a SNP GDS file
<code>sample.id</code>	a vector of sample id specifying selected samples; if <code>NULL</code> , all samples are used
<code>snp.id</code>	a vector of snp id specifying selected SNPs; if <code>NULL</code> , all SNPs are used
<code>autosome.only</code>	if <code>TRUE</code> , use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
<code>remove.monosnp</code>	if <code>TRUE</code> , remove monomorphic SNPs
<code>maf</code>	to use the SNPs with " <code>&gt;= maf</code> " only; if <code>NaN</code> , no MAF threshold
<code>missing.rate</code>	to use the SNPs with " <code>&lt;= missing.rate</code> " only; if <code>NaN</code> , no missing threshold
<code>eigen.cnt</code>	output the number of eigenvectors; if <code>eigen.cnt &lt;= 0</code> , then return all eigenvectors
<code>num.thread</code>	the number of (CPU) cores used; if <code>NA</code> , detect the number of cores automatically
<code>bayesian</code>	if <code>TRUE</code> , use bayesian normalization
<code>need.genmat</code>	if <code>TRUE</code> , return the genetic covariance matrix
<code>genmat.only</code>	return the genetic covariance matrix only, do not compute the eigenvalues and eigenvectors
<code>eigen.method</code>	"DSPEVX" – compute the top <code>eigen.cnt</code> eigenvalues and eigenvectors using LAPACK::DSPEVX; "DSPEV" – to be compatible with SNPRelate_1.1.6 or earlier, using LAPACK::DSPEV; "DSPEVX" is significantly faster than "DSPEV" if only top principal components are of interest
<code>verbose</code>	if <code>TRUE</code> , show information

**Details**

The minor allele frequency and missing rate for each SNP passed in `snp.id` are calculated over all the samples in `sample.id`.

**Value**

Return a `snpGdsPCAClass` object, and it is a list:

<code>sample.id</code>	the sample ids used in the analysis
<code>snp.id</code>	the SNP ids used in the analysis
<code>eigenval</code>	eigenvalues
<code>eigenvect</code>	eigenvectors, "# of samples" x "eigen.cnt"
<code>varprop</code>	variance proportion for each principal component
<code>TraceXTX</code>	the trace of the genetic covariance matrix
<code>Bayesian</code>	whether use bayesian normalization
<code>genmat</code>	the genetic covariance matrix

**Author(s)**

Xiuwen Zheng

**References**

Patterson, N., Price, A. L. & Reich, D. Population structure and eigenanalysis. PLoS Genet. 2, e190 (2006).

**See Also**

[snpgdsPCACorr](#), [snpgdsPCASampLoading](#), [snpgdsPCASNPLoading](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

# run PCA
RV <- snpgdsPCA(genofile)

# eigenvalues
head(RV$eigenval)

# variance proportion (%)
head(round(RV$varprop*100, 2))
# [1] 12.23 5.84 1.01 0.95 0.84 0.74

#### there is no population information ####

# make a data.frame
tab <- data.frame(sample.id = RV$sample.id,
  EV1 = RV$eigenvect[,1], # the first eigenvector
  EV2 = RV$eigenvect[,2], # the second eigenvector
  stringsAsFactors = FALSE)
head(tab)
#  sample.id      EV1      EV2
# 1  NA19152 -0.08411287 -0.01226860
# 2  NA19139 -0.08360644 -0.01085849
# 3  NA18912 -0.08110808 -0.01184524
# 4  NA19160 -0.08680864 -0.01447106
# 5  NA07034 0.03109761 0.07709255
# 6  NA07055 0.03228450 0.08155730

# draw
plot(tab$EV2, tab$EV1, xlab="eigenvector 2", ylab="eigenvector 1")

#### there are population information ####

# get population information
```

```

# or pop_code <- scan("pop.txt", what=character())
# if it is stored in a text file "pop.txt"
pop_code <- read.gdsn(index.gdsn(genofile, "sample.annot/pop.group"))

# get sample id
samp.id <- read.gdsn(index.gdsn(genofile, "sample.id"))

# assume the order of sample IDs is as the same as population codes
cbind(samp.id, pop_code)
#      samp.id      pop_code
# [1,] "NA19152"    "YRI"
# [2,] "NA19139"    "YRI"
# [3,] "NA18912"    "YRI"
# [4,] "NA19160"    "YRI"
# [5,] "NA07034"    "CEU"
# ...

# make a data.frame
tab <- data.frame(sample.id = RV$sample.id,
  pop = factor(pop_code)[match(RV$sample.id, samp.id)],
  EV1 = RV$eigenvect[,1], # the first eigenvector
  EV2 = RV$eigenvect[,2], # the second eigenvector
  stringsAsFactors = FALSE)
head(tab)
#  sample.id pop      EV1      EV2
# 1  NA19152 YRI -0.08411287 -0.01226860
# 2  NA19139 YRI -0.08360644 -0.01085849
# 3  NA18912 YRI -0.08110808 -0.01184524
# 4  NA19160 YRI -0.08680864 -0.01447106
# 5  NA07034 CEU  0.03109761  0.07709255
# 6  NA07055 CEU  0.03228450  0.08155730

# draw
plot(tab$EV2, tab$EV1, col=as.integer(tab$pop),
  xlab="eigenvector 2", ylab="eigenvector 1")
legend("bottomright", legend=levels(tab$pop), pch="o", col=1:4)

# close the file
snpGdsClose(genofile)

```

**Description**

To calculate the SNP correlations between eigenvectors and SNP genotypes

**Usage**

```
snpgdsPCACorr(pcaobj, gdsobj, snp.id=NULL, eig.which=NULL, num.thread=1L,
              verbose=TRUE)
```

**Arguments**

pcaobj	the snpgdsPCAClass object returned from the function <a href="#">snpgdsPCA</a>
gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
eig.which	a vector of integers, to specify which eigenvectors to be used
num.thread	the number of (CPU) cores used; if NA, detect the number of cores automatically
verbose	if TRUE, show information

**Value**

Return a list:

sample.id	the sample ids used in the analysis
snp.id	the SNP ids used in the analysis
snpcorr	a matrix of correlation coefficients, "# of eigenvectors" x "# of SNPs"

**Author(s)**

Xiuwen Zheng

**References**

Patterson N, Price AL, Reich D (2006) Population structure and eigenanalysis. *PLoS Genetics* 2:e190.

**See Also**

[snpgdsPCA](#), [snpgdsPCASampLoading](#), [snpgdsPCASNPLoading](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())
# get chromosome index
chr <- read.gdsn(index.gdsn(genofile, "snp.chromosome"))

pca <- snpgdsPCA(genofile)
CORR <- snpgdsPCACorr(pca, genofile, eig.which=1:4)
plot(abs(CORR$snpcorr[3,]), xlab="SNP Index", ylab="PC 3", col=chr)

# close the file
snpgdsClose(genofile)
```

---

snpGdsPCASampLoading *Project individuals onto existing principal component axes*

---

### Description

To calculate the sample eigenvectors using the specified SNP loadings

### Usage

```
snpGdsPCASampLoading(loadobj, gdsobj, sample.id=NULL, num.thread=1L,
  verbose=TRUE)
```

### Arguments

loadobj	the snpGdsPCASNPLoadingClass object, returned from <a href="#">snpGdsPCASNPLoading</a>
gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
sample.id	a vector of sample id specifying selected samples; if NULL, all samples are used
num.thread	the number of CPU cores used
verbose	if TRUE, show information

### Details

The sample.id are usually different from the samples used in the calculation of SNP loadings.

### Value

Return a snpGdsPCAClass object, and it is a list:

sample.id	the sample ids used in the analysis
snp.id	the SNP ids used in the analysis
eigenval	eigenvalues
eigenvect	eigenvectors, “# of samples” x “eigen.cnt”
TraceXTX	the trace of the genetic covariance matrix
Bayesian	whether use bayesian normalization

### Author(s)

Xiuwen Zheng

### References

Patterson N, Price AL, Reich D (2006) Population structure and eigenanalysis. *PLoS Genetics* 2:e190.

Zhu, X., Li, S., Cooper, R. S., and Elston, R. C. (2008). A unified association analysis approach for family and unrelated samples correcting for stratification. *Am J Hum Genet*, 82(2), 352-365.

**See Also**

[snpgdsPCA](#), [snpgdsPCACorr](#), [snpgdsPCASNPLoading](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

sample.id <- read.gdsn(index.gdsn(genofile, "sample.id"))

PCARV <- snpgdsPCA(genofile, eigen.cnt=8)
SnpLoad <- snpgdsPCASNPLoading(PCARV, genofile)

# calculate sample eigenvectors from SNP loadings
SL <- snpgdsPCASampLoading(SnpLoad, genofile, sample.id=sample.id[1:100])

diff <- PCARV$eigenvect[1:100,] - SL$eigenvect
summary(c(diff))
# ~ ZERO

# close the genotype file
snpgdsClose(genofile)
```

---

snpgdsPCASNPLoading    *SNP loadings in principal component analysis*

---

**Description**

To calculate the SNP loadings in Principal Component Analysis

**Usage**

```
snpgdsPCASNPLoading(pcaobj, gdsobj, num.thread=1L, verbose=TRUE)
```

**Arguments**

pcaobj	the snpgdsPCAClass object returned from the function <a href="#">snpgdsPCA</a>
gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
num.thread	the number of (CPU) cores used; if NA, detect the number of cores automatically
verbose	if TRUE, show information

**Details**

Calculate the SNP loadings (or SNP eigenvectors) from the principal component analysis conducted in snpgdsPCA.

**Value**

Return a snpgdsPCASNPLoading object, which is a list:

sample.id	the sample ids used in the analysis
snp.id	the SNP ids used in the analysis
eigenval	eigenvalues
snploading	the SNP loadings, or SNP eigenvectors
TraceXTX	the trace of the genetic covariance matrix
Bayesian	whether use bayesian normalization
avefreq	the allele frequency used in snpgdsPCA
scale	internal parameter

**Author(s)**

Xiuwen Zheng

**References**

Patterson N, Price AL, Reich D (2006) Population structure and eigenanalysis. *PLoS Genetics* 2:e190.

Price AL, Patterson NJ, Plenge RM, Weinblatt ME, Shadick NA, Reich D (2006) Principal components analysis corrects for stratification in genome-wide association studies. *Nat Genet.* 38, 904-909.

Zhu, X., Li, S., Cooper, R. S., and Elston, R. C. (2008). A unified association analysis approach for family and unrelated samples correcting for stratification. *Am J Hum Genet*, 82(2), 352-365.

**See Also**

[snpgdsPCA](#), [snpgdsPCASampLoading](#), [snpgdsPCACorr](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

PCARV <- snpgdsPCA(genofile, eigen.cnt=8)
SnpLoad <- snpgdsPCASNPLoading(PCARV, genofile)

names(SnpLoad)
# [1] "sample.id" "snp.id" "eigenval" "snploading" "TraceXTX"
# [6] "Bayesian" "avefreq" "scale"
dim(SnpLoad$snploading)
# [1] 8 8722

plot(SnpLoad$snploading[1,], type="h", ylab="PC 1")

# close the genotype file
snpgdsClose(genofile)
```

---

 snpgdsPED2GDS

*Conversion from PLINK PED to GDS*


---

**Description**

Convert a PLINK PED text file to a GDS file.

**Usage**

```
snpgdsPED2GDS(ped.fn, map.fn, out.gdsfn, family=TRUE, snpfirstdim=FALSE,
              compress.annotation="ZIP_RA.max", compress.geno="", verbose=TRUE)
```

**Arguments**

ped.fn	the file name of PED file, genotype information
map.fn	the file name of MAP file
out.gdsfn	the output GDS file
family	if TRUE, to include family information in the sample annotation
snpfirstdim	if TRUE, genotypes are stored in the individual-major mode, (i.e, list all SNPs for the first individual, and then list all SNPs for the second individual, etc)
compress.annotation	the compression method for the GDS variables, except "genotype"; optional values are defined in the function add.gdsn
compress.geno	the compression method for "genotype"; optional values are defined in the function add.gdsn
verbose	if TRUE, show information

**Details**

GDS – Genomic Data Structures, the extended file name used for storing genetic data, and the file format is used in the [gdsfmt](#) package.

PED – PLINK PED format.

**Value**

None.

**Author(s)**

Xiuwen Zheng

**References**

Purcell S, Neale B, Todd-Brown K, Thomas L, Ferreira MAR, Bender D, Maller J, Sklar P, de Bakker PIW, Daly MJ & Sham PC. 2007. PLINK: a toolset for whole-genome association and population-based linkage analysis. *American Journal of Human Genetics*, 81.



**See Also**

[snpGDS2PED](#), [snpGDSBED2GDS](#), [snpGDS2BED](#)

**Examples**

```
# open
genofile <- snpGDSOpen(snpGDSExampleFileName())

snpGDS2PED(genofile, "tmp")

# close
snpGDSClose(genofile)

# PED ==> GDS
snpGDS2PED2GDS("tmp.ped", "tmp.map", "test.gds")

# delete the temporary file
unlink(c("tmp.ped", "tmp.map", "test.gds"), force=TRUE)
```

---

snpGDSampMissRate      *Missing Rate of Samples*

---

**Description**

Return the missing fraction for each sample

**Usage**

```
snpGDSampMissRate(gdsobj, sample.id=NULL, snp.id=NULL, with.id=FALSE)
```

**Arguments**

gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
sample.id	a vector of sample id specifying selected samples; if NULL, all samples will be used
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs will be used
with.id	if TRUE, the returned value with sample id

**Value**

A vector of numeric values.

**Author(s)**

Xiuwen Zheng

**See Also**

[snpgdsSNPRateFreq](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

RV <- snpgdsSampMissRate(genofile)
summary(RV)

# close the genotype file
snpgdsClose(genofile)
```

---

snpgdsSelectSNP      *SNP selection*

---

**Description**

Create a list of candidate SNPs based on specified criteria

**Usage**

```
snpgdsSelectSNP(gdsobj, sample.id=NULL, snp.id=NULL, autosome.only=TRUE,
  remove.monosnp=TRUE, maf=NaN, missing.rate=NaN, verbose=TRUE)
```

**Arguments**

gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
sample.id	a vector of sample id specifying selected samples; if NULL, all samples will be used
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs will be used
autosome.only	if TRUE, use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
remove.monosnp	if TRUE, remove monomorphic SNPs
maf	to use the SNPs with " $\geq$ maf" only; if NaN, no any MAF threshold
missing.rate	to use the SNPs with " $\leq$ missing.rate" only; if NaN, no any missing threshold
verbose	if TRUE, show information

**Value**

Return a list of snp ids.

**Author(s)**

Xiuwen Zheng

**See Also**

[snpGDSsampMissRate](#), [snpGDSsnprateFreq](#), [snpGDSLDpruning](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGDSOpen(snpGDSExampleFileName())

snpset <- snpGDSselectSNP(genofile, maf=0.05, missing.rate=0.95)
length(snpset)
# 7502

# close the genotype file
snpGDSclose(genofile)
```

---

snpGDSslidingWindow     *Sliding window*

---

**Description**

Apply a user-defined function with a sliding window.

**Usage**

```
snpGDSslidingWindow(gdsobj, sample.id=NULL, snp.id=NULL,
  FUN=NULL, winsize=100000L, shift=10000L, unit=c("basepair", "locus"),
  wstart=NULL, autosome.only=FALSE, remove.monosnp=TRUE, maf=NaN,
  missing.rate=NaN, as.is=c("list", "numeric", "array"),
  with.id=c("snp.id", "snp.id.in.window", "none"), num.thread=1,
  verbose=TRUE, ...)
```

**Arguments**

gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
sample.id	a vector of sample id specifying selected samples; if NULL, all samples are used
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs are used
FUN	the user-defined function, see details
winsize	the size of sliding window
shift	the amount of shifting the sliding window
unit	"basepair" – winsize and shift are applied with SNP coordinate of basepair; "locus" – winsize and shift are applied according to the SNP order in the GDS file
wstart	NULL – no specific starting position; an integer – a starting position for all chromosomes; or a vector of integer – the starting positions for each chromosome

autosome.only	if TRUE, use autosomal SNPs only; if it is a numeric or character value, keep SNPs according to the specified chromosome
remove.monosnp	if TRUE, remove monomorphic SNPs
maf	to use the SNPs with " $\geq$ maf" only; if NaN, no MAF threshold
missing.rate	to use the SNPs with " $\leq$ missing.rate" only; if NaN, no missing threshold
as.is	save the value returned from FUN as "list" or "numeric"; "array" is equivalent to "numeric" except some cases, see details
with.id	"snp.id", "snp.id.in.window" or "none"
num.thread	the number of (CPU) cores used; if NA, detect the number of cores automatically
verbose	if TRUE, show information
...	optional arguments to FUN

### Details

If FUN="snpgdsFst", two additional arguments "population" and "method" should be specified. "population" and "method" are defined in [snpgdsFst](#). "as.is" could be "list" (returns a list of the values from [snpgdsFst](#)), "numeric" ( population-average Fst, returns a vector) or "array" (population-average and -specific Fst, returns a '# of pop + 1'-by-'# of windows' matrix, and the first row is population-average Fst).

If FUN="snpgdsSNPRateFreq", .

### Value

Return a list

### Author(s)

Xiuwen Zheng

### Examples

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

# sliding windows
rv <- snpgdsSlidingWindow(genofile, winsize=500000, shift=100000,
  FUN=function(...) NULL)

# plot
plot(rv$chr1.num, ylab="# of SNPs in the sliding window")

# close the genotype file
snpgdsClose(genofile)
```

---

snpGDS_SNPList	<i>Create a SNP list object</i>
----------------	---------------------------------

---

**Description**

A list object of SNP information including rs, chr, pos, allele and allele frequency.

**Usage**

```
snpGDS_SNPList(gdsobj, sample.id=NULL)
```

**Arguments**

gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
sample.id	a vector of sample id specifying selected samples; if NULL, all samples are used

**Value**

Return an object of `snpGDS_SNPListClass` including the following components:

rs.id	SNP id
chromosome	SNP chromosome index
position	SNP physical position in basepair
allele	reference / non-ref alleles
afreq	allele frequency

**Author(s)**

Xiuwen Zheng

**See Also**

[snpGDS\\_SNPListIntersect](#), [snpGDS\\_SNPListStrand](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGDSOpen(snpGDSExampleFileName())

# to get a snp list object
snplist <- snpGDS_SNPList(genofile)

# close the file
snpGDS_Close(genofile)
```

---

snpGdsSNPListClass     *the class of a SNP list*

---

**Description**

the class of a SNP list, and its instance is returned from [snpGdsSNPList](#).

**Value**

Return an object of “snpGdsSNPListClass” including the following components:

rs.id	SNP id
chromosome	SNP chromosome index
position	SNP physical position in basepair
allele	reference / non-ref alleles
afreq	allele frequency

**Author(s)**

Xiuwen Zheng

**See Also**

[snpGdsSNPList](#), [snpGdsSNPListIntersect](#)

---

snpGdsSNPListIntersect

*Get a common SNP list between two SNP list objects*

---

**Description**

Get a common SNP list by comparing their rs id, chromosome indices and positions.

**Usage**

```
snpGdsSNPListIntersect(snplist1, snplist2)
```

**Arguments**

snplist1	the first SNP list object <a href="#">snpGdsSNPListClass</a>
snplist2	the second SNP list object <a href="#">snpGdsSNPListClass</a>

**Value**

Return an object of `snpGDS_SNPListClass` including the following components:

<code>rs.id</code>	SNP id
<code>chromosome</code>	SNP chromosome index
<code>position</code>	SNP physical position in basepair
<code>allele</code>	reference / non-ref alleles from the first SNP list object
<code>afreq</code>	allele frequency from the first SNP list object

**Author(s)**

Xiuwen Zheng

**See Also**

[snpGDS\\_SNPList](#), [snpGDS\\_SNPListStrand](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpGDS_Open(snpGDS_ExampleFileName())

# to get a snp list object
snplist1 <- snpGDS_SNPList(genofile)
snplist2 <- snpGDS_SNPList(genofile)

# a common snp list
snplist <- snpGDS_SNPListIntersect(snplist1, snplist2)

summary(snplist$afreq)

# close the file
snpGDS_Close(genofile)
```

---

`snpGDS_SNPListStrand`    *Switch allele strand.*

---

**Description**

To get a logical vector, indicating whether allele references of `snplist2` need to be switched, with respect to `snplist1`.

**Usage**

```
snpGDS_SNPListStrand(snplist1, snplist2, same.strand=FALSE)
```

**Arguments**

snplist1            the first SNP list object “snpgdsSNPListClass”  
 snplist2            the second SNP list object “snpgdsSNPListClass”  
 same.strand        TRUE assuming alleles are on the same strand (e.g., forward strand); otherwise,  
                       FALSE not assuming whether on the same strand or not

**Value**

a logical vector, where TRUE indicates the allele references need to be switched, and NA indicates that locus is not in the common snp list.

**Author(s)**

Xiuwen Zheng

**See Also**

[snpgdsSNPList](#), [snpgdsSNPListStrand](#)

**Examples**

```

# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

# to get a snp list object
snplist1 <- snpgdsSNPList(genofile)
snplist2 <- snpgdsSNPList(genofile)

# a common snp list
L <- snpgdsSNPListStrand(snplist1, snplist2)

table(L, exclude=NULL)

# close the file
snpgdsClose(genofile)

```

---

snpgdsSNPRateFreq        *Allele Frequency, Minor Allele Frequency, Missing Rate of SNPs*

---

**Description**

Calculate the allele frequency, minor allele frequency and missing rate per SNP.

**Usage**

```
snpgdsSNPRateFreq(gdsobj, sample.id=NULL, snp.id=NULL, with.id=FALSE)
```



**Arguments**

gdsobj	an object of class <a href="#">SNPGDSFileClass</a> , a SNP GDS file
sample.id	a vector of sample id specifying selected samples; if NULL, all samples will be used
snp.id	a vector of snp id specifying selected SNPs; if NULL, all SNPs will be used
with.id	if TRUE, return sample and SNP IDs

**Value**

Return a list:

AlleleFreq	allele frequencies
MinorFreq	minor allele frequencies
MissingRate	missing rates
sample.id	sample id, if with.id=TRUE
snp.id	SNP id, if with.id=TRUE

**Author(s)**

Xiuwen Zheng

**See Also**

[snpgdsSampMissRate](#)

**Examples**

```
# open an example dataset (HapMap)
genofile <- snpgdsOpen(snpgdsExampleFileName())

RV <- snpgdsSNPRateFreq(genofile)
hist(RV$AlleleFreq, breaks=128)
summary(RV$MissingRate)

# close the file
snpgdsClose(genofile)
```

---

snpgdsSummary

*Summary of GDS genotype file*

---

**Description**

Print the information stored in the gds object

**Usage**

```
snpgdsSummary(gds, show=TRUE)
```

**Arguments**

`gds` a GDS file name, or an object of class `SNPGDSFileClass`  
`show` if TRUE, show information

**Value**

Return a list:

`sample.id` the IDs of valid samples  
`snp.id` the IDs of valid SNPs

**Author(s)**

Xiuwen Zheng

**Examples**

```
snpGDSSummary(snpGDSExampleFileName())
```

---

`snpGDSTranspose`      *Transpose genotypic matrix*

---

**Description**

Transpose the genotypic matrix if needed.

**Usage**

```
snpGDSTranspose(gds.fn, snpfirstdim=FALSE, compress=NULL, optimize=TRUE,
  verbose=TRUE)
```

**Arguments**

`gds.fn` the file name of SNP GDS format  
`snpfirstdim` if TRUE, genotypes are stored in snp-by-sample; if FALSE, sample-by-snp mode; if NA, force to transpose the SNP matrix  
`compress` the compression mode for SNP genotypes, optional values are defined in the function of `add.gdsn`; if NULL, to use the compression mode  
`optimize` if TRUE, call `cleanup.gds` after transposing  
`verbose` if TRUE, show information

**Value**

None.

**Author(s)**

Xiuwen Zheng

**Examples**

```
# the file name of SNP GDS
(fn <- snpGDSExampleFileName())

# copy the file
file.copy(fn, "test.gds", overwrite=TRUE)

# summary
snpGDSsummary("test.gds")

# transpose the SNP matrix
snpGDStranspose("test.gds", snpfirstdim=TRUE)

# summary
snpGDSsummary("test.gds")

# delete the temporary file
unlink("test.gds", force=TRUE)
```

snpGDSVCF2GDS

*Reformat VCF file(s)***Description**

Reformat Variant Call Format (VCF) file(s)

**Usage**

```
snpGDSVCF2GDS(vcf.fn, out.fn, method=c("biallelic.only", "copy.num.of.ref"),
  snpfirstdim=FALSE, compress.annotation="ZIP_RA.max", compress.geno="",
  ref.allele=NULL, ignore.chr.prefix="chr", verbose=TRUE)
```

**Arguments**

vcf.fn	the file name of VCF format, vcf.fn can be a vector, see details
out.fn	the file name of output GDS
method	either "biallelic.only" by default or "copy.num.of.ref", see details
snpfirstdim	if TRUE, genotypes are stored in the individual-major mode, (i.e, list all SNPs for the first individual, and then list all SNPs for the second individual, etc)
compress.annotation	the compression method for the GDS variables, except "genotype"; optional values are defined in the function add.gdsn

<code>compress.geno</code>	the compression method for "genotype"; optional values are defined in the function <code>add.gdsn</code>
<code>ref.allele</code>	NULL or a character vector indicating reference allele (like "A", "G", "T", NA, ...) for each site where NA to use the original reference allele in the VCF file(s). The length of character vector should be the total number of variants in the VCF file(s).
<code>ignore.chr.prefix</code>	a vector of character, indicating the prefix of chromosome which should be ignored, like "chr"; it is not case-sensitive
<code>verbose</code>	if TRUE, show information

### Details

GDS – Genomic Data Structures used for storing genetic array-oriented data, and the file format used in the [gdsfmt](#) package.

VCF – The Variant Call Format (VCF), which is a generic format for storing DNA polymorphism data such as SNPs, insertions, deletions and structural variants, together with rich annotations.

If there are more than one file names in `vcf.fn`, `snpgdsVCF2GDS` will merge all dataset together if they all contain the same samples. It is useful to combine genetic/genomic data together if VCF data are divided by chromosomes.

`method = "biallelic.only"`: to exact bi-allelic and polymorphic SNP data (excluding monomorphic variants); `method = "copy.num.of.ref"`: to extract and store dosage (0, 1, 2) of the reference allele for all variant sites, including bi-allelic SNPs, multi-allelic SNPs, indels and structural variants.

Haploid and triploid calls are allowed in the transfer, the variable `snp.id` stores the original the row index of variants, and the variable `snp.rs.id` stores the rs id.

When `snp.chromosome` in the GDS file is character, `SNPRelate` treats a chromosome as autosome only if it can be converted to a numeric value ( like "1", "22"). It uses "X" and "Y" for non-autosomes instead of numeric codes. However, some software format chromosomes in VCF files with a prefix "chr". Users should remove that prefix when importing VCF files by setting `ignore.chr.prefix = "chr"`.

### Value

Return the file name of GDS format with an absolute path.

### Author(s)

Xiuwen Zheng

### References

The variant call format and VCFtools. Danecek P, Auton A, Abecasis G, Albers CA, Banks E, DePristo MA, Handsaker RE, Lunter G, Marth GT, Sherry ST, McVean G, Durbin R; 1000 Genomes Project Analysis Group. *Bioinformatics*. 2011 Aug 1;27(15):2156-8. Epub 2011 Jun 7.

<http://corearray.sourceforge.net/>

**See Also**[snpgdsBED2GDS](#)**Examples**

```
# the VCF file
vcf.fn <- system.file("extdata", "sequence.vcf", package="SNPRelate")
cat(readLines(vcf.fn), sep="\n")

snpgdsVCF2GDS(vcf.fn, "test1.gds", method="biallelic.only")
snpgdsSummary("test1.gds")

snpgdsVCF2GDS(vcf.fn, "test2.gds", method="biallelic.only", snpfirstdim=TRUE)
snpgdsSummary("test2.gds")

snpgdsVCF2GDS(vcf.fn, "test3.gds", method="copy.num.of.ref", snpfirstdim=TRUE)
snpgdsSummary("test3.gds")

snpgdsVCF2GDS(vcf.fn, "test4.gds", method="copy.num.of.ref")
snpgdsSummary("test4.gds")

snpgdsVCF2GDS(vcf.fn, "test5.gds", method="copy.num.of.ref",
  ref.allele=c("A", "T", "T", "T", "A"))
snpgdsSummary("test5.gds")

# open "test1.gds"
(genofile <- snpgdsOpen("test1.gds"))

read.gdsn(index.gdsn(genofile, "sample.id"))
read.gdsn(index.gdsn(genofile, "snp.rs.id"))
read.gdsn(index.gdsn(genofile, "genotype"))

# close the file
snpgdsClose(genofile)

# open "test2.gds"
(genofile <- snpgdsOpen("test2.gds"))

read.gdsn(index.gdsn(genofile, "sample.id"))
read.gdsn(index.gdsn(genofile, "snp.rs.id"))
read.gdsn(index.gdsn(genofile, "genotype"))

# close the file
snpgdsClose(genofile)

# open "test3.gds"
(genofile <- snpgdsOpen("test3.gds"))
```

```
read.gdsn(index.gdsn(genofile, "sample.id"))
read.gdsn(index.gdsn(genofile, "snp.rs.id"))
read.gdsn(index.gdsn(genofile, "genotype"))

# close the file
snpgdsClose(genofile)

# open "test4.gds"
(genofile <- snpgdsOpen("test4.gds"))

read.gdsn(index.gdsn(genofile, "sample.id"))
read.gdsn(index.gdsn(genofile, "snp.rs.id"))
read.gdsn(index.gdsn(genofile, "snp.allele"))
read.gdsn(index.gdsn(genofile, "genotype"))

# close the file
snpgdsClose(genofile)

# open "test5.gds"
(genofile <- snpgdsOpen("test5.gds"))

read.gdsn(index.gdsn(genofile, "sample.id"))
read.gdsn(index.gdsn(genofile, "snp.rs.id"))
read.gdsn(index.gdsn(genofile, "snp.allele"))
read.gdsn(index.gdsn(genofile, "genotype"))

# close the file
snpgdsClose(genofile)

# delete the temporary files
unlink(paste("test", 1:5, ".gds", sep=""), force=TRUE)
```

---

snpgdsVCF2GDS\_R

*Reformat a VCF file (R implementation)*

---

## Description

Reformat a Variant Call Format (VCF) file

## Usage

```
snpgdsVCF2GDS_R(vcf.fn, out.fn, nblock=1024,
  method = c("biallelic.only", "copy.num.of.ref"),
  compress.annotation="ZIP_RA.max", snpfirstdim=FALSE, option = NULL,
  verbose=TRUE)
```

**Arguments**

<code>vcf.fn</code>	the file name of VCF format, <code>vcf.fn</code> can be a vector, see details
<code>out.fn</code>	the output gds file
<code>nblock</code>	the buffer lines
<code>method</code>	either "biallelic.only" by default or "copy.num.of.ref", see details
<code>compress.annotation</code>	the compression method for the GDS variables, except "genotype"; optional values are defined in the function <code>add.gdsn</code>
<code>snpfirstdim</code>	if TRUE, genotypes are stored in the individual-major mode, (i.e, list all SNPs for the first individual, and then list all SNPs for the second individual, etc)
<code>option</code>	NULL or an object from <a href="#">snpGDSOption</a> , see details
<code>verbose</code>	if TRUE, show information

**Details**

GDS – Genomic Data Structures used for storing genetic array-oriented data, and the file format used in the [gdsfmt](#) package.

VCF – The Variant Call Format (VCF), which is a generic format for storing DNA polymorphism data such as SNPs, insertions, deletions and structural variants, together with rich annotations.

If there are more than one file name in `vcf.fn`, `snpGDSVCF2GDS` will merge all dataset together once they all contain the same samples. It is useful to combine genetic data if VCF data are divided by chromosomes.

`method = "biallelic.only"`: to exact bi-allelic and polymorphic SNP data (excluding monomorphic variants); `method = "biallelic.only"`: to exact bi-allelic and polymorphic SNP data; `method = "copy.num.of.ref"`: to extract and store dosage (0, 1, 2) of the reference allele for all variant sites, including bi-allelic SNPs, multi-allelic SNPs, indels and structural variants.

Haploid and triploid calls are allowed in the transfer, the variable `snp.id` stores the original the row index of variants, and the variable `snp.rs.id` stores the rs id.

The user could use `option` to specify the range of code for autosomes. For humans there are 22 autosomes (from 1 to 22), but dogs have 38 autosomes. Note that the default settings are used for humans. The user could call `option = snpGDSOption(autosome.end=38)` for importing the VCF file of dog. It also allows defining new chromosome coding, e.g., `option = snpGDSOption(Z=27)`, then "Z" will be replaced by the number 27.

**Value**

None.

**Author(s)**

Xiuwen Zheng

## References

The variant call format and VCFtools. Danecek P, Auton A, Abecasis G, Albers CA, Banks E, DePristo MA, Handsaker RE, Lunter G, Marth GT, Sherry ST, McVean G, Durbin R; 1000 Genomes Project Analysis Group. *Bioinformatics*. 2011 Aug 1;27(15):2156-8. Epub 2011 Jun 7.

## See Also

[snpgdsVCF2GDS\\_R](#), [snpgdsOption](#), [snpgdsBED2GDS](#)

## Examples

```
# The VCF file
vcf.fn <- system.file("extdata", "sequence.vcf", package="SNPRelate")
cat(readLines(vcf.fn), sep="\n")

snpgdsVCF2GDS_R(vcf.fn, "test1.gds", method="biallelic.only")
snpgdsSummary("test1.gds")

snpgdsVCF2GDS_R(vcf.fn, "test2.gds", method="biallelic.only")
snpgdsSummary("test2.gds")

snpgdsVCF2GDS_R(vcf.fn, "test3.gds", method="copy.num.of.ref")
snpgdsSummary("test3.gds")

snpgdsVCF2GDS_R(vcf.fn, "test4.gds", method="copy.num.of.ref")
snpgdsSummary("test4.gds")
```



# Index

## \*Topic **GDS**

- [snpgdsAdmixProp, 6](#)
- [snpgdsAlleleSwitch, 8](#)
- [snpgdsApartSelection, 9](#)
- [snpgdsBED2GDS, 10](#)
- [snpgdsClose, 12](#)
- [snpgdsCombineGeno, 13](#)
- [snpgdsCreateGeno, 14](#)
- [snpgdsCreateGenoSet, 16](#)
- [snpgdsCutTree, 18](#)
- [snpgdsDiss, 20](#)
- [snpgdsDrawTree, 22](#)
- [snpgdsEIGMIX, 24](#)
- [snpgdsErrMsg, 26](#)
- [snpgdsExampleFileName, 27](#)
- [SNPGDSFileClass, 27](#)
- [snpgdsFst, 28](#)
- [snpgdsGDS2BED, 29](#)
- [snpgdsGDS2Eigen, 31](#)
- [snpgdsGDS2PED, 32](#)
- [snpgdsGEN2GDS, 33](#)
- [snpgdsGetGeno, 35](#)
- [snpgdsGRM, 36](#)
- [snpgdsHCluster, 38](#)
- [snpgdsHWE, 39](#)
- [snpgdsIBDKING, 40](#)
- [snpgdsIBDMLE, 43](#)
- [snpgdsIBDMLELogLik, 46](#)
- [snpgdsIBDMoM, 48](#)
- [snpgdsIBDSelection, 51](#)
- [snpgdsIBS, 52](#)
- [snpgdsIBSNum, 54](#)
- [snpgdsIndInb, 55](#)
- [snpgdsIndInbCoef, 56](#)
- [snpgdsLDMat, 58](#)
- [snpgdsLDpair, 59](#)
- [snpgdsLDpruning, 61](#)
- [snpgdsOpen, 63](#)
- [snpgdsOption, 64](#)

- [snpgdsPairIBD, 65](#)
- [snpgdsPairIBDMLELogLik, 68](#)
- [snpgdsPairScore, 70](#)
- [snpgdsPCA, 72](#)
- [snpgdsPCACorr, 75](#)
- [snpgdsPCASampLoading, 77](#)
- [snpgdsPCASNPLoading, 78](#)
- [snpgdsPED2GDS, 80](#)
- [snpgdsSampMissRate, 81](#)
- [snpgdsSelectSNP, 82](#)
- [snpgdsSlidingWindow, 83](#)
- [snpgdsSNPList, 85](#)
- [snpgdsSNPListClass, 86](#)
- [snpgdsSNPListIntersect, 86](#)
- [snpgdsSNPListStrand, 87](#)
- [snpgdsSNPRateFreq, 88](#)
- [snpgdsSummary, 89](#)
- [snpgdsTranspose, 90](#)
- [snpgdsVCF2GDS, 91](#)
- [SNPRelate-package, 3](#)

## \*Topic **GWAS**

- [snpgdsAdmixProp, 6](#)
- [snpgdsAlleleSwitch, 8](#)
- [snpgdsApartSelection, 9](#)
- [snpgdsBED2GDS, 10](#)
- [snpgdsClose, 12](#)
- [snpgdsCombineGeno, 13](#)
- [snpgdsCreateGeno, 14](#)
- [snpgdsCreateGenoSet, 16](#)
- [snpgdsCutTree, 18](#)
- [snpgdsDiss, 20](#)
- [snpgdsDrawTree, 22](#)
- [snpgdsEIGMIX, 24](#)
- [snpgdsErrMsg, 26](#)
- [snpgdsExampleFileName, 27](#)
- [SNPGDSFileClass, 27](#)
- [snpgdsFst, 28](#)
- [snpgdsGDS2BED, 29](#)
- [snpgdsGDS2Eigen, 31](#)

- snpGDS2PED, 32
- snpGDS2GDS, 33
- snpGDSGetGeno, 35
- snpGDSGRM, 36
- snpGDSHCluster, 38
- snpGDSHWE, 39
- snpGDSIBDKING, 40
- snpGDSIBDMLE, 43
- snpGDSIBDMLELogLik, 46
- snpGDSIBDMoM, 48
- snpGDSIBDSelection, 51
- snpGDSIBS, 52
- snpGDSIBSNum, 54
- snpGDSIndInb, 55
- snpGDSIndInbCoef, 56
- snpGDSLDMat, 58
- snpGDSLDpair, 59
- snpGDSLDpruning, 61
- snpGDSOpen, 63
- snpGDSOption, 64
- snpGDSPairIBD, 65
- snpGDSPairIBDMLELogLik, 68
- snpGDSPairScore, 70
- snpGDSPCA, 72
- snpGDSPCACorr, 75
- snpGDSPCASampLoading, 77
- snpGDSPCASNPLoading, 78
- snpGDSPED2GDS, 80
- snpGDSsmpMissRate, 81
- snpGDSselectSNP, 82
- snpGDSslidingWindow, 83
- snpGDSsnplList, 85
- snpGDSsnplListClass, 86
- snpGDSsnplListIntersect, 86
- snpGDSsnplListStrand, 87
- snpGDSsnprRateFreq, 88
- snpGDSsummary, 89
- snpGDStranspose, 90
- snpGDSVCF2GDS, 91
- snpGDSVCF2GDS\_R, 94
- SNPRelate-package, 3
- \*Topic **PCA**
  - snpGDSPCA, 72
  - snpGDSPCACorr, 75
  - snpGDSPCASampLoading, 77
  - snpGDSPCASNPLoading, 78
- \*Topic **datasets**
  - hapmap\_geno, 5
- \*Topic **gds**
  - snpGDSVCF2GDS\_R, 94
- cleanup.gds, 90
- closefn.gds, 12
- gds.class, 27, 32
- gdsfmt, 11, 30–32, 34, 80, 92, 95
- hapmap\_geno, 5
- hclust, 38
- openfn.gds, 63
- snpGDSAdmixProp, 6
- snpGDSAlleleSwitch, 8
- snpGDSApartSelection, 9
- snpGDSBED2GDS, 10, 30, 34, 81, 93, 96
- snpGDSClose, 12, 27, 64
- snpGDSCombineGeno, 13, 15, 17
- snpGDSCreateGeno, 14, 14, 17
- snpGDSCreateGenoSet, 14, 15, 16
- snpGDSCutTree, 18, 22, 23, 38
- snpGSDSDiss, 19, 20, 38
- snpGDSDrawTree, 19, 22
- snpGDSEIGMIX, 6, 7, 24, 25
- snpGDSErrMsg, 26
- snpGDSExampleFileName, 27
- SNPGDSFileClass, 8, 12, 20, 24, 27, 28, 30, 31, 35, 36, 39, 41, 44, 46, 49, 52, 54, 55, 58, 61, 63, 64, 70, 73, 76–78, 81–83, 85, 89, 90
- SNPGDSFileClass-class (SNPGDSFileClass), 27
- snpGDSfst, 28, 37, 84
- snpGDSGDS2BED, 29, 33, 81
- snpGDSGDS2Eigen, 31
- snpGDSGDS2PED, 12, 30, 31, 32, 81
- snpGDSGEN2GDS, 33
- snpGDSGetGeno, 35
- snpGDSGRM, 36
- snpGDSHCluster, 18, 19, 21, 38
- snpGDSHWE, 39
- snpGDSIBDKING, 40, 51
- snpGDSIBDMLE, 42, 43, 47, 50, 51, 66, 69
- snpGDSIBDMLELogLik, 45, 46, 50, 66, 69
- snpGDSIBDMoM, 42, 45, 47, 48, 51, 66, 69
- snpGDSIBDSelection, 51
- snpGDSIBS, 19, 38, 52, 55, 71

snpgdsIBSNum, [53](#), [54](#)  
snpgdsIndInb, [37](#), [55](#)  
snpgdsIndInbCoef, [56](#)  
snpgdsLDMat, [58](#), [60](#), [62](#)  
snpgdsLDpair, [59](#), [59](#), [62](#)  
snpgdsLDpruning, [10](#), [59](#), [60](#), [61](#), [83](#)  
snpgdsOpen, [13](#), [27](#), [63](#)  
snpgdsOption, [11](#), [12](#), [64](#), [95](#), [96](#)  
snpgdsPairIBD, [65](#), [69](#)  
snpgdsPairIBDMLELogLik, [66](#), [67](#)  
snpgdsPairScore, [70](#)  
snpgdsPCA, [6](#), [7](#), [25](#), [72](#), [76](#), [78](#), [79](#)  
snpgdsPCACorr, [74](#), [75](#), [78](#), [79](#)  
snpgdsPCASampLoading, [74](#), [76](#), [77](#), [79](#)  
snpgdsPCASNPLoading, [74](#), [76–78](#), [78](#)  
snpgdsPED2GDS, [12](#), [80](#)  
snpgdsSampMissRate, [81](#), [83](#), [89](#)  
snpgdsSelectSNP, [82](#)  
snpgdsSlidingWindow, [83](#)  
snpgdsSNPList, [85](#), [86–88](#)  
snpgdsSNPListClass, [13](#), [86](#), [86](#)  
snpgdsSNPListIntersect, [85](#), [86](#), [86](#)  
snpgdsSNPListStrand, [85](#), [87](#), [87](#), [88](#)  
snpgdsSNPRateFreq, [40](#), [82](#), [83](#), [88](#)  
snpgdsSummary, [89](#)  
snpgdsTranspose, [90](#)  
snpgdsVCF2GDS, [34](#), [91](#)  
snpgdsVCF2GDS\_R, [94](#), [96](#)  
SNPRelate (SNPRelate-package), [3](#)  
SNPRelate-package, [3](#)