

Package ‘geneAttribution’

November 21, 2024

Type Package

Title Identification of candidate genes associated with genetic variation

Version 1.32.0

Date 2016-10-16

Author Arthur Wuster

Maintainer Arthur Wuster <wustera@gene.com>

Description Identification of the most likely gene or genes through which variation at a given genomic locus in the human genome acts. The most basic functionality assumes that the closer gene is to the input locus, the more likely the gene is to be causative. Additionally, any empirical data that links genomic regions to genes (e.g. eQTL or genome conformation data) can be used if it is supplied in the UCSC .BED file format.

License Artistic-2.0

biocViews SNP, GenePrediction, GenomeWideAssociation, VariantAnnotation, GenomicVariation

Imports utils, GenomicRanges, org.Hs.eg.db, BiocGenerics, GenomeInfoDb, GenomicFeatures, IRanges, rtracklayer

Suggests TxDb.Hsapiens.UCSC.hg38.knownGene, TxDb.Hsapiens.UCSC.hg19.knownGene, knitr, rmarkdown, testthat

RoxygenNote 5.0.1

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/geneAttribution>

git_branch RELEASE_3_20

git_last_commit 7bbfdc1

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-20

Contents

geneAttribution	2
geneModels	3
loadBed	3
normP	4

geneAttribution	<i>geneAttribution: Identification of candidate genes associated with noncoding genetic variation</i>
-----------------	---

Description

Identification of the most likely gene or genes through which variation at a given genomic locus in the human genome acts. The most basic functionality assumes that the closer gene is to the input locus, the more likely the gene is to be causative. Additionally, any empirical data that links genomic regions to genes (e.g. eQTL or genome conformation data) can be used if it is supplied in UCSC .bed file format. A typical workflow requires loading gene models and empirical data, then running `geneAttribution()` on the locus of interest

Given genomic coordinate, return normalized probability for each gene

Usage

```
geneAttribution(chr, pos, geneCoordinates, empiricalData, lambda = 7.61e-06,
  maxDist = 1e+06, minPP = 0.01)
```

Arguments

<code>chr</code>	A character string representing a chromosome (e.g. "chr2")
<code>pos</code>	An integer representing a genomic position in the same genome build that gene models
<code>geneCoordinates</code>	A <code>GenomicRanges</code> object, as generated by <code>geneModels()</code>
<code>empiricalData</code>	A list of <code>GenomicRanges</code> objects, as generated by <code>loadBed()</code> . Optional
<code>lambda</code>	Float. Variable for exponential distribution. Default based on empirical eQTL data from multiple tissues. Optional
<code>maxDist</code>	Integer. Only genes within this distance of query locus are considered. Optional
<code>minPP</code>	Float. Genes with a posterior probability < <code>minPP</code> are lumped as "Other". Can be set to 0 when all genes should be reported. Optional

Value

A sorted, numeric vector of normalized gene probabilities

Examples

```
geneLocs <- geneModels()
fileName <- system.file("extdata", "eqlHaplotypeBlocks.b38.bed", package="geneAttribution")
empirical <- loadBed(fileName)
geneAttribution("chr2", 127156000, geneLocs, empirical)
```

 geneModels

Load gene models

Description

Get gene models as a GenomicRanges object, with gene names in the symbol column For hg19, you may want to use TxDb.Hsapiens.UCSC.hg19.knownGene and for GRCh38, TxDb.Hsapiens.UCSC.hg38.knownGene (set as default)

Usage

```
geneModels(txdb = TxDb.Hsapiens.UCSC.hg38.knownGene::TxDb.Hsapiens.UCSC.hg38.knownGene,
           maxGeneLength = 1e+06, genesToInclude, genesToExclude)
```

Arguments

txdb GenomicFeatures TxDb object containing genomic coordinates of genes
 maxGeneLength An integer. Gene models that are longer than this are excluded. Optional
 genesToInclude A character vector of gene symbols of genes to include (e.g. only protein coding genes). Optional
 genesToExclude A character vector of gene symbols of genes to exclude. Optional

Value

A GenomicRanges object containing human gene models

Examples

```
geneModels()
geneModels(genesToInclude = c("CYR1", "ADAMTS1", "ADAMTS5", "N6AMT1", "LTN1"))
```

 loadBed

*Load UCSC *.BED files containing empirical data*

Description

Required *.BED file format (tab-separated): chr start end name (optional column: score). Sample files supplied with package are limited to chromosome 2.

Usage

```
loadBed(files, weights)
```

Arguments

files A character vector containing *.BED file names
 weights An integer vector containing weighting for each bed file. Optional

Value

A list of GenomicRanges objects containing the data from the *.BED files, with weightings in the score column

Examples

```
fileName1 <- system.file("extdata", "hiCRegions.b38.bed", package="geneAttribution")
fileName2 <- system.file("extdata", "eqtlHaplotypeBlocks.b38.bed", package="geneAttribution")
loadBed(c(fileName1, fileName2), c(2, 5))
```

normP

Normalize likelihoods and return probabilities

Description

Normalize likelihoods and return probabilities

Usage

```
normP(pVector, minPP = 0)
```

Arguments

pVector A numeric vector of pre-normalization likelihoods
minPP A float. Genes with a posterior probability < minPP are lumped as "Other".
Optional

Value

A sorted, numeric vector of normalized probabilities

Examples

```
normP(c(5, 1, 1, 1, 1, 1, 0.1))
normP(c(5, 1, 1, 1, 1, 1, 0.1), minPP=0.1)
```

Index

geneAttribution, [2](#)
geneAttribution-package
 (geneAttribution), [2](#)
geneModels, [3](#)

loadBed, [3](#)

normP, [4](#)