

# Package ‘miRLAB’

April 14, 2017

**Type** Package

**Title** Dry lab for exploring miRNA-mRNA relationships

**Version** 1.4.0

**Date** 2016-01-05

**Author** Thuc Duy Le, Junpeng Zhang

**Maintainer** Thuc Duy Le <Thuc.Le@unisa.edu.au>

**Imports** RCurl, httr, stringr, Hmisc, energy, entropy, Roleswitch,  
gplots, glmnet, impute, limma, pcalg

## Description

Provide tools exploring miRNA-mRNA relationships, including popular miRNA target prediction methods, ensemble methods that integrate individual methods, functions to get data from on-line resources, functions to validate the results, and functions to conduct enrichment analyses.

**License** GPL (>=2)

**Suggests** knitr, RUnit, BiocGenerics, AnnotationDbi, org.Hs.eg.db,  
GOstats, Category

**VignetteBuilder** knitr

**biocViews** miRNA, GeneExpression, NetworkInference, Network

**NeedsCompilation** no

## R topics documented:

miRLAB-package . . . . .	2
Borda . . . . .	3
BordaTopk . . . . .	3
bRank . . . . .	4
convert . . . . .	5
Dcov . . . . .	5
DiffExpAnalysis . . . . .	6
Elastic . . . . .	7
experiment . . . . .	8
Extopk . . . . .	8
filterAndCompare . . . . .	9
getData . . . . .	9
GOBPenrichment . . . . .	10
Hoeffding . . . . .	11
IDA . . . . .	12

ImputeNormData . . . . .	13
KEGGenrichment . . . . .	13
Kendall . . . . .	14
Lasso . . . . .	15
MI . . . . .	15
Pearson . . . . .	16
ProMISe . . . . .	17
RDC . . . . .	18
Read . . . . .	18
ReadExtResult . . . . .	19
readHeader . . . . .	19
Spearman . . . . .	20
Standardise . . . . .	21
ValidateAll . . . . .	21
Validation . . . . .	22
ValidationT . . . . .	23
Zscore . . . . .	24

<b>Index</b>	<b>25</b>
--------------	-----------

---

miRLAB-package

*A dry lab for exploring miRNA-mRNA relationships*


---

## Description

Provide tools exploring miRNA-mRNA relationships, including popular miRNA target prediction methods using expression data, ensemble methods that integrate individual methods, functions to get data from online resources, functions to validate the results, and functions to conduct enrichment analyses.

## Details

Package: miRLAB  
Type: Package  
Version: 0.99  
Date: 2015-04-23  
License: GPL(>=2)

## Author(s)

Thuc Duy Le, Junpeng Zhang

Maintainer: Thuc Duy Le <Thuc.Le@unisa.edu.au>

## References

miRLAB: An R based dry lab for exploring miRNA-mRNA relationships

---

Borda	<i>Ensemble method for miRNA target prediction using Borda count election</i>
-------	---

---

**Description**

Use the Borda count election method to integrate the rankings from different miRNA target prediction methods

**Usage**

```
Borda(listCEmatrices)
```

**Arguments**

`listCEmatrices` a list of matrices that include the correlation coefficients/causal effects/scores resulting from different target prediction methods

**Value**

a matrix of ranking scores (averaging all the rankings from different methods). Columns are miRNAs and rows are mRNAs

**References**

1. Le, T.D., Zhang, J., Liu, L., and Li, J. (2015) Ensemble Methods for miRNA Target Prediction from Expression Data, Plos ONE.
2. Marbach, D., Costello, J.C., Kuffner, R., Vega, N.M., Prill, R.J., Camacho, D.M., Allison, K.R. and DREAM5 Consortium (2012). Wisdom of crowds for robust gene network inference. Nat. Methods, 9, 796-804.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
ps=Pearson(dataset, cause=1:3, effect=4:18)
ida=IDA(dataset, cause=1:3, effect=4:18)
borda=Borda(list(ps, ida))
```

---

BordaTopk	<i>Ensemble method for miRNA target prediction using Borda count election with topk targets</i>
-----------	---

---

**Description**

Use the Borda count election method to integrate the rankings from different miRNA target prediction methods, but only topk targets of each miRNA are included in the calculation. The targets outside the topk will be assigned a large and fixed rank, e.g. number of genes in the dataset.

**Usage**

```
BordaTopk(listCEmatrices, topk)
```

**Arguments**

- `listCEmatrices` a list of matrices that include the correlation/causal effects/scores resulting from a target prediction method
- `topk` number of targets of a miRNA to be included in the calculation (Borda count election)

**Value**

a matrix of ranking scores (averaging all the rankings from different methods). Columns are miRNAs and rows are mRNAs

**References**

Le, T.D., Zhang, J., Liu, L., and Li, J. (2015) Ensemble Methods for miRNA Target Prediction from Expression Data, Plos ONE.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
ps=Pearson(dataset, cause=1:3, effect=4:18)
ida=IDA(dataset, cause=1:3, effect=4:18)
borda=BordaTopk(list(ps, ida), topk=10)
```

---

bRank	<i>Extract topk predicted targets of a miRNA Rank all the targets of a miRNA and extract the topk targets</i>
-------	---

---

**Description**

Extract topk predicted targets of a miRNA Rank all the targets of a miRNA and extract the topk targets

**Usage**

```
bRank(CEmatrix, causeIndex, topk, downreg = TRUE)
```

**Arguments**

- `CEmatrix` the matrix of correlation/causal effect/score results with columns are miRNAs and rows are mRNAs
- `causeIndex` the column index of the miRNA that we would like to extract
- `topk` the number of targets being extracted
- `downreg` if TRUE the negative correlation/causal effect/score will be on the top of the ranking. This is to favour the negative regulations.

**Value**

a matrix with 3 columns, where the first column contains the miRNA, the second column contains the mRNAs and the last column contains the correlations/causal effects/scores

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
ps=Pearson(dataset, cause=1:3, effect=4:18)
miR200aTop10 = bRank(ps, 3, 10, TRUE)
```

---

 convert

---

*Convert miRNA symbols from a miRBase version to another*


---

**Description**

This function convert the miRNAs in the input file from the "source" miRBase version to the "Target" version. If users do not know the miRBase version of the input file, please set the source version to 0. The function will match the miRNAs in the input file to all miRBase versions to find the most likely miRBase version. Currently, we have versions 16-21.

**Usage**

```
convert(miRNAListFile, sourceV, targetV)
```

**Arguments**

**miRNAListFile** the input file containing a list of miRNA symbols in csv format

**sourceV** the miRBase version of the input miRNAs, e.g. 16. If users do not know the version, use 0.

**targetV** the miRBase version that we want to convert into, e.g. 21.

**Value**

A csv file in the working directory containing the converted miRNA symbols.

**Examples**

```
miRs=system.file("extdata", "ToymiRs.csv", package="miRLAB")
convert(miRs, 17, 21)
```

---

 Dcov

---

*miRNA target prediction with the Distance correlation method*


---

**Description**

Calculate the Distance correlation of each pair of miRNA-mRNA, and return a matrix of correlation coefficients with columns are miRNAs and rows are mRNAs.

**Usage**

```
Dcov(datacsv, cause, effect, targetbinding = NA)
```

**Arguments**

dataset	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
targetbinding	the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data will be intersected with the interactions in the target binding file.

**Value**

A matrix that includes the Distance correlation values. Columns are miRNAs, rows are mRNAs.

**References**

Szekely, G., Rizzo, M. and Bakirov, N. (2007) Measuring and testing independence by correlation of distances. *Ann. Stat.*, 35, 2769 - 94.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=Dcov(dataset, 1:3, 4:18)
```

---

DiffExpAnalysis

*Differentially expressed analysis*

---

**Description**

Find the top miRNAs and mRNAs that are differently expression between different conditions, e.g. cancer vs normal

**Usage**

```
DiffExpAnalysis(miR1, miR2, mR1, mR2, topkmiR, topkmR, p.miR, p.mR)
```

**Arguments**

miR1	the miRNA dataset for condition 1, e.g. cancer
miR2	the miRNA dataset for condition 2, e.g. normal
mR1	the mRNA dataset for condition 1, e.g. cancer
mR2	the mRNA dataset for condition 2, e.g. normal
topkmiR	the maximum number of miRNAs that we would like to extract, e.g. top 50 miRNAs.
topkmR	the maximum number of mRNAs that we would like to extract, e.g. top 2000 mRNAs.
p.miR	cutoff value for adjusted p-values when conducting differentially expressed analysis for miRNAs.
p.mR	cutoff value for adjusted p-values when conducting differentially expressed analysis for mRNAs.

**Value**

the dataset that includes differentially expressed miRNAs and mRNAs. columns are miRNAs and mRNAs and rows are samples

**References**

Smyth, G.K. (2005). Limma: linear models for microarray data. In Bioinformatics and computational biology solutions using R and Bioconductor (pp. 397-420). Springer New York.

---

Elastic	<i>miRNA target prediction with the Elastic-net regression coefficient method</i>
---------	---

---

**Description**

Calculate the Elastic-net regression coefficient of each pair of miRNA-mRNA, and return a matrix of correlation coefficients with columns are miRNAs and rows are mRNAs.

**Usage**

```
Elastic(datacsv, cause, effect, targetbinding = NA)
```

**Arguments**

datacsv	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
targetbinding	the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data will be intersected with the interactions in the target binding file.

**Value**

A matrix that includes the Elastic-net regression coefficients. Columns are miRNAs, rows are mRNAs.

**References**

1. Le, T.D., Zhang, J., Liu, L., and Li, J. (2015) Ensemble Methods for miRNA Target Prediction from Expression Data, under review.
2. Zou, H., & Hastie, T. (2005). Regularization and variable selection via the elastic net. J. R. Stat. Soc. Series B Stat. Methodol., 67, 301-320.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=Elastic(dataset, 1:3, 4:18)
```

---

experiment	<i>Function for validate the results from all 12 methods.</i>
------------	---

---

**Description**

Function for validate the results from all 12 methods.

**Usage**

```
experiment(allmethods, topk, Expgroundtruth, LFC, downreg)
```

**Arguments**

allmethods	A list of results (matrix with columns are miRNA and rows are mRNAs).
topk	Top k targets of each miRNA that will be extracted for validation
Expgroundtruth	The ground truth in .csv file for validation
LFC	log fold-change for validating the results using transfection experiments
downreg	If set to TRUE the negative effects will have higher ranks than the positives.

**Value**

The validation results for all 12 methods

---

Extopk	<i>Extract top k miRNA-mRNA interactions</i>
--------	--

---

**Description**

Rank the miRNA-mRNA interactions based on absolute values of the correlations/scores/causal effects, and return the topk interactions.

**Usage**

```
Extopk(cormat, topk)
```

**Arguments**

cormat	the correlation matrix that need to be extracted with columns are miRNAs and rows are mRNAs
topk	the number of interactions that need to be extracted.

**Value**

topk interactions

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
EMTresults=Pearson(dataset, 1:3, 4:18)
top10=Extopk(EMTresults, 10)
```



---

filterAndCompare	<i>Filter and compare the validation results from 12 methods Keep the miRNAs that have at least noVal confirmed targets and compare the validation results from all methods.</i>
------------------	--

---

**Description**

Filter and compare the validation results from 12 methods Keep the miRNAs that have at least noVal confirmed targets and compare the validation results from all methods.

**Usage**

```
filterAndCompare(allresults, noVal)
```

**Arguments**

allresults	the results from all methods generated from experiment function. This is a list.
noVal	Number of confirmed targets in each method (threshold) to filter. Records (miRNA) with less than this will be removed

**Value**

the validation results of all methods

**Examples**

```
print("result=filterAndCompare(allresults, 2)")
```

---

getData	<i>Get data from TCGA</i>
---------	---------------------------

---

**Description**

Download matched miRNA and mRNA expression profiles from TCGA using TCGA Assembler. In order to this function to work, users need to download the the file "DirectoryTraverseResult\_Jul-08-2014.rda" from [nugget.unisa.edu.au/Thuc/miRLAB/](http://nugget.unisa.edu.au/Thuc/miRLAB/) and place it in the working directory

**Usage**

```
getData(CancerName)
```

**Arguments**

CancerName	The name of cancer using abbreviation of cancer name as one of the followings: <ul style="list-style-type: none"> <li>• Adrenocortical carcinoma: ACC</li> <li>• Bladder urothelial carcinoma: BLCA</li> <li>• Breast invasive carcinoma: BRCA</li> <li>• Cervical squamous cell carcinoma and endocervical adenocarcinoma: CESC</li> <li>• Colon adenocarcinoma: COAD</li> </ul>
------------	---

- Lymphoid neoplasm diffuse large B-cell lymphoma: DLBC
- Esophageal carcinoma: ESCA
- Glioblastoma multiforme: GBM
- Head and neck squamous cell carcinoma: HNSC
- Kidney chromophobe: KICH
- Kidney renal clear cell carcinoma: KIRC
- Kidney renal papillary cell carcinoma: KIRP
- Acute myeloid leukemia: LAML
- Brain lower grade glioma: LGG
- Liver hepatocellular carcinoma: LIHC
- Lung adenocarcinoma: LUAD
- Lung squamous cell carcinoma: LUSC
- Ovarian serous cystadenocarcinoma: OV
- Pancreatic adenocarcinoma: PAAD
- Prostate adenocarcinoma: PRAD
- Rectum adenocarcinoma: READ
- Sarcoma: SARC
- Skin cutaneous melanoma: SKCM
- Stomach adenocarcinoma: STAD
- Thyroid carcinoma: THCA
- Uterine corpus endometrial carcinoma: UCEC
- Uterine carcinosarcoma: UCS

### Value

Dataset of matched miRNA and mRNA expression profiles

### References

Zhu, Y., Qiu, P., and Ji, Y. (2014). TCGA-Assembler: open-source software for retrieving and processing TCGA data. *Nat. Methods*, 11, 599-600.

### Examples

```
## Not run:  
BreastCancer=getData("BRCA")  
  
## End(Not run)
```

---

GOBPenrichment

*Functional enrichment analysis*

---

### Description

GO BP enrichment analysis for a gene list

### Usage

```
GOBPenrichment(Genes, Cutoff)
```

**Arguments**

Genes                    a list of gene symbols  
 Cutoff                    the significant level, e.g. 0.05

**Value**

a list of GO terms for the genes

**References**

Ashburner, M., Ball, C.A., Blake, J.A., Botstein, D., Butler, H., Cherry, J.M., Davis, A.P., Dolinski, K., Dwight, S.S., Eppig, J.T., Harris, M.A., Hill, D.P., Issel-Tarver, L., Kasarskis, A., Lewis, S., Matese, J.C., Richardson, J.E., Ringwald, M., Rubin, G.M. and Sherlock, G. (2000) Gene Ontology: tool for the unification of biology. Nat. Genet., 25, 25-29.

**Examples**

```
print("result = GOBPenrichment(genelist, 0.05)")
```

---

Hoeffding	<i>miRNA target prediction with the Hoeffding correlation coefficient method</i>
-----------	--

---

**Description**

Calculate the Hoeffding correlation coefficient of each pair of miRNA-mRNA, and return a matrix of correlation coefficients with columns are miRNAs and rows are mRNAs.

**Usage**

```
Hoeffding(datacsv, cause, effect, targetbinding = NA)
```

**Arguments**

datacsv                    the input dataset in csv format  
 cause                    the column range that specifies the causes (miRNAs), e.g. 1:35  
 effect                    the column range that specifies the effects (mRNAs), e.g. 36:2000  
 targetbinding            the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data will be intersected with the interactions in the target binding file.

**Value**

A matrix that includes the Hoeffding correlation coefficients. Columns are miRNAs, rows are mRNAs.

**References**

Hoeffding, W. (1948) A non-parametric test of independence. Ann. Math. Stat., 19, 546 - 57.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=Hoeffding(dataset, 1:3, 4:18)
```

IDA

*miRNA target prediction with the IDA method***Description**

Calculate the causal effect of each pair of miRNA-mRNA, and return a matrix of causal effects with columns are miRNAs and rows are mRNAs.

**Usage**

```
IDA(datacsv, cause, effect, pmethod = "original", alpha = 0.05,
    targetbinding = NA)
```

**Arguments**

datacsv	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
pmethod	choose different versions of the PC algorithm, including "original" (default) "stable", and "stable.fast"
alpha	significance level for the conditional independence test, e.g. 0.05.
targetbinding	the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data will be intersected with the interactions in the target binding file.

**Value**

A matrix that includes the causal effects. Columns are miRNAs, rows are mRNAs.

**References**

1. Le, T.D., Liu, L., Tsykin, A., Goodall, G.J., Liu, B., Sun, B.Y. and Li, J. (2013) Inferring microRNA-mRNA causal regulatory relationships from expression data. *Bioinformatics*, 29, 765-771.
2. Zhang, J., Le, T.D., Liu, L., Liu, B., He, J., Goodall, G.J. and Li, J. (2014) Identifying direct miRNA-mRNA causal regulatory relationships in heterogeneous data. *J. Biomed. Inform.*, 52, 438-47.
3. Maathuis, H.M., Colombo, D., Kalisch, M. and Buhlmann, P. (2010) Predicting causal effects in large-scale systems from observational data. *Nat. Methods*, 7, 247-249.
4. Maathuis, H.M., Kalisch, M. and Buhlmann, P. (2009) Estimating high-dimensional intervention effects from observational data. *Ann. Stat.*, 37, 3133-3164.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=IDA(dataset, 1:3, 4:18)
```

---

ImputeNormData	<i>Filter, impute, and normalise data.</i>
----------------	--

---

**Description**

Remove the genes (rows) that have more than  $r\%$  of missing data; use the impute package to fill in missing data, and finally normalise the data.

**Usage**

```
ImputeNormData(dataset, r)
```

**Arguments**

dataset	The input dataset in csv format. e.g. "EMT.csv" #'
r	The rate threshold to filter the records (genes). Genes with more than $r\%$ missing data will be removed.

**Value**

The processed dataset.

**References**

1. Hastie T, Tibshirani R, Narasimhan B and Chu G. impute: Imputation for microarray data. R package version 1.42.0.
2. Smyth, G.K. (2005). Limma: linear models for microarray data. In Bioinformatics and computational biology solutions using R and Bioconductor (pp. 397-420). Springer New York.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
impdata=ImputeNormData(dataset, 0.1)
```

---

KEGGenrichment	<i>Functional enrichment analysis KEGG enrichment analysis for a gene list</i>
----------------	--

---

**Description**

Functional enrichment analysis KEGG enrichment analysis for a gene list

**Usage**

```
KEGGenrichment(Genes, Cutoff)
```

**Arguments**

Genes	a list of gene symbols
Cutoff	the significant level, e.g. 0.05

**Value**

a list of pathways for the genes

**References**

Kanehisa, M. and Goto, S. (2000) KEGG: kyoto encyclopedia of genes and genomes. *Nucleic Acids Res.*, 28, 27-30.

**Examples**

```
print("result = KEGGenrichment(genelist, 0.05)")
```

---

Kendall	<i>miRNA target prediction with the Kendall correlation coefficient method</i>
---------	--

---

**Description**

Calculate the Kendall correlation coefficient of each pair of miRNA-mRNA, and return a matrix of correlation coefficients with columns are miRNAs and rows are mRNAs.

**Usage**

```
Kendall(datacsv, cause, effect, targetbinding = NA)
```

**Arguments**

datacsv	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
targetbinding	the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data will be intersected with the interactions in the target binding file.

**Value**

A matrix that includes the Kendall correlation coefficients. Columns are miRNAs, rows are mRNAs.

**References**

Kendall, M. (1938) A new measure of rank correlation. *Biometrika*, 30, 81 - 9.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=Kendall(dataset, 1:3, 4:18)
```

---

 Lasso

*miRNA target prediction with the Lasso method*


---

**Description**

Calculate the Lasso regression coefficient of each pair of miRNA-mRNA, and return a matrix of coefficients with columns are miRNAs and rows are mRNAs.

**Usage**

```
Lasso(datascv, cause, effect, targetbinding = NA)
```

**Arguments**

datascv	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
targetbinding	the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data with be intersected with the interactions in the target binding file.

**Value**

A matrix that includes the Lasso regression coefficients. Columns are miRNAs, rows are mRNAs.

**References**

1. Le, T.D., Zhang, J., Liu, L., and Li, J. (2015) Ensemble Methods for miRNA Target Prediction from Expression Data, submitted.
2. Tibshirani, R. (1996). Regression shrinkage and selection via the lasso. J. R. Stat. Soc. Series B Stat. Methodol., 267-288.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=Lasso(dataset, 1:3, 4:18)
```

---

 MI

*miRNA target prediction with mutual information method*


---

**Description**

Calculate the mutual information of each pair of miRNA-mRNA, and return a matrix of mutual information values with columns are miRNAs and rows are mRNAs.

**Usage**

```
MI(datascv, cause, effect, targetbinding = NA)
```

**Arguments**

datacsv	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
targetbinding	the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data with be intersected with the interactions in the target binding file.

**Value**

A matrix that includes the mutual information values. Columns are miRNAs, rows are mRNAs.

**References**

Moon, Y.I., Balaji, R., and Lall, U. (1995) Estimation of mutual information using kernel density estimators. Phys. Rev. E, 52, 2318 - 21.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=MI(dataset, 1:3, 4:18)
```

---

Pearson	<i>miRNA target prediction with the Pearson correlation coefficient method</i>
---------	--

---

**Description**

Calculate the Pearson correlation coefficient of each pair of miRNA-mRNA, and return a matrix of correlation coefficients with columns are miRNAs and rows are mRNAs.

**Usage**

```
Pearson(datacsv, cause, effect, targetbinding = NA)
```

**Arguments**

datacsv	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
targetbinding	the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data with be intersected with the interactions in the target binding file.

**Value**

A matrix that includes the Pearson correlation coefficients. Columns are miRNAs, rows are mRNAs.



## References

Pearson, K. (1920) Notes on the history of correlation. *Biometrika*, 13, 25 - 45.

## Examples

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=Pearson(dataset, 1:3, 4:18)
```

---

ProMISe

*miRNA target prediction with the ProMISe method*

---

## Description

Calculate the ProMISe score of each pair of miRNA-mRNA, and return a matrix of values with columns are miRNAs and rows are mRNAs.

## Usage

```
ProMISe(datascv, cause, effect, targetbinding = NA)
```

## Arguments

<code>datascv</code>	the input dataset in csv format
<code>cause</code>	the column range that specifies the causes (miRNAs), e.g. 1:35
<code>effect</code>	the column range that specifies the effects (mRNAs), e.g. 36:2000
<code>targetbinding</code>	the putative target, e.g. "TargetScan.csv". If <code>targetbinding</code> is not specified, only expression data is used. If <code>targetbinding</code> is specified, the prediction results using expression data will be intersected with the interactions in the target binding file.

## Value

A matrix that includes the ProMISe scores. Columns are miRNAs, rows are mRNAs.

## References

Li, Y., Liang, C., Wong, K.C., Jin, K., and Zhang, Z. (2014). Inferring probabilistic miRNA - mRNA interaction signatures in cancers: a role-switch approach. *Nucleic Acids Res.*, 42, e76-e76.

## Examples

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=ProMISe(dataset, 1:3, 4:18)
```

---

RDC	<i>miRNA target prediction with the Randomized Dependence Coefficient method</i>
-----	--

---

### Description

Calculate the Randomized Dependence coefficient of each pair of miRNA-mRNA, and return a matrix of coefficients with columns are miRNAs and rows are mRNAs.

### Usage

```
RDC(datacsv, cause, effect, targetbinding = NA)
```

### Arguments

datacsv	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
targetbinding	the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data will be intersected with the interactions in the target binding file.

### Value

A matrix that includes the correlation coefficients. Columns are miRNAs, rows are mRNAs.

### Examples

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=RDC(dataset, 1:3, 4:18)
```

---

Read	<i>Read dataset from csv file</i>
------	-----------------------------------

---

### Description

Read dataset from csv file

### Usage

```
Read(dataset)
```

### Arguments

dataset	The input dataset in csv format
---------	---------------------------------

### Value

dataset in matrix format

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
data=Read(dataset)
```

---

ReadExtResult	<i>Read results from other methods</i>
---------------	--

---

**Description**

Read the results predicted by external methods (methods that are not in this package and may not be implemented in R). Consequently, we can compare the results predicted by the external methods and results predicted by the methods in the miRLAB package.

**Usage**

```
ReadExtResult(datacsv, cause, effect, ExtCEcsv)
```

**Arguments**

datacsv	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
ExtCEcsv	score matrix predicted by an external matrix with columns are miRNAs and rows are mRNAs.

**Value**

a matrix of scores predicted by an external matrix and ready for further validation and comparison tasks.

**Examples**

```
print("GenemiR=ReadExtResult(dataset, cause=1:3, effect=4:18, 'genemirresults.csv')")
```

---

readHeader	<i>Read the header of the dataset</i>
------------	---------------------------------------

---

**Description**

Read the header of the dataset

**Usage**

```
readHeader(dataset)
```

**Arguments**

dataset	the character string of the names of the dataset in csv format, e.g. "ToyEMT.csv"
---------	---

**Value**

the header of the dataset

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
header=readHeader(dataset)
```

---

Spearman	<i>miRNA target prediction with the Spearman correlation coefficient method</i>
----------	---

---

**Description**

Calculate the Spearman correlation coefficient of each pair of miRNA-mRNA, and return a matrix of correlation coefficients with columns are miRNAs and rows are mRNAs.

**Usage**

```
Spearman(datacsv, cause, effect, targetbinding = NA)
```

**Arguments**

datacsv	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
targetbinding	the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data will be intersected with the interactions in the target binding file.

**Value**

A matrix that includes the Spearman correlation coefficients. Columns are miRNAs, rows are mRNAs.

**References**

Spearman, C. (1904) General intelligence, objectively determined and measured. Am. J. Psychol., 15, 201 - 92.

**Examples**

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
results=Spearman(dataset, 1:3, 4:18)
```

---

Standardise	<i>Standardise the dataset Standardise the dataset to have mean=0 and std=1 in each column.</i>
-------------	---

---

**Description**

Standardise the dataset Standardise the dataset to have mean=0 and std=1 in each column.

**Usage**

```
Standardise(dataset)
```

**Arguments**

dataset	The input dataset in csv format. e.g. "ToyEMT.csv". The first column is the sample name.
---------	--

**Value**

The standardised dataset.

**Examples**

```
## Not run:
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
stdata=Standardise(dataset)

## End(Not run)
```

---

ValidateAll	<i>Validate the targets of all miRNA using both experimentally confirmed and transfection data</i>
-------------	--

---

**Description**

Given the predicted target of all miRNA, the function returns a list of targets of each miRNA that are confirmed based on the experimentally validated interactions or curated transfection data. Users need to download the file logFC.imputed.rda from [nugget.unisa.edu.au/Thuc/miRLAB/](http://nugget.unisa.edu.au/Thuc/miRLAB/) and place it in the working directory (this file is obtained from the TargetScoreData package)

**Usage**

```
ValidateAll(CEmatrix, topk, groundtruth, LFC, downreg = TRUE)
```

**Arguments**

CEmatrix	the matrix of correlation/causal effects/scores with columns are miRNAs and rows are mRNAs
topk	the number of targets of each miRNA that are being validated.
groundtruth	the csv file containing the ground truth.
LFC	the log fold change threshold for the transfection data. The targets that have the absolute value of log fold change greater than the LFC will be regarded as the confirmed targets.
downreg	if TRUE the negative correlation/causal effect/score values will be ranked on the top of the ranking. This is to favour the down regulations.

**Value**

a list of matrices that contains the confirmed interactions by both provided ground truth and built-in transfection data.

**Examples**

```
print("ps=Pearson(dataset, cause=1:3, effect=4:18)")
print("results=ValidateAll(ps, 10, groundtruth, LFC=0.5, downreg=TRUE)")
```

---

 Validation

---

*Validate the targets of a miRNA*


---

**Description**

Given the predicted target of a miRNA, the function returns a list of targets that are experimentally confirmed based on the provided ground truth. Users can provide their own ground truth or use the built-in ground truth which is the union of Tarbase, miRTarbase, miRecords, and miRWalk.

**Usage**

```
Validation(topkList, datacsv)
```

**Arguments**

topkList	a matrix with 3 columns. The first column is the miRNA name, the second contains the target mRNAs, and the third contains the correlation values/ causal effects/ scores
datacsv	the ground truth for the validation. The ground truth is a matrix with 2 columns, where the first column is the miRNA and the second is the mRNA.

**Value**

a matrix in the same format of the input matrix put only contains the confirmed interactions.

## Examples

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")
ps=Pearson(dataset, cause=1:3, effect=4:18)
miR200aTop10=bRank(ps, 3, 10, TRUE)
groundtruth=system.file("extdata", "Toygroundtruth.csv", package="miRLAB")
miR200aTop10Confirmed = Validation(miR200aTop10, groundtruth)
```

---

ValidationT

*Validate the targets of a miRNA using transfection data*

---

## Description

Given the predicted target of a miRNA, the function returns a list of targets that are confirmed based on the curated transfection data. Users need to download the file `logFC.imputed.rda` from `nugget.unisa.edu.au/Thuc/miRLAB/` and place it in the working directory (this file is obtained from the `TargetScoreData` package)

## Usage

```
ValidationT(topkList, LFC)
```

## Arguments

<code>topkList</code>	a matrix with 3 columns. The first column is the miRNA name, the second contains the target mRNAs, and the third contains the correlation values/ causal effects/ scores
<code>LFC</code>	the log fold change threshold. The targets that have the absolute value of log fold change greater than the LFC will be regarded as the confirmed targets.

## Value

a matrix in the same format of the input matrix put only contains the confirmed interactions.

## References

1. Le, T.D., Zhang, J., Liu, L., and Li, J. (2015) Ensemble Methods for miRNA Target Prediction from Expression Data, under review.
2. Li Y, Goldenberg A, Wong K and Zhang Z (2014). A probabilistic approach to explore human microRNA targetome using microRNA-overexpression data and sequence information. *Bioinformatics*, 30(5), pp. 621-628. <http://dx.doi.org/10.1093/bioinformatics/btt599>.

## Examples

```
print("ps=Pearson(dataset, cause=1:35, effect=36:1189)")
print("miR200aTop100=bRank(ps, 11, 100, TRUE)")
print("miR200aTop100Confirmed = ValidationT(miR200aTop100, 1.0)")
```

---

Zscore

*miRNA target prediction with the Z-score method*

---

### Description

Calculate the Z-score value of each pair of miRNA-mRNA, and return a matrix of values with columns are miRNAs and rows are mRNAs.

### Usage

```
Zscore(datacsv, cause, effect, targetbinding = NA)
```

### Arguments

datacsv	the input dataset in csv format
cause	the column range that specifies the causes (miRNAs), e.g. 1:35
effect	the column range that specifies the effects (mRNAs), e.g. 36:2000
targetbinding	the putative target, e.g. "TargetScan.csv". If targetbinding is not specified, only expression data is used. If targetbinding is specified, the prediction results using expression data with be intersected with the interactions in the target binding file.

### Value

A matrix that includes the Z-score values. Columns are miRNAs, rows are mRNAs.

### References

Prill, R.J., Marbach, D., Saez-Rodriguez, J., Sorger, P.K., Alexopoulos, L.G., Xue, X., Clarke, N.D., Altan-Bonnet, G. and Stolovitzky, G. (2010) Towards a rigorous assessment of systems biology models: the DREAM3 challenges. PLoS One, 5, e9202.

### Examples

```
dataset=system.file("extdata", "ToyEMT.csv", package="miRLAB")  
results=Zscore(dataset, 1:3, 4:18)
```



# Index

\*Topic **package**  
  miRLAB-package, 2

\*Topic  
  miRLAB-package, 2

Borda, 3  
BordaTopk, 3  
bRank, 4

convert, 5

Dcov, 5  
DiffExpAnalysis, 6

Elastic, 7  
experiment, 8  
Extopk, 8

filterAndCompare, 9

getData, 9  
GOBPenrichment, 10

Hoeffding, 11

IDA, 12  
ImputeNormData, 13

KEGGenrichment, 13  
Kendall, 14

Lasso, 15

MI, 15  
miRLAB (miRLAB-package), 2  
miRLAB-package, 2

Pearson, 16  
ProMISe, 17

RDC, 18  
Read, 18  
ReadExtResult, 19  
readHeader, 19

Spearman, 20

Standardise, 21

ValidateAll, 21  
Validation, 22  
ValidationT, 23

Zscore, 24