

Package ‘affyio’

October 15, 2018

Version 1.50.0

Title Tools for parsing Affymetrix data files

Author Ben Bolstad <bmb@bmbolstad.com>

Maintainer Ben Bolstad <bmb@bmbolstad.com>

Depends R (>= 2.6.0)

Imports zlibbioc, methods

Description Routines for parsing Affymetrix data files based upon file format information. Primary focus is on accessing the CEL and CDF file formats.

License LGPL (>= 2)

URL <https://github.com/bmbolstad/affyio>

biocViews Microarray, DataImport, Infrastructure

LazyLoad yes

git_url <https://git.bioconductor.org/packages/affyio>

git_branch RELEASE_3_7

git_last_commit 911ea4f

git_last_commit_date 2018-04-30

Date/Publication 2018-10-15

R topics documented:

check.cdf.type	2
get.celfile.dates	2
read.cdffile.list	3
read.celfile	4
read.celfile.header	4
read.celfile.probeintensity.matrices	5

Index	6
--------------	----------

check.cdf.type *CDF file format function*

Description

This function returns a text string giving the file format for the supplied filename

Usage

```
check.cdf.type(filename)
```

Arguments

filename fullpath to a cdf file

Value

Returns a string which is currently one of:

text	the cdf file is of the text format
xda	the cdf file is of the binary format used in GCOS
unknown	the parser can not handle this format or does not recognize this file as a CDF file

Author(s)

B. M. Bolstad <bmb@bmbolstad.com>

get.celfile.dates *Extract Dates from CEL files*

Description

This function reads the header information for a series of CEL files then extracts and returns the dates.

Usage

```
get.celfile.dates(filenamees, ...)
```

Arguments

filenamees a vector of characters with the CEL filenames. May be fully pathed.
... further arguments passed on to [read.celfile.header](#).

Details

The function uses [read.celfile.header](#) to read in the header of each file. The ScanDate component is then parsed to extract the date. Note that an assumption is made about the format. Namely, that dates are in the Y-m-d or m/d/y format.

Value

A vector of class `Date` with one date for each cel file.

Author(s)

Rafael A. Irizarry <rafa@jimmy.harvard.edu>

See Also

See Also as `read.celfile.header`.

`read.cdffile.list` *Read CDF file into an R list*

Description

This function reads the entire contents of a cdf file into an R list structure

Usage

```
read.cdffile.list(filename, cdf.path = getwd())
```

Arguments

<code>filename</code>	name of CDF file
<code>cdf.path</code>	path to cdf file

Details

Note that this function can be very memory intensive with large CDF files.

Value

returns a list structure. The exact contents may vary depending on the file format of the cdf file (see `check.cdf.type`)

Author(s)

B. M. Bolstad <bmb@bmbolstad.com>

read.celfile *Read a CEL file into an R list*

Description

This function reads the entire contents of a CEL file into an R list structure

Usage

```
read.celfile(filename,intensity.means.only=FALSE)
```

Arguments

filename name of CEL file
intensity.means.only If TRUE then read on only the MEAN section in INTENSITY

Details

The list has four main items. HEADER, INTENSITY, MASKS, OUTLIERS. Note that INTENSITY is a list of three vectors MEAN, STDEV, NPIXELS. HEADER is also a list. Both of MASKS and OUTLIERS are matrices.

Value

returns a list structure. The exact contents may vary depending on the file format of the CEL file

Author(s)

B. M. Bolstad <bmb@bmbolstad.com>

read.celfile.header *Read header information from cel file*

Description

This function reads some of the header information (appears before probe intensity data) from the supplied cel file.

Usage

```
read.celfile.header(filename,info=c("basic","full"),verbose=FALSE)
```

Arguments

filename name of CEL file. May be fully pathed
info A string. basic returns the dimensions of the chip and the name of the CDF file used when the CEL file was produced. full returns more information in greater detail.
verbose a [logical](#). When true the parsing routine prints more information, typically useful for debugging.

Value

A list data structure.

Author(s)

B. M. Bolstad <bmb@bmbolstad.com>

read.celfile.probeintensity.matrices

Read PM or MM from CEL file into matrices

Description

This function reads PM, MM or both types of intensities into matrices. These matrices have all the probes for a probeset in adjacent rows

Usage

```
read.celfile.probeintensity.matrices(filenamees, cdfInfo, rm.mask=FALSE, rm.outliers=FALSE, rm.extra=FALSE)
```

Arguments

filenamees	a character vector of filenames
cdfInfo	a list with items giving PM and MM locations for desired probesets. In same structure as returned by make.cdf.package
rm.mask	a logical . Return these probes as NA if there are in the [MASK] section of the CEL file
rm.outliers	a logical . Return these probes as NA if there are in the [OUTLIERS] section of the CEL file.
rm.extra	a logical . Return these probes as NA if there are in the [OUTLIERS] section of the CEL file.
verbose	a logical . When true the parsing routine prints more information, typically useful for debugging.
which	a string specifying which probe type to return

Value

returns a **list** of **matrix** items. One matrix contains PM probe intensities, with probes in rows and arrays in columns

Author(s)

B. M. Bolstad <bmb@bmbolstad.com>

Index

*Topic **IO**

- check.cdf.type, 2
- get.celfile.dates, 2
- read.cdffile.list, 3
- read.celfile, 4
- read.celfile.header, 4
- read.celfile.probeintensity.matrices,
5

check.cdf.type, 2, 3

Date, 3

get.celfile.dates, 2

list, 5

logical, 4, 5

make.cdf.package, 5

matrix, 5

read.cdffile.list, 3

read.celfile, 4

read.celfile.header, 2, 3, 4

read.celfile.probeintensity.matrices,
5